G2 chart

Honeywell

PSTN Line for built in communicator

A228



RS232

Computer, printer

A229



External communicator

Trigger lead

Standard 6-core cable, 50m maximum

Common features for G2-20 and G2-44+



12V battery
17Ah on G2-44+
12Ah on G2-20

12 4

RS485 Bus

Keypad or keyprox (x4)



CP050-00-01/
CP051-00-01
(MK8 Keypad/prox)


CP037/CP038
(MK7 Keypad/prox)

Max Badge reader (x1)




MX04

RIO:
8 zones and
4 outputs
with
power supply
or in
standalone
box (x4 on
G2-44+, x1
on G2-20)



P026


8
4



C072

8
4


Ethernet module (x1)



E080-2

IP network

RF Portal (x2)



C079-2



Remote Servicing Suite
Downloader

Two twisted pairs screened cable, Belden 8723 or equivalent. 1km maximum. (100m is using standard 4 core cable)

Standard 4-core cable, 100m Maximum. Star or daisy chain wiring structure

Honeywell wired series

PIRs IntelliSense®



IS21X Range

DUAL TEC®



DT7000 Range

Glassbreak Flexguard®



FG Range

Extra features for G2-44+ version



A235

2-way voice (x1)


ECP Bus



2012-172*

6160 keypad (x4)

8
4



2011-161*

ECP zone expander
8 zones and
4 outputs (x3)

*Supports legacy equipment only

Wireless sensors range



DT8M
DUAL TEC® Motion Sensor



FG8M
Acoustic Glassbreak Sensor



SHK8M/SHKC8M
Piezo Shock Sensor



DET8M
Flood & Temperature Sensor



DO800M
Small Door Contact



DODT800GY-B /
DODT800M
Door Contact



IR8M/IRPI8M
PIR Sensor/
Pet Immune Version



DF8M
Smoke Detector



TCB8M
Remote Keyfob



TCBPA8M-1
PA Button



TCC8M
Two-way Keyfob

NOTE: New sensors valid for G2 panel firmware from version V1.5 onwards.
Compatible across the Galaxy® Range

Visit www.honeywell.com/security/uk/intruder for details of the full range of compatible wired and wireless peripherals.