

470-12

WATER SENSOR



Honeywell's 470-12 is designed to allow water or any conductive non-flammable liquid to be detected with low voltage and low current. It can monitor up to two sensor probes simultaneously.

Ideal for basements, laundry rooms and kitchen or anywhere flooding is a possibility and early warning is desirable to prevent damage.

Features

- Can monitor up to 2 sensing probes (470PB) simultaneously
- Selectable (Hi or Low) sensitivity setting
- Includes One 470PB external water probe
- Includes Form C output relay

Specifications

Power

- 12 Volts DC

Probe Current on Activation

- 1.0 milliamps

Total Current Draw on Activation

- 40 milliamps

Alarm Output

- SPDT Form C Relay Contact

Relay Rating

- 5 amps

Sensitivity

- The 470-12 is provided with two sensitivity setting for greater flexibility.

Dimensions

- Module size: 4"W x 2 1/4"H x 2 3/4"D (101mm x 57mm x 70mm)
- Probe size: 2"W x 1"H x 1/2"D (51mm x 25mm x 13mm)

Ordering

470-12
470PB

12 VDC Water Sensor (1 probe included)
Additional External Water Probe

Find out more:

Fax : +44 (0) 1698 738300
www.honeywell.com/security/uk

-
Fax : +31 (0) 299-410201
www.honeywell.com/security/nl

Honeywell Security & Data Collection

Newhouse Industrial Estate
Motherwell, Lanarkshire, ML1 5SB
Scotland
Tel :+44 (0) 1698 738200

Ampèrestraat 41
1446 TR Purmerend
The Netherlands
Tel : +31 (0) 299-410200
www.honeywell.com

Honeywell