

GFPS-6S

Intelligent Power Module

General

The GFPS-6S intelligent power module by Gamewell-FCI is a cost-effective power supply that delivers 6 amps of notification appliance circuit power and built-in synchronization for appliances from the following manufacturers:

- SystemSensor®
- Gentex®
- Faraday™
- AMSECO®
- Wheelock®

The GFPS-6S's advanced microprocessor design is years ahead of the competition. Its switch mode power supply design offers up to 50% more efficiency than competitive linear mode power supplies.

The GFPS-6S is a 6 amp notification power expander that provides its own AC power connection, battery charging circuit, and backup battery for use with the Gamewell-FCI's GWF-7075 fire alarm control panels (FACPs). The GFPS-6S is the cost-effective solution used for powering notification appliances required by the Americans with Disabilities Act (ADA). The GFPS-6S has a built-in ANSI cadence pattern. The output circuits can be programmed as notification appliance circuits, or as auxiliary power (configurable for constant, resettable, or door holder power).

Installation

The GFPS-6S cabinet is surface mounted.

Compatibility

The GFPS-6S is compatible with the following FACP:

- GWF-7075 Intelligent Fire Panel

ORDERING INFORMATION

GFPS-6S: Intelligent Power Module




GFPS-6S


FEATURES & BENEFITS

- UL® Listed for 6 amps of notification power
- The power supply's advanced switch mode design reduces damaging heat and manages power up to 50% more efficiently than other systems
- Offers a built-in synchronization for appliances from Gentex, Faraday, AMSECO, System Sensor, and Wheelock
- Provides 24 VDC filtered output voltage
- 3 amps per output circuit
- Includes four power-limited notification outputs:
 - Two Class A
 - Four Class B
 - One Class A
 - Two Class B
- Has a built-in ANSI Cadence pattern output capability
- The NACs are programmable as notification appliance circuits, or as auxiliary power to be used as constant, resettable, or door holder power
- Contains a ground fault detector
- Communicates to the FACP via 4-wire SBUS (wire runs up to 6000 ft)
- Features an AC loss delay option that shuts off power to the non-essential high current accessories like the magnetic door holders
- Built with a lightweight design that offers a simple installation and reduces shipping costs

NOTE 1: USE 4 OUTPUTS PROGRAMMABLE AS NOTIFICATION APPLIANCE CIRCUITS, OR AS AUXILIARY POWER.



NOTE 2: PROGRAM AUXILIARY POWER TO BE ANY OF THE FOLLOWING:
- CONSTANT
- RESETTABLE
- DOOR HOLDER POWER



NOTE 3: USE RS-485 COMMUNICATION TO A COMPATIBLE GWF-7075 FIRE ALARM CONTROL PANEL.



Figure 1 GFPS-6S Panel Setup

GFPS-6S Technical Specifications

SYSTEMS

Physical

Height: 16" (40.6 cm)
Width: 12.25" (30.9 cm)
Depth: 3" (7.6 kg)
Shipping Weight: 8.7 lbs. (3.9 kg)

Electrical

AC Input: 120 VAC at 2.7A
Output: 24 VDC at 6A
Alarm Current: 160 mA
Standby Current: 40 mA
Notification/Auxiliary Power Circuits: 4
Output Configuration: 2 Class A (Style Z)
4 Class B (Style Y)
1 Class A & 2 Class B
Amps Per Output Circuit: 3.0 (6.0 amps total)
Notification Circuit Output: 20.4 – 27.3 VDC @ 3.0A each
End-of-Line Resistance: 4.7k W EOL resistor required on each
Class B circuit Battery Charging Capacity: 7.0 – 35.0 AH

TEMPERATURE AND HUMIDITY RANGES

This system meets NFPA requirements for operation at 0 – 49°C/32 – 120°F and at a relative humidity 93% ± 2% RH (noncondensing) at 32°C ± 2°C (90°F ± 3°F). However, the useful life of the system's standby batteries and the electronic components may be adversely affected by extreme temperature ranges and humidity. Therefore, it is recommended that this system and its peripherals be installed in an environment with a normal room temperature of 15 – 27°C/60 – 80°F.

Standards

The GFPS-6S is designed to comply with the following standard:

UL Standard: 864 9th Edition and 1481

Agency Listings and Approvals

These listings and approvals apply to the modules specified in this document. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. Consult factory for latest listing status.

UL: 864

1481 listed

CSFM approved

MEA approved

ISO 9001 Certification

For a complete listing of all compliance approvals and certifications, please visit:

<http://www.gamewell-fci.com/en-US/documentation/Pages/Listings.aspx>

AMSECO™ is a trademark of AMSECO.

Faraday™ is a trademark of Faraday.

Gamewell-FCI® and Honeywell® are registered trademarks and Farenhyte™ is a trademark of Honeywell International, Inc.

Gentex® is a registered trademark of Gentex Corporation.

Microsoft, Windows®, and the Windows Logo® are registered trademarks or trademarks of Microsoft Corporation.

System Sensor® is a registered trademark of System Sensor.

UL® is a registered trademark of Underwriter's Laboratories Inc.

Wheelock® is a registered trademark of Wheelock, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For more information

Learn more about Gamewell-FCI's GFPS-6S and other products available by visiting www.Gamewell-FCI.com

Honeywell Gamewell-FCI

12 Clintonville Road
Northford, CT 06472-1610
203.484.7161
www.honeywell.com

9021-601005 | A | 11/17
©2017 Honeywell International Inc.

Honeywell