



by Honeywell

Textual Visual Notification

Description

The LEDArray Series Indoor Displays are LED message centers designed for light industrial, commercial, and office use. They quickly display large amounts of information in eight colors and three rainbow effects (red only versions are also available). These message centers are among the brightest and sharpest indoor displays available.

Messages are entered through a wireless, remote control keyboard. The wireless, remote control keyboard is as easy to use as an ordinary calculator. The exclusive, three-step message entry with Automode programming eliminates the user's need to learn complicated programming procedures. Within seconds, the user can create exciting visual messages that cannot be ignored. Ten preset mass notification messages are provided.

In applications requiring multiple units to communicate important information, Alpha displays can be networked and connected to a PC to form a powerful integrated visual information system. These displays can be used throughout your plant or business facility. Use the Contact Interface Panel for Fire Alarm or Manual type activation.

Specifications

Case dimensions (with power supply):	28.9"L x 2.1"D x 4.5"H (73.4 L x 5.3 D x 11.4 H cm)
Approximate weight:	6.25 lbs (2.83 kg)
Display dimensions	27"L x 2.1"H (68.6 L x 5.3 H cm)
Display array:	90 x 7 pixels
Characters displayed in one line:	15 characters
Display Memory:	7,000 characters
Pixel Size (Diameter):	0.2" (0.5 cm)
Built-in Animation Displays:	<ul style="list-style-type: none"> • Cherry Bomb Exploding • Welcome and Thank You • Don't Drink and Drive • Fireworks • Slot Machine • No Smoking • Running Animal
Pixel (LED) Color:	Red
Serial Computer Interface:	RS232 and RS485 (multi-drop networking for up to 255 displays)

Alpha-215 Indoor Display



Alpha-215 Indoor Display

Features

- Provides simple point-to-point RS232 communications
- Supports multi-drop RS485 connections
- Uses a character size of: 2.1" (5.13 cm)
- Offers a one year USA factory warranty.
- Stores and displays over 80 messages
- Has 8 colors and 3 rainbow effects
- Includes 6 character fonts
- Contains an optional Ethernet LAN connections

An ISO 9001-2000 Company



GAMEWELL-FCI

12 Clintonville Road, Northford, CT 06472-1610 USA • Tel: (203) 484-7161 • Fax: (203) 484-7118

Specifications are for information only, are not intended for installation purposes, and are subject to change without notice. No responsibility is assumed by Gamewell-FCI for their use.

©2012 by Honeywell International Inc. All rights reserved.

www.gamewell-fci.com

9021-60729 Rev. A page 1 of 2

Specifications (Continued)

Options: Ethernet LAN adapter
Center-to-Center Pixel Spacing (Pitch): 0.3" (0.8 cm)
Power: Input: 5A, 35W, 7 VAC, 120 VAC or 230 VAC adapter available
Character Size: 2.1" (5.3 cm)
Power Cord Length: 10 ft. (3m)
Character Set: Block (sans serif), decorative (serif), upper/ lower case, slim/wide
Keyboard: Handheld, Eurostyle, IR Remote operated
Memory Retention: One month typical
Case Material: Molded plastic
Message Capacity: 81 different messages can be stored and displayed
Limited Warranty: One-year parts and labor, factory servicing

Message

Operating Modes: 25 consisting of the following:

- Automode
- Interlock
- Scroll
- Spray-On
- Switch
- Wipe (6 directions)
- Starburst
- Condensed Rotate
- Continuous message entry with automatic centering in any mode
- Programmable logos and graphics
- Five hold speeds
- Hold
- Sparkle-On
- Twinkle
- Slide-Across
- Slash
- Roll (6 directions)
- Rotate
- Snow

Operating

Temperature: 32° to 120°F, 0° to 49°C
Humidity Range: 0% to 95% non-condensing
Mounting: Hardware to accommodate ceiling or wall mounting

Ordering Information

Part Number	Description
Alpha-215	Programmable LED array, 2.5" x 26" (6.35 cm x 66.04 cm) display with remote control.
MNS-Control8	FACP interface for LED arrays, 8 messages.
MNS-Control16	FACP interface for LED arrays, 16 messages.
MNS-Cable	1' (0.30m) RS-485 connector cable for MNS Control

GAMEWELL-FCI