

MCS-CO3

Addressable Carbon Monoxide Detectors

MCS-CO3 is an intelligent, addressable carbon monoxide (CO) detector with integral communication to provide point location for alarm communication and selective maintenance.

This detector has point ID capability that enables each detector address to be set with rotary address switches providing exact device locations. The modern design and expanded color options support contemporary aesthetic demands. In addition, each detector is constructed for exceptional installation and maintenance efficiency.

MCS-CO3 incorporates carbon monoxide (CO) detection principles meeting the UL 2075 standard for system-connected life safety carbon monoxide detection. As an addressable detector, additional modules are not needed for point ID which streamlines the installation process. This allows you to upgrade your addressable fire system to meet new CO code requirements in applications with fuel burning equipment such as furnace areas and laundry rooms.

Released through the incomplete burning of various fuels, CO is a colorless, odorless and deadly gas that is virtually impossible to detect with the human senses. Because the potential exists for dangerous levels of CO to accumulate in almost any building, legislation mandating the use of CO detection in commercial spaces continues to grow.

MCS-CO3 is recommended for use in conjunction with B200S intelligent sounder bases. These bases can generate a Temp 4 pattern for CO alarm indication. They recognize the System Sensor® synchronization protocol.



MCS-CO3 installed in B200S-WH sounder base

FEATURES AND BENEFITS

- Intelligent CO detector
- Automatic drift compensation of CO cell
- RealTest® CO testing capability
- UL 2075 listed
- Audible signal for CO alarm when used with B200S series base
- 10-year CO cell with end-of-life warning and fault
- New modern profile
- Expanded color options with black and ivory color kits

Honeywell



MCS-CO3 TECHNICAL SPECIFICATIONS

PHYSICAL

Height: 2.7 in. (69 mm) installed in B200S series sounder base

Diameter: 6.875 in. (175 mm) installed in B200S series sounder bases

Weight: 3.4 oz. (95 g)

Color: White

ENVIRONMENTAL

Operating Humidity Range: 15% to 90% Relative Humidity, Non-condensing

Operating Temperature Range: 32°F to 122°F (0°C to 50°C)

ELECTRICAL

Operating Voltage Range: 15 to 32 VDC

Operating Current @ 24 VDC: 200 uA (one communication every 5 seconds with green LED blink on communication)

Maximum Alarm Current: 2 mA @ 24 VDC (one communication every 5 seconds with red LED solid on)

Maximum Current: 4.5 mA @ 24 VDC (one communication every 5 seconds with amber LED solid on)

Isolator Load Rating: 0.0063

SYSTEM COMPATIBILITY

Communication Protocol: Velociti®

E3 Series: Firmware Version 4.10 or higher.

S3 Series: Firmware Version 1.21 or higher.

NGA: Firmware Version 4.01 or higher.

CAMWorks: Version 3.53.003 or higher.

FocalPoint®: Version 4.52 or higher.

CO MONITORING

UL Standard Reference: Alarm Thresholds

Parts Per Million	Detector Response Time
70 ± 5ppm	60 – 240 min.
150 ± 5ppm	10 – 50 min.
400 ± 10ppm	4 – 15 min.

Per UL standard 2075, MCS-CO3 has been tested to the sensitivity limits defined in UL 2034.

ORDERING INFORMATION

CO Detectors

MCS-CO3: Intelligent addressable carbon monoxide detector, white, UL listed

Bases

B501-WHITE: 4" Mounting base, white, UL-listed

B501-WHITE-BP: 4" Mounting base, white, UL-listed, bulk-pack 10

B501-BL: 4" Mounting base, black, UL-listed

B501-IV: 4" Mounting base, ivory, UL-listed

B300-6: 6" Flanged mounting base, UL-listed, white

B300-6-BP: 6" Flanged mounting base, UL-listed, white, bulk-pack 10

B300-6-IV: 6" Flanged mounting base, UL-listed, ivory

B200S-WH: Intelligent sounder base, white, UL-listed

B200S-IV: Intelligent sounder base, ivory, UL-listed

B200S-LF-WH: Intelligent sounder base, low-frequency, white, UL-listed

B200S-LF-IV: Intelligent sounder base, low-frequency, ivory, UL-listed

B224BI-WH: Intelligent isolator base, white, UL-listed

B224BI-IV: Intelligent isolator base, ivory, UL-listed

B224RB-WH: Intelligent relay base, white, UL-listed

B224RB-IV: Intelligent relay base, ivory, UL-listed

Accessories

SMB600: Surface Mounting Kit (flanged), ivory

TR300: Trim ring, white. (TR300-IV is ivory.)

CK300-CO: CO Color Kit (includes cover and trim ring), white. (CK300-CO-IV is ivory; CK300-CO-BL is black.)

RA100Z: Remote LED annunciator, UL-listed

M02-04-00: Detector test magnet

M02-09-00: Telescoping test magnet

AGENCY LISTINGS AND APPROVALS

UL Listed: S1195

CSFM: 5278-1703:0509

GameWell-FCI®, Velociti®, CAMWorks®, E3 Series®, FocalPoint®, System Sensor®, and RealTest® are registered trademarks of Honeywell International Inc.

©2020 by Honeywell International Inc. All rights reserved.

Unauthorized use of this document is strictly prohibited.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

Country of origin: Mexico

Honeywell GameWell-FCI

12 Clintonville Road
Northford, CT 06472-1610
203.484.7161
www.gamewell-fci.com

9021-62020 | B | 11/20
©2020 Honeywell International Inc.

