OMNI FIBERGLASS ANTENNA
763 - 869 MHz

BDA-FA-763869-2-2

Product Features

- Omnidirectional
- Regular ceiling installation, use conveniently



Electric Specifications	Value
Frequency Range	763-869 MHz
Bandwidth	106 MHz
Gain	2.5 dBi
VSWR	≤2.0
Polarization	Vertical
Vertical Beamwidth	30°
Input Impedance	50 Ω
Max. Input Power	100 W
Lightning Protection	DC Ground

Mechanical Specifications	Value
Connector Type	N-Type Female
Dimensions	350 mm
Support Pole Diameter	φ35-φ50(mm)
Weight	0.4 kg
Material	Aluminum
Radome Material	Fiberglass
Operating Temperature	-40°C to +65°C
Rated Wind Velocity-m/s	60

DOC HON-62105.01 • 09202022 • DMC

Honeywell Building Technologies
715 Peachtree Street NE
Atlanta, GA 30308
www.honeywell.com

HON-62105.01 • 09202022
©2020 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.
This document is not intended to be used for installation purposes. We try to keep our product information
up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.
Country of origin: U.S.A.

THE FUTURE IS WHAT WE MAKE IT

Honeywell