

MS-7 Series

Manual Fire Alarm Pull Stations

General

The Gamewell-FCI, MS-7 Series manual fire alarm pull stations are available in a wide variety of configurations. The pull stations comply with the Americans with Disabilities Act (ADA) 5-lb. maximum pull force requirement. Operating instructions and Braille text are engraved in the handle. All pull stations include a key lock/reset which is keyed alike with the Gamewell-FCI fire alarm control panels and other manual fire alarm pull stations.

MS-7AF Velociti Addressable Station

The MS-7AF Velociti® Series addressable station is a double action pull station designed for installation in the signaling line circuit of Gamewell-FCI analog addressable control panels. Activation of the pull station causes its assigned address to register at the fire alarm control panel. The door contains an LED which flashes green in normal condition and lights steady red when the station has been activated.* The station features screw terminals.

MS-7ASF Velociti Addressable Station

The MS-7ASF Velociti® Series addressable pull station is a single action station designed for installation in the signaling line circuit of Gamewell-FCI analog addressable control panels. Activation of the station causes its assigned address to register at the control panel. The door contains an LED which flashes green in normal condition and lights steady red when the pull station is activated.* The station features screw terminals.

The Velociti® Series pull stations use a communication protocol that substantially increases the speed of communication between the sensors and certain Gamewell-FCI analog addressable fire alarm controls. These devices operate in a grouped fashion. If one of the devices in the group has a status change, the panel's microprocessor stops the group poll and focuses on the single device. The net effect offers a response speed up to five times greater than earlier designs.

MS-7 Double Action Station

The MS-7 double action pull station is used with conventional fire alarm control panels. It features a set of single pole contacts and screw terminals for connection to an initiating circuit.



MS-7 Series

FEATURES & BENEFITS

- | | | | | |
|--|--|---|--|--|
| <ul style="list-style-type: none"> • Addressable stations compatible with all Gamewell-FCI analog addressable fire alarm controls • Conventional stations suitable for use with any UL® Listed control panel | <ul style="list-style-type: none"> • The pull stations (MS-7LOB) are Listed for outdoor applications • Complies with ADA pull force requirements | <ul style="list-style-type: none"> • Offers surface or semi-flush mounting • Shock and vibration resistant • Both single and double action pull stations available | <ul style="list-style-type: none"> • Includes a tumbler lock for test and reset keyed alike with analog addressable fire alarm controls | <p>*Only the red LED is operative in panels that do not operate in Velociti mode</p> |
|--|--|---|--|--|

MS-7S Single Action Station

The MS-7S single action pull station is used with conventional fire alarm control panels. It features a set of single pole contacts and wire leads for connection to an initiating circuit.

MS-7SP Double Action Station

The MS-7SP is a double action pull station similar to the MS-7 station, with the additional feature of including both English and Spanish instructions molded into the unit.

MS-7LR Dual-action Agent Release Station

The MS-7LR is designed for use with the Gamewell-FCI fire alarm control panels with releasing capabilities and Flex Series releasing systems. It features a set of single pole contacts and screw terminals used to connect to an initiating circuit.

MS-7LRA Agent Release Station with Abort

The MS-7LRA is designed for use with the Gamewell-FCI fire alarm control panels with releasing capabilities and Flex Series releasing systems where system abort capabilities are required. It consists of the following:

- An MS-7LR mounted on a plate with an abort switch
- LED indicators that signal system normal and system activated status

MS-7LOB Double Action Station (Listed for Outdoor Applications)

The MS-7LOB station must be mounted on a Model SB-I/O backbox. In retrofit applications, the pull station is UL Listed for use with the WP-10 backbox. It is intended for use with conventional control panels and has a set of single pole contacts and screw terminals.

Mounting

The MS-7 interior pull stations may be surface mounted or semi-flush mounted on a standard double-gang, or 4-inch (10.2 cm) square electrical box. An optional trim ring (BG12TR) may also be used for semi-flush mounting.

NYC-Plate

The NYC-Plate provides the backplate for the manual pull station. (See Figure 1).



Figure 1 NYC-Plate

Ordering Information

MS-7: Double action station

MS-7AF:** Velociti addressable double action station

MS-7ASF:** Velociti addressable single action station

MS-7S: Single action station, wire leads

MS-7SP: Double action station, English and Spanish instructions

MS-7LR: Agent release station, dual-action

MS-7LRA: Agent release station with abort switch, LED indicators, dual-action

MS-7LOB: Double action station, outdoor use (Includes SB-I/O - Indoor/outdoor use backbox)

SB-I/O: Indoor/outdoor use backbox

SB-10: Surface backbox

BG12TR: Trim ring for semi-flush mount, plastic

NY-PLATE: NYC backplate for manual pull station

**For use with the Gamewell-FCI analog addressable control panels only.

MS-7 Series Technical Specifications

SYSTEMS

Material: Lexan®

Contact Ratings: 0.25 amps. @ 30 VAC/VDC (resistive)

Dimensions: 5 5/8" H x 4 1/4" W x 1 1/4" D
(14 x 10.1 x 3.2 cm)

Operating Temperature:

(MS-7AF, MS-7ASF): 32° to 120° F (0° to 49° C)

(MS-7LOB): -30° to 150° F (-35° to 66° C)

Relative Humidity:

(MS-7AF, MS-7ASF): 10 to 93% (non-condensing)

(MS-7LOB): 85% ± 5% @ 86° ± 3.6° (30° ± 2° C)

Alarm Current: .0030 amp. 0.007 for LED

Supervisory Current:

(MS-7AF, MS-7ASF): .00030 amps.

TEMPERATURE AND HUMIDITY RANGES

This system meets NFPA requirements for operation at 0 – 49°C/32 – 120°F and at a relative humidity 93% ± 2% RH (noncondensing) at 32°C ± 2°C (90°F ± 3°F).

However, the useful life of the system's standby batteries and the electronic components may be adversely affected by extreme temperature ranges and humidity. Therefore, it is recommended that this system and its peripherals be installed in an environment with a normal room temperature of 15 – 27°C/60 – 80°F.

STANDARDS

The MS-7 Series is designed to comply with the following standard:

UL Standard: UL 864 9th Edition

AGENCY LISTINGS AND APPROVALS

These listings and approvals apply to the modules specified in this document. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. Consult factory for latest listing status.

UL: S2465

FM: 3023594

MEA FDNY: 67-02-E Vol. VII

CSFM:

7160-1703:0119

7160-1703:0170

7160-1703:0109

ISO 9001 Certification

For a complete listing of all compliance approvals and certifications, please visit:

<http://www.gamewell-fci.com/en-US/documentation/Pages/Listings.aspx>

LEXAN® is a registered trademark of GE Plastics, a subsidiary of General Electric Company.

Velociti® and Gamewell-FCI are registered trademarks of Honeywell International Inc.

UL® is a registered trademark of Underwriter's Laboratories Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For more information

Learn more about Gamewell-FCI's MS-7 Series and other products available by visiting www.Gamewell-FCI.com

Honeywell Gamewell-FCI

12 Clintonville Road
Northford, CT 06472-1610
203.484.7161
www.honeywell.com

9020-0616 | F | 11/17
©2017 Honeywell International Inc.

Honeywell