

SPECTRALERT® ADVANCE Outdoor Notification Appliances

Outdoor Selectable Output Speaker Strobes and Dual Voltage Evacuation Speakers

DESCRIPTION

The SpectrAlert® Advance Series offers the broadest product line of outdoor speakers and speaker strobes in the industry. The Series offers the following selections for use with a variety of applications:

- metal and plastic outdoor back boxes
- white and red plastic housings
- wall and ceiling mounting options

SpectrAlert Advance outdoor speakers and speaker strobes offer reliable operation over a temperature range of -40°F to 151°F. They may be used indoors or outdoors and used in wet or dry applications. In addition, these speakers provide a broad frequency response range and offer low harmonic distortion to provide an accurate and intelligible broadcast of evacuation messages. High sound pressure level at all tap settings ensures that messages are broadcast clearly.

The plug-in design allows the installer to pre-wire mounting plates and dress the wires before plugging in the speakers to help reduce ground faults. This design also allows faster installations with instant feedback to ensure that wiring is properly connected, rotary switches are set to select voltage and power settings, and provide field selectable candela settings for wall and ceiling speaker strobes.

The weatherproof back boxes offer plastic and metal options. They are designed to accommodate in-and-out wiring for daisy chaining outdoor devices. The plastic weatherproof back boxes are shipped with the product and feature removable side flanges and provide improved resistance to salt water corrosion. The screw hole knockouts, located on the back of the weatherproof back box, eliminate the need to drill holes for screw-in mounting. Both weatherproof back boxes are available with 3/4 inch top and bottom conduit entries and 3/4 inch knock-outs at the back. Included with each back box is a screw-in NPT plug with an O-ring gasket for a watertight seal. Metal back boxes are available separately.



SpectrAlert® Advance

FEATURES AND BENEFITS

- Compatible with the System Sensor® synchronization protocol
- Offers electrical compatibility with existing SpectrAlert® products
- Provides a rotary switch to simplify the field selection of speaker voltage and power settings
- Designed for ceiling and wall mount applications
- Includes a universal mounting plate for wall- and ceiling-mount units
- Has a plug-in design
- Contains a shorting spring on the mounting plate to test continuity before installation
- Weatherproof per NEMA 4x, IP56
- Automatic selection of 12- or 24-volt operation at 15 and 15/75 candela
- Field selectable candela settings on wall and ceiling units

Architectural/Engineering Specifications

General

SpectrAlert Advance outdoor speaker and speaker strobes shall mount to a weatherproof back box. A universal mounting plate shall be used for mounting ceiling and wall products. The notification appliance circuit and amplifier wiring shall terminate at the universal mounting plate. Outdoor SpectrAlert Advance products shall operate between -40°F and 151°F from a regulated DC, or full-wave rectified, unfiltered power supply.

Speaker

The Speaker shall be a System® Sensor SpectrAlert® Advance Model dual voltage transformer speaker capable of operating at 25.0 or 70.7 nominal Vrms. Speaker shall be Listed to UL® Standard S4048 for outdoor fire protective signaling systems. Speaker shall have a frequency range of 400 to 4000 Hz and shall have an operating temperature from -40°F to 150.8°F. Speaker shall have power taps and wattage settings which are selected by rotary switches. The speaker must be installed with its weatherproof backbox in order to remain outdoor approved per UL® listing S4048. The speaker shall be suitable for use in air handling spaces, as well as wet environments.

Speaker Strobe Combination

The Speaker Strobe shall be a System Sensor Model listed to UL 1638 and UL 1480 and be approved for fire protective signaling systems. Speaker shall be capable of operating at 25.0 or 70.7 nominal Vrms, and shall have a frequency range of 400 to 4000 Hz. Speaker shall have power taps that are selected by rotary switch. The strobe shall consist of a xenon flash tube with associated lens/reflector system and operate on either 12V or 24V. The strobe shall also feature selectable candela output, providing options for 15 or 15/75 candela when operating on 12V and 15, 15/75, 30, 75, 110, 115, 135, 150, 177 or 185 when operating on 24V. The strobe shall comply with the Americans with Disabilities Act requirement for visible signaling appliances, flashing at 1 Hz over the strobe's entire operating voltage range. The speaker strobe must be installed with its weatherproof back box in order to remain outdoor approved per UL. The speaker strobe shall be suitable for use in wet environments.

Sound Output				
UL Reverberant (dBA@10 ft)	2 W	1 W	1/2 W	1/4 W
Outdoor Speaker	90	87	84	81
Outdoor Speaker/ Speaker Strobe	89	86	83	80

UL Maximum Strobe Current Draw (mA RMS)					
	Candela	8 to 17.5 Volts		16 to 33 Volts	
		DC	FWR	DC	FWR
Standard Candela Range	15	123	128	66	71
	15/75	142	148	77	81
	30	NA	NA	94	96
	75	NA	NA	158	153
	vmvm95	NA	NA	181	176
	110	NA	NA	202	195
High Candela Range	115	NA	NA	210	205
	135	NA	NA	228	207
	150	NA	NA	246	220
	177	NA	NA	281	251
	185	NA	NA	286	258

Candela Derating

NOTE: For K series products used at low temperatures, listed candela ratings must be reduced in accordance with this table.

Strobe Output (cd)	
Listed Candela	Candela Rating at -40 F
15	Do not use below 32 F
15/75	
30	
75	44
95	70
110	110
115	115
135	135
150	150
177	177
185	185

ORDERING INFORMATION

Outdoor Speakers/Strobes:

SPWK: Wall mount outdoor speaker; white

SPRK: Wall mount outdoor speaker; red

SPSWK: Wall mount outdoor speaker strobe, selectable candela (15, 15/75, 30, 75, 95, 100, 115); white

SPSRK: Wall mount outdoor speaker strobe, selectable candela (15, 15/75, 30, 75, 95, 100, 115); red

SPCWK: Ceiling mount outdoor speaker; white.

SPSCWK: Ceiling mount outdoor speaker strobe, selectable candela (15, 15/75, 30, 50, 75, 95, 110, 115); white

SPSCWHK: Ceiling mount outdoor speaker strobe, selectable candela, high cd (135, 150, 177, 185); white

Outdoor Strobes:

SRHK: Strobe, 12/24 volt, high-candela 135, 150, 177, 185, red, outdoor, includes backbox

SCRK: Strobe, 12/24 volt, multi-candela 15, 15/75, 30, 75, 110, 115, red, outdoor, includes backbox

SCWHK: Strobe, 12/24 volt, high-candela 135, 150, 177, 185, white, outdoor, includes backbox

SCWK: Strobe, 12/24 volt, multi-candela 15, 15/75, 30, 75, 110, 115, outdoor, includes backbox

SRHK: Strobe, 12/24 volt, high-candela 135, 150, 177, 185, red, outdoor, includes backbox

SRK: Strobe, 12/24 volt, multi-candela 15, 15/75, 30, 75, 110, 115, red, outdoor, includes backbox

SWHK: Strobe, 12/24 volt, high-candela 135, 150, 177, 185, white, outdoor, includes backbox

SWK: Strobe, 12/24 volt, multi-candela 15, 15/75, 30, 75, 110, 115, white, outdoor, includes backbox

Accessories:

MWBB: Wall, metal weatherproof backbox; red

MWBBW: Wall, metal weatherproof backbox; white

MWBBCW: Ceiling, metal weatherproof backbox; white

PWBB: Wall, plastic weatherproof backbox; red

PWBBW: Wall, plastic weatherproof backbox; white

PWBBCW: Ceiling, plastic weatherproof backbox; white

OUTDOOR NOTIFICATION APPLIANCES TECHNICAL SPECIFICATIONS

SPECIFICATIONS

Physical Specifications:

Operating Temperature: -40°F to 151°F
(-40°C to 66°C)

Wall-Mount Dimensions:

SPS Speaker Strobe: 6.0"L x 5.0"W x 4.9"D
(including lens and speaker)

SP Speaker: 6.0"L x 5.0"W x 2.9"D

Ceiling Mount Dimensions:

SPS Speaker Strobe: 6.8"Dia x 4.8"D
(including lens and speaker)

SP Speaker: 6.8"L x 2.9"D

Wall-Mount Weatherproof Backbox:

Dimensions: 6.5"L x 5.5"H x 2.9"D

Ceiling-Mount Weatherproof Backbox:

Dimensions: 7.2"Dia x 2.9"D

Electrical/Operating Specifications:

Nominal Voltage (Speakers): 25 Volts or 70.7 Volts (nominal)

Maximum Supervisory Voltage (Speakers): 50VDC

Strobe Flash Rate: 1 flash per second

Nominal Voltage (Strobes): Regulated 12VDC/FWR or 24VDC/FWR

Operating Voltage Range (includes fire panels with built-in sync): 8 to 17.5V (12V nominal) or 16 to 33V (24 nominal)

Operating Voltage with MDL Sync Module: 9 to 17.5V (12V nominal) or 17 to 33V (24V nominal)

Frequency Range: 400 to 4000Hz

Power: ¼, ½, 1, 2 watts

STANDARDS

The SpectrAlert Outdoor Notification Appliances are designed to comply with the following standard:

UL Standard: UL S4048

AGENCY LISTINGS AND APPROVALS

These listings and approvals apply to the modules specified in this document. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. Consult the factory for the latest listing status.

UL Listed: S4048, Vol. 1, Sec. 2

MEA FDNY: 10-08-E

CSFM: 7300-1653:201

E3 Series®, System Sensor®, SpectrAlert® Advance and Gamewell-FCI® are registered trademarks of Honeywell International, Inc.

UL® is a registered trademark of Underwriters Laboratories.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

Country of origin: Mexico

Honeywell Gamewell-FCI

12 Clintonville Road
Northford, CT 06472-1610
203.484.7161
www.gamewell-fci.com

9021-60345 | B | 04/20
©2020 Honeywell International Inc.

