



The Alerton® VisualLogic® VAV-DD-E is a versatile, BACnet-compliant field controller that provides pressure-independent control of any dual-duct variable air volume (VAV) box. As a native BACnet controller, the VAV-DD-E integrates seamlessly with your BACnet system, communicating at up to 115.2 Kbps on a BACnet MS/TP LAN.

The VAV-DD-E-F includes two filters to reduce dust contamination. The VAV-DD-E eliminates the need for expensive products and external pressure sensors to control dual-duct VAV boxes.

The VAV-DD-E supports the Alerton Microtouch™, as well as the BACtalk® Microset, Microset II, and Microset 4 intelligent wall sensors, which offer convenient data display, setpoint adjustment, and technician access to equipment setup parameters.

All VAV-DD-E control logic is programmed using Alerton's easy-to-learn graphical programming language, VisualLogic®. Programming and setup data are stored in non-volatile flash memory, ensuring stable and reliable operation.

The VAV-DD-E contains two integral airflow sensors to provide pressure independent operation of a dual-duct VAV box. The airflow sensor is factory calibrated at multiple velocity points and is field-adjustable during balancing. Minimum, maximum, and reheat airflows can be entered using a Microset wall unit or compatible operator workstation software.

## DUAL-DUCT VARIABLE AIR VOLUME FIELD CONTROLLER

### FEATURES AND HIGHLIGHTS

- Fully BACnet-compliant on MS/TP LAN at up to 115.2 Kbps.
- Programmable control logic can be field-modified.
- Download-able operating code to allow for future software improvements.
- 32-bit processor architecture with all program data backed up in nonvolatile flash memory.
- High-speed processing of DDC program, with an internal logical loop time of 100 msec.
- Backwards compatible with older VAV-DD and VAV-DDC3 models.

### APPLICATIONS

Recommended for pressure-independent control of any dual-duct variable air volume (VAV) box.

### SPECIFICATION STATEMENT

Solution shall provide a BACnet certified terminal device to control a dual-duct variable air volume box. It shall provide four universal inputs, four binary outputs, two air-flow sensors and two filters. Processor shall be 32-bit. Inputs and outputs shall be 16-bit resolution. Device shall support the Microset protocol. Solution shall monitor discharge air or other field inputs. Device must allow a technician to adjust calibration in the field during balancing to compensate for variations in box installation and type.

VAV-DD-E-F						
UI	HBO	GBO	RO	AO	AF	F
UNIVERSAL INPUTS	HOT SWITCHED TRIAC BINARY OUTPUTS	GROUND SWITCHED BINARY OUTPUTS	RELAY OUTPUT	ANALOG OUTPUTS	AIR-FLOW SENSOR	FILTER
4	0	4	0	0	2	2

**TECHNICAL DATA**

**POWER** – 24 VAC @ 50-60 Hz. 4 VA minimum (maximum 52 VA with loads). Half-wave rectified.

**INPUTS** – 16-bit universal inputs accept 3k (Ibex) or 10k thermistor (type II), dry contact, 0-20 mA, 0-10V, 0-5V, or dry-contact pulse. External 250-ohm resistor required for 0-20 mA inputs. Pulse input maximum frequency of 100 Hz. Pulse input minimum duty cycle 5mS ON / 5mS OFF (pulse input not supported on IN-0).

**BINARY OUTPUTS** – Triacs rated 24VAC @ 50/60 Hz, 500 mA continuous and 800 mA (AC rms) for 60 milliseconds.

**MICROSET** – Supports BACtalk® Microset, Microset II, or Microset 4 on input 0 (IN-0).

**INPUT/OUTPUT TERMINATIONS** – Removable header-type screw terminals accept 14-24 AWG wire.

**PRESSURE SENSORS** – 16-bit polarity insensitive pressure sensor. 0-2 in. w.c. (500 Pa) range. 0.0004 in. w.c. (0.1 Pa) zero-point accuracy. 0.5% span repeatability. 1/8-inch x 3/8-inch long barb-fitting.

**FILTERS** – In-line filters for pressure sensor available to enhance long-term stability.

**MAX DIMENSIONS** – 5.2" (132mm) H x 3.3" (84mm) W x 1.1" (28mm) D

**MOUNTING** – Screw mounting

**ENVIRONMENTAL** – 0 to 158°F (-17 to 70°C) / 5 to 95%RH, non-condensing

**COMMUNICATIONS** – EIA-485 (RS-485) over twisted shielded-pair (TSP); auto-baud switching (9.6kbps, 19.2kbps, 38.4kbps, 76.8kbps, or 115.2kbps); communication status LED.

**PROTOCOLS** – BACnet MS/TP (master)

**PROGRAMMING** – Supports Alerton's BD4 DDC file format using Alerton's VisualLogic® toolset.

**MICROPROCESSOR** – 32-bit ARM Cortex-M4F, 80 MHz

**MEMORY** – 512 MB non-volatile flash.

**SECURITY** – Integrated secure boot prevents loading of tampered firmware.

**ORDERING INFORMATION****ITEM NUMBER**

VAV-DD-E	ALERTON VAV DUAL-DUCT BACNET CONTROLLER
VAV-DD-E-F	ALERTON VAV DUAL-DUCT BACNET CONTROLLER WITH FILTER
VAV-FILTER	ALERTON VAV FILTER SINGLE
VAV-FILTER-50	ALERTON VAV FILTER BULK PACK (50)

**CERTIFICATION AND CONFORMANCE**

**BACNET CONFORMANCE** – An application specific controller (ASC) level device; tested and approved by BTL. See Protocol Implementation Conformance Statement (PICS).

**UL** – Listed Underwriters Laboratory for Open Energy Management Equipment (PAZX) under the UL Standard for Safety 916; listing includes both U.S. and Canadian certification. UL 2043 and CAN/ULC-S142 compliant for use in plenum applications.

**EMC** – EMC Directive 89/336/EEC (European CE Mark).

**FCC** – This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



16201 25th Avenue W., Lynnwood, WA 98087  
Telephone: (425) 921-4900 / Fax: (425) 921-4872  
alerton.com / sales@alerton.com