



SWIFT AV Base

The System Sensor SWIFT® Wireless system offers an AV base to support L-Series devices in wireless installations.



Features

- Wireless installation
- Class A mesh network
- Addressable code wheels
- Commercial applications
- Listed to UL 464, UL 1638, UL 1971, CAN/ULC S525, CAN/ULC S526, and CSA C22.2 No. 205"
- Frequency hopping
- Bi-Directional Communications

The **SWIFT AV bases (WAV-CRL, WAV-CWL, WAV-RL and WAV-WL)** are intended for use with compatible System Sensor L-Series AV notification appliances to meet a comprehensive range of notification requirements. The AV Base provides power for the audio and visual signals and supports wireless communication with the Fire Alarm Control Panel (FACP). The L-Series AV notification appliance is mounted directly to the wireless AV base allowing flexibility in color, placement and signal output.

Power is supplied through two sets of 4 batteries – one set provides power for wireless communication, and the other set provides power for the notification appliance's audio and/or visual signal. Battery life of the wireless portion is UL listed for at least 2 years. Battery life for the AV set of batteries depends upon the activation time and output level of the audio or visual signal. The AV base boosts output voltage to support 24VDC options on connected devices.

The SWIFT synchronization module (W-SYNC) can be used to provide audio and visual synchronization between SWIFT notification appliances and System Sensor wired notification appliances. The wireless synchronization module operates from 24V power with supplemental battery support and communicates through the mesh network to the gateway and FACP. Synchronization is only available with notification appliances that use the System Sensor synchronization protocol. Synchronization of the SWIFT notification appliances within a single mesh network is inherent in the wireless system and a wireless synchronization module is not needed. The W-SYNC also provides wireless control and monitoring of a Notification Appliance Circuit (NAC) expander or power supply.

Agency Listings



SWIFT SYSTEM OVERVIEW

The SWIFT Smart Wireless Integrated Fire Technology wireless system offers intelligent (addressable) devices which provide secure, reliable communication to the Fire Alarm Control Panel (FACP) across a Class A mesh network. Wireless devices create an opportunity for applications where it is costly (concrete walls/ceilings, buried wires), obtrusive (surface mount conduit), or possibly dangerous

(asbestos) to use traditional wired devices. It allows fast installation for time-critical situations and provides the flexibility to add wireless onto wired systems for retrofit installations. Both wired and wireless devices can be present on the same FACP for an integrated solution.

The mesh network within the SWIFT system creates a child-parent relationship between the devices so that each device has two parents providing a second path for communications on every device. If one device can no longer operate for any reason, the rest of the devices can still communicate with each other, directly

or through one or more intermediate devices. Once an initial mesh network is formed, mesh restructuring automatically occurs to find the strongest paths possible within the network.

The SWIFT system also engages frequency hopping to prevent system interference whether intentional or accidental. Each device complies with part 15 of the FCC rules: 1) The device may not cause harmful interference and 2) The device must accept any interference received including interference that may cause undesired operation.

Specifications

Physical/Operating Specifications	
Dimensions (Ceiling)	Diameter 7.4" (19 cm); Depth 1.6" (4 cm)
Weight (Ceiling):	20.0 oz (567 g) installed with 8 batteries
Dimensions (Wall)	Height 6" (15 cm); Width 5.1" (13 cm); Depth 1.6" (4 cm)
Weight (Wall)	17.6 oz (499 g) installed with 8 batteries
Electrical Specifications	
RF Operating Voltage Range	3.3 VDC
RF Maximum Current Draw	5 mA (LED On)
RF Operating Voltage	12 VDC
AV Output, Operating Voltage	24 VDC (nominal)
AV Maximum Standby Current	6.5 mA
AV Maximum Alarm Current	550 mA
Standby Current	210 µA @ 3.3 VDC (LED blink enabled)
Maximum Transmit RF Power	17 dBm
Radio Frequency Range	902-928 MHz
Operating Humidity Range	10% to 93% Relative Humidity, Non-condensing
Operating Temperature Range	32°F to 120°F (0°C to 49°C)
Battery Type	8 Panasonic CR123A or 8 Duracell DL123A
Battery Life	<i>RF batteries:</i> 2 year minimum. <i>AV batteries:</i> See Table 2 for AV battery life.
Battery Replacement	Replace during annual maintenance or when TROUBLE BATTERY LOW displays.

AV Battery Life at Temporal 3, Ambient Conditions												
Model	Model Type	Battery Life (Hour, Minutes), per Candela Setting										
		15 cd	30 cd	75 cd	95 cd	110 cd	115 cd	135 cd	150 cd	177 cd	185 cd	
Chime-only	Wall	127h 23m	—	—	—	—	—	—	—	—	—	
	Ceiling	—	—	—	—	—	—	—	—	—	—	
Horn-only	Wall	31h 51m	—	—	—	—	—	—	—	—	—	
	Ceiling	—	—	—	—	—	—	—	—	—	—	
Strobe-only	Wall	20h 44m	14h 09m	8h 20m	7h 22m	6h 02m	—	5h 11m	—	—	4h 01m	
	Ceiling	21h 45m	14h 09m	8h 02m	6h 39m	—	5h 39m	—	4h 43m	3h 57m	—	
Chime-Strobe	Wall	18h 12m	12h 55m	7h 58m	6h 31m	5h 18m	—	4h 26m	—	—	3h 37m	
	Ceiling	18h 35m	12h 44m	7h 41m	6h 28m	—	5h 24m	—	4h 29m	3h 45m	—	
Horn-Strobe	Wall	16h 31m	12h 03m	7h 22m	6h 17m	5h 30m	—	4h 33m	—	—	3h 38m	
	Ceiling	12h 34m	9h 54m	6h 14m	5h 24m	—	4h 46m	—	4h 07m	3h 31m	—	
Low-Freq. Sounder-Only	Wall	8h 15m	—	—	—	—	—	—	—	—	—	
	Ceiling	8h 15m	—	—	—	—	—	—	—	—	—	
Low-Freq. Sounder-Strobe	Wall	—	9h 6m	7h 45m	5h 39m	4h 56m	4h 54m	-	4h 12m	—	—	3h 18m

NOTE: Battery life will decrease using continuous tone or other coded patterns and under non-ambient environmental conditions.

Compatible Equipment

Note: ULC-listed models have all required languages.

System Sensor L-Series AV Devices		
Model (UL listed)	Model (ULC listed)	Description
CHRL	CHRLA*	Chime Red Wall
CHSCRL	CHSCRLA*	Chime/Strobe Red Ceiling
	CHSCRLA-E	Chime/Strobe Red Ceiling, English
	CHSCRLA-F	Chime/Strobe Red Ceiling, French
CHSCWL	CHSCWLA*	Chime Strobe White Ceiling
	CHSCWLA-E	Chime/Strobe White Ceiling, English
	CHSCWLA-F	Chime/Strobe White Ceiling, French
CHSRL	CHSRLA*	Chime Strobe Red Wall
	CHSRLA-E	Chime/Strobe Red Wall, English
	CHSRLA-F	Chime/Strobe Red Wall, French
CHSWL	CHSWLA	Chime Strobe White Wall
	CHSWLA-E	Chime/Strobe White Wall, English
	CHSWLA-F	Chime/Strobe White Wall, French
CHWL	CHWLA	Chime White Wall
HCRL-LF	HCRLA-LF*	520Hz Sounder Red Ceiling
HRL	HRLA	Horn Red Wall
HRL-LF	HRLA-LF*	520Hz Sounder Red Wall
HCWL-LF	HCWLA-LF*	520Hz Sounder White Ceiling
HWL	HWLA	Horn White Wall
HWL-LF	HWLA-LF*	520Hz Sounder White Wall
P2RL	P2RLA*	Horn/Strobe 2-wire Red Wall
	P2RLA-E	Horn/Strobe 2-wire Red Wall, English
	P2RLA-F	Horn/Strobe 2-wire Red Wall, French
P2RL-LF	P2RLA-LF*	520Hz Sounder/Strobe Red Wall
P2RL-P	P2RLA-P	Horn Strobe 2-wire Red Wall, Plain
P2RL-SP	—	Horn Strobe 2-wire Red Wall, Fuego
P2WL	P2WLA	Horn Strobe 2-wire White Wall
	P2WLA-E	Horn/Strobe 2-wire White Wall, English
	P2WLA-F	Horn/Strobe 2-wire White Wall, French

System Sensor L-Series AV Devices		
Model (UL listed)	Model (ULC listed)	Description
P2WL-LF	P2WLA-LF*	520Hz Sounder/Strobe White Wall
P2WL-P	P2WLA-P	Horn Strobe 2-wire White Wall, Plain
P2WL-SP	—	Horn Strobe 2-wire White Wall, Fuego
PC2RL	PC2RLA*	Horn Strobe 2-wire Red Ceiling
	PC2RLA-E	Horn/Strobe 2-wire Red Ceiling, English
	PC2RLA-F	Horn/Strobe 2-wire Red Ceiling, French
PC2WL	PC2WLA*	Horn Strobe 2-wire White Ceiling
	PC2WLA-E	Horn/Strobe 2-wire White Ceiling, English
	PC2WLA-F	Horn/Strobe 2-wire White Ceiling, French
SCRL	SCRLA*	Strobe Red Ceiling
	SCRLA-E*	Strobe Red Ceiling, English
	SCRLA-F	Strobe Red Ceiling, French
SCWL	SCWLA*	Strobe White Ceiling
	SCWLA-E	Strobe White Ceiling, English
	SCWLA-F	Strobe White Ceiling, French
SCWL-CLR-ALERT	—	Strobe White Ceiling Clear Lens Alert
SRL	SRLA*	Strobe Red Wall
	SRLA-E	Strobe Red Wall, English
	SRLA-F	Strobe Red Wall, French
SRL-P	SRLA-P	Strobe Red Wall, Plain
SRL-SP	—	Strobe Red Wall, Fuego
SWL	SWLA*	Strobe White Wall
	SWLA-E	Strobe White Wall, English
	SWLA-F	Strobe White Wall, French
SWL-ALERT	—	Strobe White Wall, Amber Lens
SWL-CLR-ALERT	—	Strobe White Wall, Clear Lens
SWL-P	SWLA-P	Strobe White Wall, Plain

*Bilingual Canadian model

Ordering Information

Part No.	Description
WAV-CRL	Wireless AV base, ceiling, red
WAV-CWL	Wireless AV base, ceiling, white
WAV-RL*	Wireless AV base, wall, red
WAV-WL*	Wireless AV base, wall, white
W-SYNC	Wireless Sync Module
W-BATCART	Wireless battery cartridge, 10-pack

*Note: WAV-RL & WAV-WL are compatible with wall-mount L-Series devices manufactured after 26 April 2019 (date code 9045 and later). WAV-CRL and WAV-CWL are compatible with all ceiling-mount L-Series devices. The WAV-CRL, WAV-CWL, WAV-RL, and WAV-WL SWIFT Wireless AV Base are designed to comply with the following standards: UL 864 9th Edition and 10th edition, NFPA 72, CAN/ULC S525 and S526, and CSA C22.2 No.205.

Accessories

W-BATCART

Wireless battery cartridge



System Sensor® and SWIFT® are registered trademarks of Honeywell International, Inc.
Duracell® is a registered trademark of Duracell U.S. Operations Inc.
Panasonic® is a registered trademark of Panasonic Corporation.



3825 Ohio Avenue • St. Charles, IL 60174
Phone: 800-SENSOR2 • Fax: 630-377-6495

©2022 System Sensor.
Product specifications subject to change without notice. Visit systemsensor.com for current product information, including the latest version of this data sheet.
SPDS902-04 • 3/10/2022