

Galaxy® TouchCenter Plus

Intuitive Touchscreen Keypad with Live Camera View

Galaxy TouchCenter Plus is a colour touchscreen keypad through which users can easily interact and operate Grade 2 and Grade 3 Galaxy Flex/Flex+ and Galaxy Dimension intruder alarm systems. Gain control at one's fingertips. The intuitive touchscreen display has clear icons and menu driven prompts. TouchCenter Plus features a faster installation, reduced training needs and fewer service callouts – reducing operational errors and subsequent false alarms.

Clear and simple system management

TouchCenter Plus gives users the choice of operation via touchscreen, key tags, or RFID cards, making it easy to operate both intrusion and access control functions of the system. Even the largest multi-site systems are simple to manage. The intuitive interface and overview screens display system and zone status, groups, and events.

Keep in touch with home or business

The real-time Cam view features live streaming on demand, from local or remote IP cameras – giving users the ability to keep an eye on the interior and exterior of their homes and businesses. The convenient built-in Cam live view gives users the flexibility to monitor activity in a wide variety of areas.

Efficient building control

Through the building/home control feature, operating systems such as lighting, air-conditioning, and heating becomes easy.

Elegant design

The modern design of Galaxy TouchCenter Plus includes flush mount options to fit today's contemporary interiors and to ensure a sleek and slim look when mounted.

Picture the possibilities

The high-resolution (800x400p) touchscreen also doubles as a digital picture frame for residential and commercial customers. With the ability to display family photos, create slideshows, utilise MP4 video and audio players, and display advertisements, employee communications and logos, the Galaxy TouchCenter Plus is a true multi-purpose solution that adds value to any installation. Just picture the possibilities.



Highlights

Complex features. Simple operation.

- Enhanced touchscreen operations (with icons and menu driven prompts)
- Live camera view built-in
- System status overview
- Security screen graphics (set/unset multiple areas or groups)
- Optional proximity operation for easier system management
- Easy to add, delete or edit user codes and tags
- Event log display
- Advanced zone settings (status, edit and view list, etc)

Complex features. Simple installation.

- Console mode (full MK7 & MK8) emulation enables full programming
- Virtual keypad ensures full system management
- Future-proof via continuous firmware updates by SD Card

KEY FEATURES



- Intuitive Galaxy security and access system management.



- View live video streaming from IP cameras via Wi-Fi/cable connection (monitor traffic, car parking, employee activity, kids playground etc).



- Aesthetic design with flush or wall mount options.



- MP4 video & audio player with advertisement/photo frame option.



- Output control enabling automation of building & home systems.

Galaxy TouchCenter Plus System features

The power of simplicity – Easy to use, intuitive interface

Home screen



Direct access to full system features

Group status



Easy to interpret group status

Easy set/unset



Easy set and unset with icon driven system status overview

Event log screen



Easy to interpret event logs for users

Add/edit user screen



Plain interface makes adding, deleting and editing user codes and tags fast and simple

Multimedia options



Conveniently access, select or switch between MP4 video, slideshows, advertisements or communications messages

Live IP Camera View



Users can stay in touch with home or business using the built-in Cam live view feature

Advanced set up screen



Faster system commissioning with clear graphics in engineer mode

Galaxy TouchCenter Plus Technical Specifications

GENERAL	
Screen Size	155mm x 87mm
Screen Resolution	800 x 480 pixels
Brightness and Volume	Adjustable slide bar enables customisation of settings
Languages Supported	English, Spanish, French, Dutch, Czech, Polish, Russian
ELECTRICAL	
Operating Voltage	9 - 13 VDC
Current (TouchCenter Plus)	260mA at 12VDC
Current (TouchCenter Plus Prox)	290mA at 12VDC
SPECIAL FUNCTIONS	
Supported Memory Cards	SD/SDHC Card Slot
IP Camera Support	Honeywell equiP® Series & Performance IP Cameras tested
Wiring	Standard four-wire connection
ENVIRONMENTAL	
Operating Temperature Range	-10 °C to 55 °C (operating) -40 °C to 70 °C (storage)
Maximum Humidity	93% RH, non-condensing
MECHANICAL	
Housing Options	Colour: White Mounting: Flush or wall mounted with A045 mount
Enclosure Dimensions (W x H x D):	218 x 162 x 34 mm
Weight	760g
REGULATORY	
Compliance	CE, EN50131-1:2006+A1:2009 and BS8243:2010; Security Grade 3; Environmental Class II
Ancillary Control Equipment (ACE) type	Type B (fixed equipment)

Ordering and compatibility

ORDERING INFORMATION	
CP045-00	Galaxy TouchCenter Plus flush mount
CP046-00	Galaxy TouchCenter Plus flush mount (with prox)
A045	Wall mount for Galaxy TouchCenter Plus

COMPATIBILITY		
INTRUDER ALARM CONTROL PANELS		
Alarm system	Max. No. keypads	Min. panel software version
Galaxy Flex/Flex+ 20/50/100	1	3.xx
Galaxy Dimension 48	1	6.xx
Galaxy Dimension 96/264	2	6.xx
Galaxy Dimension 520	4	6.xx
IP CAMERAS		
equiP Series IP Cameras	Complete range of fully featured IP Cameras for medium to large installations	
HDZ Series IP Cameras	Indoor and outdoor HDZ PTZ cameras	
Performance IP Cameras	Affordable IP camera series for small to medium installations	

NOTE: Please consult your Honeywell representative for details on specific IP cameras supported

Find out more:

www.honeywell.com/security/uk

Email: securitysales@honeywell.com

Honeywell Security and Fire

Europe, Middle East and Africa

United Kingdom

Newhouse Industrial Estate

Motherwell

Lanarkshire

ML1 5SB

Tel: +44 (0)844 8000 235

www.honeywell.com

Middle East

Post Office Box 18530

LOB Building 08, Office 199

Jebel Ali

Dubai

United Arab Emirates

Tel: +971 04 881 5506

South Africa

Honeywell House – Treur Close

Waterfall Park

Gauteng

PO Box 6674

Midrand 1685

South Africa

Tel: +27 (0)11 695 8000

www.honeywell.com/security/za

Italy

Via della Resistenza, 53/59

20090 Buccinasco

Milano

Italia

Tel: +39 (0) 248 880 51

www.honeywell.com/security/it

