

Analogue call point

M5A - W5A series is an indoor analogue break-glass call point designed to be used as manual alarm for fire system. Two models available: M5A-xx e W5A.-xx series include an addressable mini-module for interfacing with NOTIFIER control panels. All call points are compliant to the EU directive for CE mark and CPR certified for EN54.11 and EN54.18.

> MAIN FEATURES

- Easy to install
- Status LED; it shows the different device state:
- BLINKING, in communication with control panel
- STAEADY, alarm
- Easy wiring thanks to plug-in connectors
- Easy test; introducing the supplied specific key, the
- glass will move down, switching manual call point in
- alarm condition.
- Breaking-glass with protective label or flexible
- resettable membrane.
- Suitable for wall mounting or flush mounting. The
- base is supplied with call point.

> Application

Call series is suitable for commercial, industrial or residential application. The series is used as manual call point in case of fire. It is usually installed outside doors so that it can be used in evacuation event

> Installation

A suitable plastic box (supplied) can be used for mounting. Used for both sight and recessed installations. The base is already supplied with the button, for mounting on box B503, a special adapter is available.

> Function

If the glass is broken, the internal micro-switch will be activated and the alarm signal will transmit to panel.



SERIES

M5A-RP02SG-N026-01

Addressable break-glass call point indoor IP24D.



W5A-RP02SG-N026-01

Addressable break-glass call point outdoor IP67.



M5A-YP021G-N065-01

Addressable break glass manual call point yellow color for command release in extinguishing system. Provided with test key. EN 12094 part 3.



M5A-BP021G-N065-01

Addressable break glass manual call point blue color for stop release in extinguishing system. Provided with key test.



FEATURES

Electrical

- Operating voltage: 15-30Vcc
- Main voltage: 24Vcc

Absorption

Stand-by: 350 μ A, 660 μ A With communication

- In Alarm: 6mA (Typical)
- Red LED: 2mA (tipico)
- Yellow LED: 7.5mA max (tipico)

Enviromental

- IP grade:
 - M5A: IP24D
 - W5A IP67
- Operative Temperature:
 - M5A: -10° a +55°C
 - W5A: -30°+70°C

Technical

- Section cable: 0,5 – 2,5mm²
- Weight:
 - M5A: 110 gr./ 160gr. with base
 - W5A 270gr.
- Dimension:
 - M5A 89 x93x59,5 (with base)
 - W5A: 97,5 x93x65,5 (with base)

accessories

SUS758

Box of 10 pieces of spare glasses for Series call points. Neutral inscription.



PS200

Plastic cover for manual call points.



M700K-503

Frame and adapter for B503 wall boxes. Pack of 10 pcs.



SR1T

Red mounting support.



PS174W

Yellow mounting support.



PS176W

Blue mounting support.



 **NOTIFIER**[®]
by Honeywell