OSY2
Gate Valve Supervisory Switch

NOTIFIER® by Honeywell

Ancillary Devices

General

Notifer's OSY2 is used to monitor the open position of an Outside Screw and Yoke (OS&Y) type gate valve.

Installation is simple with the OSY2's single side conduit entrance. By providing a direct conduit pathway to the electrical source, right angle fittings are not required.



Features

- Robust construction.
- Application flexibility.
- Simplified installation.
- Reliable performance.
- Adjustable length actuator.
- Tamper resistant cover screws.
- Can be mounted vertically or horizontally.
- Both SPDT contacts are enclosed in a durable terminal block for added strength.

Specifications:

Contact Ratings:	2.5A @ 24 VDC
Operating Temperature Range:	0ºC to 49ºC
Enclosure Rating:	IP54
Maximum Stem Extension:	67mm
Minimum Stem Extension:	16mm
Bracket Span:	170mm

© 2009 by Honeywell International Inc. All rights reserved.
Unauthorised use of this document is strictly prohibited.

This document is not intended for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor
www.notifier.com.au