



HONEYWELL 35 Series IR Speed Dome Camera

A&E Specifications

GENERAL

SECTION INCLUDES

Provide a high definition camera system for video surveillance, including design, supply, installation, and commissioning.

RELATED SECTIONS

NOTE TO SPECIFIER: Include related sections as appropriate if video surveillance system is integrated to other systems.

- Section 26 05 00: Common Work Results for Electrical, for interface and coordination with building electrical systems and distribution.
- Section 28 05 13: Conductors and Cables for Electronic Safety and Security, for cabling between system servers, panels, and remote devices.
- Section 28 05 28: Pathways for Electronic Safety and Security, for conduit and raceway requirements.
- Section 28 23 00: Video Surveillance Equipment, for interface with, and administration of video recording equipment.

- Section 28 23 23: Video Surveillance Systems Infrastructure.
- Section 28 23 29: Video Surveillance Remote Devices and Sensors.

REFERENCES

Reference Standards: Provide systems that meet or exceed the requirements of the following publications and organizations as applicable to the work of this Section.

- Canadian ICES-003.
- Canadian Standards Association (CSA).
- Conformity for Europe (CE).
- Electronic Industry Association (EIA).
- Federal Communications Commission (FCC).
- Institute of Electronic and Electrical Engineers (IEEE).
- Joint Photographic Experts Group (JPEG).
- National Television Systems Committee (NTSC).
- Phase Alternating Line (PAL).
- Underwriters Laboratories Inc. (UL).
- IP Code (Ingress Protection Rating) per IEC 60529.

SUBMITTALS

General: Submittals shall be made in accordance with the Conditions of the Contract and Submittal Procedure Section.

Manufacturer' s Product Data: Submit manufacturer' s data sheets indicating systems and components proposed for use, including instruction manuals.

Shop Drawings: Submit installation drawings, including connection diagrams for interfacing equipment, list of connected equipment, and locations for major equipment components. Shop drawings shall indicate surrounding construction as provided for the Project.

Project Record Drawings: Indicate location of equipment and wiring on project record drawings. Submit an electronic version of the project record drawings not later than Substantial Completion of the Project.

Operation and Maintenance Data: Submit manufacturer' s operation and maintenance data customized to the system installed. Include operator manuals.

Field Tests: Submit results of field testing of every device, including date, testing personnel, retesting date (if applicable), and confirmation that every device passed field testing.

Maintenance Service Agreement: Submit a sample copy of the manufacturer' s maintenance service agreement, including cost and services for a one year period for Owner' s review.

Maintenance shall include, but not be limited to, labor and materials to repair the system, tests and adjustments, and regular inspections.

DELIVERY, STORAGE, AND HANDLING

Packing and Shipping: Deliver products in manufacturer' s labeled packages.

Storage and Protection: Store and handle products in accordance with manufacturer' s requirements, in a facility where environmental conditions are within recommended limits.

WARRANTY

Manufacturer' s Guarantee: Five (5) years from the manufacture date code under normal use and service for the video surveillance system.

QUALITY ASSURANCE

- Manufacturer: Minimum 10 years' experience in manufacturing and maintaining video surveillance systems. Manufacturer shall provide toll-free technical assistance and support available 24/7.
- Installer: Minimum 2 years' experience installing similar systems and shall be acceptable to the manufacturer of the video surveillance system.

MANUFACTURER SUPPORT

- Manufacturer shall provide customer service, pre-sales applications assistance, after-sales technical assistance, access to online technical support, and online training using Web conferencing.
- Manufacturer shall provide 24/7 technical assistance and support by means of a toll-free telephone number at no extra charge.

EXECUTION

EXAMINATION

Examine site conditions prior to installation. Notify Architect and Owner in writing if unsuitable conditions are encountered. Do not start installation until site conditions are acceptable.

INSTALLATION

- All components of the camera system shall be thoroughly tested before shipping to the project location.
- Camera system shall be installed, programmed, and tested in accordance with manufacturer' s instructions and recommendations.
 - Coordinate interfaces with other products with Owner' s representative where appropriate.
 - Provide conduit, cable, and wire for complete and reliable installation. Obtain Owner' s approval for exact location of cameras, boxes, conduit, cable, and wiring runs prior to installation.
 - Install conduit, cable, and wire parallel and square with building lines, including raised floor areas. Do not exceed 40 percent fill in conduits. Gather and tie wires for orderly installation.
 - Coordinate with other trades to provide proper sequencing of installation.

FIELD COMMISSIONING AND CERTIFICATION

Field Commissioning: Test camera system as recommended by manufacturer, including the following:

- Conduct complete inspection and testing of equipment, including verification of operation with connected equipment.
- Test devices and demonstrate operational features for Owner' s representative and authorities having jurisdiction, as applicable.
- Correct deficiencies until satisfactory results are obtained.
- Submit written copies of test results.

TRAINING

Conduct on-site system administrator and security/surveillance operator training in accordance with the manufacturer' s instructions and recommendations. Training shall include, but not be limited to camera administration, provisioning, configuration, operation, and diagnostics.

SYSTEM DESCRIPTION

The 5M/2MP Network TDN WDR IR Speed Dome Camera HC35WZ5R30/ HC35WZ2R25 shall provide:

- A. Superior Image Quality
 1. HC35WZ2R25/HC35WZ5R30: 2MP/5MP Network IR PTZ, WDR 120dB, 1/2.8" CMOS sensor.
 2. WDR, BLC, HLC, Defog, Anti-shake
 3. True day/night functionality providing vivid color images by day and clear black-and-white images at night with ICR.
 4. Excellent low-light performance 3D noise reduction, and together with H.265 Profile codec saving storage and bandwidth.
- B. Flexible Surveillance Solution
 1. HC35WZ2R25: 25x Optical Zoom, Auto Focus, 5-125mm, P-IRIS, F1.6-F3.67
 2. HC35WZ5R30: 30x Optical Zoom, Auto Focus, 5.3-159m, P-IRIS, F1.6-F4.3

3. H.265 HEVC/H.264/MJPEG, Smart Codec.
 4. Starting Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
Working Temperature: -40°C ~ 70°C (-40°F ~ 158°F) (IR OFF).
 5. ONVIF Profile G/S/T.
 6. Security features include self-signed signed certificates and data encryption.
 7. Cameras can be retrofitted on many existing NVR installations without requiring additional storage.
- C. Easy to Install and Use
1. Built-in PoE+ eliminates separate power supply and associated wiring; 24V AC inputs where PoE+ power is unavailable.
 2. Remote configuration, motorized focus and zoom adjustments and auto focus through web client or from the NVR.
- D. Onboard Video Storage
- Supports up to 256GB (Micro SD/SDHC/SDXC) card for local video storage when event triggered.
- E. Cyber Security:
- User account and password protection, HTTPS, IP Filter, Digest authentication, TLS1.2 only, Stream encryption, AES128 / 256, SSH / Telnet closed, PCI-DSS compliance.

PRODUCTS

MANUFACTURERS

- A. Specified Manufacturer: Honeywell 5M/2MP Network TDN WDR IR PTZ Camera, <https://myhoneywellbuildingsuniversity.com>.
- B. Accepted Part Numbers:

HC35WZ2R25: 2MP Network PTZ Outdoor Dome, WDR 120dB, 1/2.8" CMOS, 25X Optical Zoom, TDN, H.265 HEVC Smart Codec, PoE+, 24VAC, IP66/IP67/IK10 Casing, Black/White.

HC35WZ5R30: 5MP Network PTZ Outdoor Dome, WDR 120dB, 1/2.8" CMOS, 30X Optical Zoom, TDN, H.265 HEVC Smart Codec, PoE+, 24VAC, IP66/IP67/IK10 Casing, Black/White.

SYSTEM COMPONENTS

5MP/2MP Network TDN WDR IR PTZ Camera, camera housing, cabling, and a web-based GUI that provides complete control of camera settings and live video access.

OPERATIONAL REQUIREMENTS

- A. 5MP/2MP Network TDN WDR IR PTZ Camera system shall meet or exceed the following camera specifications:
 - 1 Image Sensor: 1/2.8" CMOS
 - 2 Total Pixels:
 - HC35WZ2R25: 1920 x 1080
 - HC35WZ5R30: 2592 x 1944
 - 3 Minimum Illumination: Color: 0.005 lux @F1.6 1/30sec BW: 0 lux @F1.6 (IR on)
 - 4 WDR range: 120dB
 - 5 IR Distance: up to 150 m
 - 6 Backlight Compensation: WDR, BLC, HLC
 - 7 Day/Night: Auto/Day/Night/Timing
 - 8 Gain Control: 0~100%.
 - 9 Noise Reduction: 2D/3D DNR
 - 10 Privacy Masking: Off / On (5 Areas)

11 Electronic Shutter Speed: 1/1 ~ 1/30000

12 Video Standard: NTSC/PAL

13 White Balance: Auto/Tungsten/Daylight/Manual

14 Signal-to-Noise Ratio: >50 dB.

15 Lens:

HC35WZ2R25: 25x Optical Zoom, 16x Digital Zoom, Auto Focus, 5-125mm, P iris, F1.6-F3.67

HC35WZ5R30: 30x Optical Zoom, 16x Digital Zoom, Auto Focus, 5.3-159m, P iris, F1.6-F4.3

16 Angle of View:

HC35WZ2R25: H: 57.02° - 3.36°, V: 33.14° - 1.91°

HC35WZ5R30: H:56.62° - 2.48°, V:42.76° - 1.91°

17 Communication: ONVIF Profile S/G/T support.

- B. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall provide true day/night functionality with an infrared (IR) cut filter for day mode.
- C. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall provide, in high contrast lighting conditions, higher quality images and significantly better dynamic range.
- D. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall provide up to 5 fully configurable privacy zones to mask sensitive areas of a video image.
- E. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall support the ONVIF Profile S/G/T specification for interoperability between network video products.
- F. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall include, as standard, a web-based GUI that provides complete control of the camera settings. The web-based GUI shall:
 - 1 Provide role-based access control with password protection.

- 2 Be easily discovered through Honeywell Unified tool or other appropriate device search tools.
- 3 Be available to record snapshot images to a PC hard disk.
- 4 Require the following hardware as a minimum for the web browser:

Operating system: Microsoft Windows 10

Processor: Intel Core i5 2.9 GHz or above, such as Intel Core i5-4590 Quad Core 3.3Ghz.

System memory (RAM): 8GB, DDR3-1600

Graphics card: 1 GB dedicated video memory, such as NVIDIA GeForce GTX 750 1 GB.

Network card: 10 Base-T/100 Base-TX Ethernet (RJ-45)

Web browser: Chrome 91.0+ / Edge 92.0+

- G. Viewer: No ActiveX control plug-in for Chrome / Edge
- H. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall support IPv4, IPv6, TCP / IP, HTTP, HTTPS, RTSP / RTP / RTCP, IGMP / Multicast, SMTP, DHCP, NTP, DNS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, TLS protocols.

NOTE TO SPECIFIER: Some development may be required in specific user cases to support some of these protocols in the field as naturally the protocols will mature over time.

- I. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall provide H.265, H.264, or MJPEG triple video streams simultaneously. The streams shall have the following functions:
 - 1 Main Stream:
HC35WZ2R25:
2-Megapixel (16:9) (Max 30fps): 1920 x 1080 / 1280 x 720 (1-25 / 30 fps)

2-Megapixel (16:9) (Max 60fps, non-true WDR mode): 1920 x 1080 / 1280 x 720 (1-50 / 60 fps)

HC35WZ5R30: 2592x1944/2592x1520/1920x1080/1280x720 (1-25/30 fps)

Note: It is only support MAX 15fps for encryption under HTTPS.

- 2 Second Stream: 704x576(PAL)/704x480(NTSC) / 640x480 / 352x288(PAL)/352x240(NTSC) (1-25 / 30 fps)

Note: It is only support MAX 15fps for encryption under HTTPS.

- 3 Third Stream: 640x480 / 352x288(PAL)/352x240(NTSC) / 320x240 (1-25 / 30 fps)

Note: It is not available for encryption.

- J. 5MP/2MP Network TDN WDR IR Speed Dome Camera shall transmit additional H.265, H.264 or MJPEG video streams simultaneously with the primary H.265, H.264 or MJPEG stream (up to triple streams).

The bit rate for the H.265, H.264 and MJPEG streams can be set to Constrained bit rate or Fixed quality. The resolutions and frame rates for all streams are adjustable by the administrator.

- K. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall feature web GUI menus for programming camera parameters. A minimum of the following menus must be available:

- 1 Live View
- 2 Camera Setup
 - General setting
 - Video
 - Audio
 - Image Settings
 - OSD
 - Privacy Mask
- 3 Network Setup

General Settings

Streaming Protocols

SMTP

SNMP

QoS

HTTPS

802.1x

4 Built-in Video Analytics

Motion Detection

Smart Motion Detection

Tampering Detection

Intrusion

Multi Loiter

People Counter

5 Alarm & Event

Alarm In And Alarm Out

SD Card Alarm

6 Storage Setup

SD Card Management

Content Management

Recording Settings

7 System Setup

General Settings

Maintenance

User Accounts

Access List

8 PTZ Setup

Preset

Scan

Patrol

Recording Patrol

Idle Action

Power Up Action

9 Information

Log

Version

- L. 5MP/2MP Network TDN WDR IR Speed Dome Camera system must provide the option of restoring all displays, alarms, camera settings, and diagnostic settings to factory default with a Web GUI command. In addition, the unit shall offer a simple "reboot" with a Web GUI comm
- M. 5MP/2MP Network TDN WDR IR Speed Dome Camera system should provide a warning message through Email, upload an image through Email or record video to a micro SD card upon Motion detection / Smart Motion Detection / Tampering detection / Intrusion Detection / Multi-Loiter Detection / People Counter. The administrators have the ability turning the Motion detection / Smart Motion Detection / Tampering detection / Intrusion Detection / Multi-Loiter Detection / People Counter function on or off through the web GUI.

NOTE TO SPECIFIER: IMPORTANT! Any damaged files on an installed micro SD card incurred by malfunction or error in files saved on the micro SD card, regardless of the cause, are not guaranteed by Honeywell.

- N. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall provide event analytics capability. It shall detect the event of video motion detection, periodically, alarm input, recording notify, camera tampering detection. Once an event is detected, it shall trigger one of following linkages in camera.
 - 1 Snapshot to Email
 - 2 Recording to SD card
 - 3 System log store in camera (can search from web)
- O. 5MP/2MP Network TDN WDR IR Speed Dome Camera housing shall consist of Aluminum and Plastic housing with coating RAL9003, Pantone Black and shall be waterproof, rated to IP66/IP67.
- P. 5MP/2MP Network TDN WDR IR Speed Dome Camera shall include two (2) on-board alarm inputs for normally open or normally closed dry contacts.
- Q. 5MP/2MP Network TDN WDR IR Speed Dome Camera shall include two (2) on-board alarm dry contact output.
- R. 5MP/2MP Network TDN WDR IR Speed Dome Camera shall have Audio Interface with Line In/Out.
- S. 5MP/2MP Network TDN WDR IR Speed Dome Camera housing shall be vandal resistant camera housing, rate to IK10 for PTZ casing.

SERIES INTEGRATIONS

- A. The following accessories are compatible with 5MP/2MP Network TDN WDR IR Speed Dome Camera:
 - 1 HA60WLMZ: PTZ Wall mount bracket, 1.5 NPT, white
 - 2 HA60PLMZ: PTZ Pole mount bracket, white
 - 3 HA60CNMZ: PTZ Corner mount bracket, white
- B. The following NVRs are compatible with 5MP/2MP Network TDN WDR IR Speed Dome Camera:
 - 1 Pro-Watch NVR: Up to 256 IP channels RAID5/6 Enterprise NVR

- 2 MAXPRO NVR PE: Up to 128 IP channels RAID5/6 Enterprise NVR
- 3 MAXPRO NVR SE: Up to 64 IP channels System NVR
- 4 MAXPRO NVR XE: Up to 16 IP channels System NVR
- 5 MAXPRO NVR SOFTWARE: Up to 128 IP channels Recording Software
- 6 ADPRO NVR FASTTRACE 2E / ADPRO NVR iFT-E: Up to 32 IP channels with up to 32 VA channels NVRs
- 7 ADPRO NVR iFT: Up to 32 IP channels or 16 IP channels with up to 16 VA channels NVRs
- 8 ADPRO NVR iFT GATEWAY: 4 IP channels + 4 VA channels
- 9 Honeywell DVM: Supported with Honeywell DVM R710.1 (and later maintenance releases)
- 10 30 Series NVR: Integration with 30 Series NVR

NOTE TO SPECIFIER: Some development may be required in specific user cases to support some of these protocols in the field as they mature over time.

SYSTEM HARDWARE

- A. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall have the following mechanical specifications:
 - 1 Unit Dimensions: Ø173.2 mm x 292.6 mm (Ø6.82" x11.52")
 - 2 Product Weight: 3.5kg (7.71lb)
 - 3 Package Weight: 5.75kg (12.68lb)
 - 4 Body Material: Die-cast aluminium housing
- B. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall have the following electrical specifications:
 - 1 Input Voltage: AC 24 V~, 3 A, 50-60 Hz; or PoE+(IEEE 802.3at, Class4) 50-57 V, MAX 24 W

- 2 Power Consumption: MAX 24 W
- C. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall have the following Audio Line in/out interface specifications:
- 1 Line in, 2.8 Vpp full scale
 - 2 Line out, max. 2.8 Vpp
- D. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall have the following Alarm in/out interface specifications:
- 1 Alarm In: two (2) on-board alarm inputs for normally open or normally closed dry contacts.
 - 2 Alarm Out: two (2) on-board alarm dry contact output with the contact rating 0.5A@24VDC.
- E. 5MP/2MP Network TDN WDR IR Speed Dome Camera system shall be designed to meet the following environmental conditions and regulatory:
- 1 Operating temperature:
Starting Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
Working Temperature: -40°C ~ 70°C (-40°F ~ 158°F) (IR OFF)
 - 2 Relative Humidity: Less than 90%, non-condensing.
 - 3 Emissions: FCC PART 15, CE (EN 55032)
 - 4 Immunity: CE (EN 50130-4), Complies with RCM and UKCA
 - 5 Safety: UL LISTED TO UL/CSA 62368-1, CE (EN 62368-1), CE (EN 60950-22), Complies with RCM and UKCA
 - 6 RoHS: CE (EN 63000), UAE (Cabinet Decree No.10 of 2017)
 - 7 Country or Region of Origin: Vietnam.

END OF SECTION