MS-G Series

Message Signs



General

The stand-alone Phoenix G2 Message Sign is the quickest way to understand an alert. It displays a single-line scrolling alert message. No additional power from the Message Remote 2 is required.

System administrators or the fire department can control the type of information displayed, scrolling speed, message length, etc. Additionally, the sign can be configured to display dispatch information, turnout timer or unit status (with a capable CAD system).

Simple installation: Easily mounts above doorways. in hallways, kitchens, offices and app bays.

There are three Phoenix G2 message sign options:

- MS-G-M Mini Message Sign (Turnout Timer) 12.8" W x 3.7"H x 2.1"D
- MS-G-E Standard Message Sign 24.8" W x 3.7" H x 2.1" D. (most common)
- MS-G-E Extended Message Sign 36.8" W x 3.7" H x 2.1" D



Specifications

Dimensions

-MS-G-M: 12.8" W x 3.7" H x 2.1" D -MS-G-S: 24.8" W x 3.7" H x 2.1" D -MS-G-E: 36.8" W x 3.7" H x 2.1"

 Input voltage: 48 VDC · Power consumption: 1W

Accessories

-MS-G Adapter Plate (Single/Double)

-MS-G Articulating Long-Arm Wall-Mount

MS Hanger Kit

Product Line Information

- MS-AP-D. MS-G Adapter Plate, Double
- MS-AP-S. MS-G Adapter Plate, Single
- · MS-G-E. Gamma Sign Extended
- MS-G-M. Turn Out Timer Sign (Mini)
- MS-G-S. Gamma Sign Standard
- MS-HK. MS-G Hanger Kit
- MS-MNT. MS Articulation Mount
- MR-2. Message Remote

US Digital Designs by Honeywell

1835 E. Sixth St. Suite #27 Tempe, AZ 85281 USA 877-551-USDD stationalerting.com

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. Phoenix G2® is a registered trademark of Honeywell International, Inc. and its related companies. ©2023 Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited. Country of Origin: USA