MP958A Pneumatic **Valve Actuator**



SPECIFICATIONS

IMPORTANT:

The specifications given in this publication do not include normal manufacturing tolerances. Therefore, an individual unit may not exactly match the listed specifications. Also, this product is tested and calibrated under closely controlled conditions and some minor differences in performance can be expected if those conditions are changed.

Model:

MP958A.

Operating Pressure Ranges:

- 2 to 5 psi [14 to 35 kPa].
- 3 to 10 psi [21 to 69 kPa].
- 8 to 11 psi [55 to 76 kPa].

Air Connection:

Push-on connector for 1/4 in. [6 mm] O. D. plastic tubing.

Maximum Safe Air Pressure: 30 psi [207 kPa]. Maximum Diaphragm Temperature:

230 F [110 C].

Close-off ratings:



RC187

CLOSE-OFF RATING IN PSI (kPa)

9449

5 V5813A 200

USA

ARLINGTON HT

Her.

11958A

^{un}eywell

Valves to control hot and/or chilled water.

958A 1017 1 INS RANGE 3-10 PSI

1/2 & 3/4 V5812A

SAFE PRESSURE 29 PSI (200 KPH

The MP958A Pneumatic Valve Actuator is direct-acting

and used only with Honeywell-Braukmann V5852A2xx,

V5862A2xx, V5853A2xx, and V5863A2xx Terminal Unit



240

C8105

BEFORE INSTALLATION

Ensure that the actuator operating pressure range is correct. Ensure that there is adequate clearance at valve location for mounting and piping actuator (Fig. 1).



Fig. 1. Rough in Dimensions for MP958A actuator with V5852Axx Valve Body.

INSTALLATION

Mounting

No tools are required to mount the MP958A actuator on a valve. Using a wrench to tighten the actuator could damage the actuator or the valve.



- Pipe the valve.Remove (unscrew) the protective cover from the valve .
- Screw the actuator onto the body of the valve, hand tight only.

Piping

Using 1/4 in. (6 mm) plastic tubing, connect the actuator to the branch line of the pneumatic thermostat or controller.

By using this Honeywell literature, you agree that Honeywell will have no liability for any damages arising out of your use or modification to, the literature. You will defend and indemnify Honeywell, its affiliates and subsidiaries, from and against any liability, cost, or damages, including attorneys' fees, arising out of, or resulting from, any modification to the literature by you.



Home and Building Control Honeywell Inc. Honeywell Plaza P.O. Box 524 Minneapolis, MN 55408-0524 Home and Building Control

Honeywell Limited-Honeywell Limitée 740 Ellesmere Road Scarborough, Ontario M1P 2V9 Helping You Control Your World

