



3825 Ohio Avenue, St. Charles, Illinois 60174
 1-800-SENSOR2, FAX: 630-377-6495
 www.systemsensor.com

SpectrAlert Advance Plain Model Decals

For use with models DECAL-R, DECAL-W, DECAL-RC, DECAL-WC



SPECIFICATIONS

Operating Temperature:	-40° F to 151° F (-40° C to 66° C)
Application Temperature:	40° F to 100° F
Cure Time:	72 Hours

Note: This product is only for use with Plain (-P) SpectrAlert Advance models.

Notice: This manual shall be left with the owner/user of this equipment.

Note: This product may be installed with both indoor and outdoor models.

GENERAL DESCRIPTION

For installation with SpectrAlert Advance plain (-P) strobes, horn strobes, and speaker strobes. Decals can also be used on standard horns and speakers. The accessory decals allow for flexibility in the field. Each set of decals ship with decals for 5 units. Wall models include 10 decal sheets and ceiling models include 15 decal sheets. Each set of decals include FIRE, ALERT, EVAC and AGENT as options. Decals are offered in red and white for both wall and ceiling devices.

INSTALLATION:

1. Cut desired strip of lettering from the sheet.
2. Apply pressure to the letter on the paper side.
3. Slowly remove the clear plastic backing one letter at a time.
4. Letters should remain adhered to the white paper backing. If letters remain adhered to clear backing, repeat set 2.
5. Apply letters with white paper backing onto clean surface of unit. Apply pressure with finger along the length of the lettering.
6. Slowly remove white paper backing one letter at a time.

FIGURE 1: WALL DECAL



A0431-00

FIGURE 2: CEILING DECAL



A0432-00