









NETAXS + OMNIASSURE TOUCH

QUICK REFERENCE GUIDE

WEB-BASED ACCESS CONTROL FOR INSTALLATION OF ANY SIZE

NETAXS-123

NETAXS-4

							
NX1MPS	NX1P	NX2MPS	NX2P	NX3MPS	NXD1	NXD2	NX4S1E
1 Door Standard Metal Enclosure	1 Door Compact Plastic Enclosure	2 Door Standard Metal Enclosure	2 Door Compact Plastic Enclosure	3 Door Standard Metal Enclosure	1 Door Add-on Board	2 Door Add-on Board	4 Door Standard Metal Enclosure

READERS

							
OT3200BHONG	OT3212BHONG	OT3300BHONG	OT3312BHONG	OT4700BHONG	OT4716BHONG	OT4800BHONG	OT4816BHONG
Smart BLE Mullion Mount	Smart BLE with Keypad Mullion Mount	Multi-Technology BLE Mullion Mount	Multi-Technology BLE with Keypad Mullion Mount	Smart BLE Square Mount	Smart BLE with Keypad Square Mount	Multi-Technology BLE Square Mount	Multi-Technology BLE with Keypad Square Mount

NETAXS WEB-BASED ACCESS CONTROL

NETAXS 1 DOOR SOLUTIONS

NX1P	NetAXS-123: One door, compact (plastic) enclosure with tamper switch, PoE or externally powered
NX1MPS	NetAXS-123: One door, standard (metal) enclosure with tamper switch. Includes 4A, 12 VDC output/100-240 VAC input power supply and 12 V, 7 AH battery

NETAXS 2 DOOR SOLUTIONS

NX2P	NetAXS-123: Two doors, compact (plastic) enclosure with tamper switch, PoE or externally powered
NX2MPS	NetAXS-123: Two doors, standard (metal) enclosure with tamper switch. Includes 4A, 12 VDC output/100-240 VAC input power supply and 12 V, 7 AH battery

NETAXS 3 DOOR SOLUTION

NX3MPS	NetAXS-123: Three doors, standard (metal) enclosure with tamper switch. Includes 4A, 12 VDC output/100-240 VAC input power supply and 12 V, 7 AH battery
--------	--

NETAXS-123 ADD-ON BOARDS (FOR 2 AND 3 DOOR SOLUTIONS)

NXD1	NetAXS-123: One door add-on board for NX1P and NX1MPS (Adds 1 door to your existing 1-door system = 2 doors)
NXD2	NetAXS-123: Two door add-on board for NX1MPS (Adds 2 doors to your existing 1-door system = 3 doors)

NETAXS 4 DOOR SOLUTION

NX4S1E	NetAXS-4: Four Door Standard Metal Enclosure with tamper switch. Includes 16.5 VAC output/120 VAC input transformer and one 12V, 7 AH battery
--------	---

NETAXS WEB-BASED ACCESS CONTROL					
PART NUMBER	DOORS				
	1	2	3	4	>4 DOORS
NX1P	✓				For systems greater than 4 doors and mixing NetAXS-123 and NetAXS-4 door controllers, the NetAXS-123 must be configured as the primary panel.
NX1MPS	✓				
NX2P		✓			
NX2MPS		✓			
NX1P + NXD1		✓			
NX1MPS + NXD1		✓			
NX3MPS			✓		
NX1MPS + NXD2			✓		
NX4S1E				✓	

RECOMMENDED ACCESSORIES	
PART NUMBER	DESCRIPTION
OMNIASSURE™ TOUCH READERS	
OT3200BHONG	Smart BLE Mullion Mount
OT3212BHONG	Smart BLE with Keypad Mullion Mount
OT3300BHONG	Multi-Technology BLE Mullion Mount
OT3312BHONG	Multi-Technology BLE with Keypad Mullion Mount
OT4700BHONG	Smart BLE Square Mount
OT4716BHONG	Smart BLE with Keypad Square Mount
OT4800BHONG	Multi-Technology BLE Square Mount
OT4816BHONG	Multi-Technology BLE with Keypad Square Mount
REQUEST-TO-EXIT	
IS310WH	Entry Level RTE, White
IS320WH	Fully Featured RTE, White
IS320BL	Fully Featured RTE, Black
CREDENTIALS	
ODPEV28N38	DESFIRE EV2 8K Card (100 pcs. box (10x10 pack))
ODKEV28N38	DESFIRE EV2 8K FOB (50 pcs. box (5x10 pack))
MOBCRD10	Mobile Credentials (10 pack)
MOBCRD100	Mobile Credentials (100 pack)
MOBCRD1000	Mobile Credentials (1000 pack)

For More Information

www.security.honeywell.com/uk

Honeywell Commercial Security

Aston Fields Road
 Whitehouse Industrial Estate
 Runcorn
 Cheshire
 WA7 3DL

Tel: +44 (0)8448 000 235

www.honeywell.com

HSA-NetAXSOAT-01-EN(1019)QRG-E
 © 2019 Honeywell International Inc.

**THE
 FUTURE
 IS
 WHAT
 WE
 MAKE IT**

