






Secure your future in a connected world

Reliable high quality video solutions for every need



Honeywell's latest IP cameras feature a simplified user interface with ONVIF integration to recording devices with new technology that makes checking the status of your system faster and easier. Designed to meet your customer's security needs, Honeywell's equiP and HDZ cameras along with MAXPRO NVRs integrate to Honeywell and third party products for a complete, fully integrated IP solution.





EQUIP SERIES CAMERAS										
PART NUMBER	DESCRIPTION	OPTICAL	MINIMUM ILLUMINATION	ENVIRON.	SMART IR LEDS	WDR	POWER	ADDITIONAL INFORMATION		
IP INDOOR IR MINIDOMES										
	H3W2GR1	1/2.7" 2MP/1080p TDN, Low-Light, 3 IR LEDs, H264	2.7-12mm, F1.4, MFZ	0.01 lux color/ 0 lux with IR LEDs on @ F1.4 Low-light	N/A	3 IR LEDs up to 20m (65')	True WDR 120 dB	12 VDC/ 24 VAC 9W Max PoE	ONVIFS & G Support for Micro SD up to 128 GB, Built-in microphone	
	H3W2GR2		7-22mm, F1.4, MFZ							
	H3W4GR1	1/3" 4MP TDN, Low-Light, 3 IR LEDs, H264	2.7-12mm, F1.4, MFZ							
OUTDOOR RUGGED IR MINIDOMES										
	H4L2GR1	1/2.8" 2MP/1080p TDN, Ultra Low-Light, H264	2.7-12mm, F1.4, MFZ	0.005 lux color/ 0 lux with IR LEDs on @ F1.4	IK10 vandal resistant IP67 rated	3 IR LEDs up to 50 m (150')	True WDR 140 dB	12 VDC/ 24 VAC 12.2W Max PoE	ONVIFS & G Support for Micro SD up to 128 GB	
	H4W2GR1	1/2.7" 2MP/1080p TDN, Low-Light, H264	2.7-12mm, F1.4, MFZ	0.01 lux color/ 0 lux with IR LEDs on @ F1.4 Low-Light						
	H4W2GR2		7-22mm, F1.4, MFZ							
	H4W4GR1	1/3" 4MP TDN, Low-Light, H264	2.7-12mm, F1.4, MFZ							
	H4D8GR1	1/1.7" 12MP (4K) TDN, Low-Light, H265	4.1-12.8mm, F1.53, MFZ	0.02 lux color @ F1.53, 0 lux B/W with IR LEDs off @ F1.5		3 IR LEDs up to 45 m (145')	Digital WDR	12 VDC/ 24 VAC 18W Max PoE+		ONVIFS, G & Q Support for Micro SD up to 128 GB
	H4L6GR2	1/1.8" 6MP TDN, Low-Light, H265	4.1-16.4mm, F1.53, MFZ	0.004 lux color @ F1.53, 0 lux B/W with IR LEDs off @ F1.5						
IP OUTDOOR RUGGED IR BULLETS										
	HBL2GR1	1/2.8" 2MP/1080p TDN, Ultra Low-Light, H264	2.7-12mm, F1.4, MFZ	0.005 lux color/0 lux with IR LEDs on @ F1.4 Ultra Low-Light	IK10 vandal resistant IP67 rated	4 IR LEDs up to 60 m (195')	True WDR 140 dB	12 VDC/ 24 VAC 14.5W Max PoE+	ONVIFS & G Support for Micro SD up to 128 GB	
	HBW2GR1	1/2.7" 2MP/1080p TDN, Low-Light, H264	2.7-12mm, F1.4, MFZ	0.01 lux color/0 lux with IR LEDs on @ F1.4 Low-Light						
	HBW2GR3		5-50mm, F1.4, MFZ							
	HBW4GR1	1/3" 4MP TDN, Low-Light, H264	2.7-12mm, F1.4, MFZ							
	HBD8GR1	1/1.7" 12MP (4k) TDN, Low-Light, H265	5.1-12.8mm, F1.7, MFZ	0.02 lux color @ F1.7/0 lux B/W with IR LEDs off @ F1.7		4 IR LEDs up to 65 m (210')	Digital WDR	12 VDC/ 24 VAC 18W Max PoE+		ONVIFS, G & Q Support for Micro SD up to 128 GB
	H4L6GR2	1/1.8" 6MP TDN, Low-Light, H265	4.1-16.4mm, F1.53, MFZ	0.004 lux color @ F1.53, 0 lux B/W with IR LEDs off @ F1.53						
IP BOX CAMERAS										
	HCL2G	1/2.8" 2MP/1080p TDN, Ultra Low-Light, WDR, H264	Ordered separately, support for DC-iris lens	0.002 lux color/ 0.0002 lux B/W @ F1.4 Ultra Low-Light	N/A	N/A	True WDR 140 dB	12 VDC/ 24 VAC 6.5W Max PoE	ONVIFS & G Support for Micro SD up to 128 GB, Built-in microphone	
	HCW2G	1/2.7" 2MP/1080p TDN, Low-Light, WDR, H264	Ordered separately, support for DC-iris lens	0.01 lux color/ 0.001 lux B/W @ F1.4 Low-Light						
	HCW4G	1/3" 4MP TDN, Low-Light, WDR, H264	Ordered separately, support for DC-iris lens							
	HCD8G	1/1.7" 12MP (4k) TDN, Low-Light, WDR, H265	Ordered separately, support for DC-iris lens	0.02 lux color @ F1.53, 0.01 lux B/W @ F1.5			Digital WDR			12 VDC/ 24 VAC 8W Max PoE
INDOOR / OUTDOOR FISHEYE IR CAMERAS										
	HFD6GR1	1/1.8" 6MP TDN Low-Light, IR, WDR, H265	1.7mm F2.0 (fisheye)	0.01 lux color/0 lux BW with IR LEDs on @ F2.0, 30 IR	IK10 vandal resistant IP67 rated	3 IR LEDs up to 8 m (25')	Digital WDR	12 VDC 10 W PoE	ONVIFS & G, Supports Micro SD up to 128 GB cards, Built-in microphone	
	HFD8GR1	1/1.8" 12MP (4k) TDN Low-Light, IR, WDR, H265	1.98mm F2.8 (fisheye)	0.01 lux color/0 lux BW with IR LEDs on @ F2.8, 30 IR						






Perfect when large-scale, detailed surveillance is critical



For continuous detailed surveillance in the most challenging environments rely on the HDZ Series of PTZ dome cameras. With 360° continuous rotation and zoom lens functionality and WDR IR options, these cameras provide consistently high coverage to capture extremely crisp video images with up to 2 million effective pixels.

IP EXPLOSION-PROOF IR CAMERAS								
PART NUMBER	DESCRIPTION		OPTICAL	MINIMUM ILLUMINATION	ENVIRON.	WDR	POWER	
 HEPB302W01A04	1/2.8" 2MP/1080p TDN Low-Light, WDR, Wiper, H265	4m armoured cable	30x 4.5-135mm F1.6 MFZ	0.005 lux color/0.0005 lux (B/W) @ F1.6	ATEX, IECEx, IP66/IP68 rated, IP69 (housing) -50°C to 65°C	WDR (120dB)	12 VDC, 24VAC, 24VDC 42 W	
HEPB302W01A10		10m armoured cable						
 HEPZ302W0	1/2.8" 2MP/1080p PTZ , TDN Low-Light, IR, WDR, Wiper, H265				0.0187 lux color/0.012 lux (B/W) @ F1.6	ATEX, IECEx, IP66/IP68 rated, IP69 (housing) -40°C to 65°C		24VAC 120W

IP CORROSION-PROOF IR CAMERA								
PART NUMBER	DESCRIPTION		OPTICAL	MINIMUM ILLUMINATION	ENVIRON.	WDR	POWER	
 HCPB302	1/1.7" 2MP/1080p TDN Low-Light, WDR, H265		30x 4.5-135mm F1.6 MFZ	0.005 lux color/0.0005 lux (B/W) @ F1.6	IP66/IP68 rated -40°C to 60°C	WDR (120dB)	24VAC 42W	




IP THERMAL/VISUAL PTZ IR CAMERA								
PART NUMBER	DESCRIPTION		OPTICAL	MINIMUM ILLUMINATION	ENVIRON.	WDR	POWER	
 HTMZ160T302W	1/1.9" 2MP/1080p TDN 336x256 thermal image PTZ, Low-Light, WDR, H264		30x 6-180mm F1.5 MFZ (60mm Thermal)	0.005 lux color/0.0005 lux (B/W) @ F1.5	IP66/IP68 rated -40°C to 70°C	WDR (120dB)	24VAC 70W	

HDZ SERIES PTZ - ULTRA LOW-LIGHT DOME CAMERAS								
PART NUMBER	DESCRIPTION	OPTICAL / PTZ	MINIMUM ILLUMINATION	ENVIRON.	SMART IR LEDS	WDR	POWER	ADDITIONAL INFORMATION
 HDZ302LIW	1/1.9" 2MP/1080p TDN Ultra Low-Light, IR, Wiper, Outdoor	6.0-180 mm F1.6-F4.8, PTZ 360° continuous rotation	0.005 lux color/0.0005 lux B/W @ F1.6;	N/A	up to 150 m (492')	True WDR 120 dB	12 VDC/24 VAC 32 W Max (PoE++)	ONVIFS & G Support for Micro SD up to 128 GB
 HDZ302LIK	1/1.9" 2MP/1080p TDN Ultra Low-Light, IR, Outdoor	6.0-180 mm F1.6-F4.8, PTZ 360° continuous rotation	0 lux IR On Ultra Low-Light	IK10 vandal resistant IP67 rated	up to 200 m (656')		12 VDC/24 VAC 38 W Max (PoE++)	
 HDZ302DE	1/2.8" 2MP/1080p TDN Indoor / Outdoor	4.5-135 mm F1.6-F4.4, PTZ 360° continuous rotation	0.005 lux color/0.0005 lux B/W @ F1.6		N/A		24 VAC ± 25%, 3A and PoE+	
 HDZ302D	1/2.8" 2MP/1080p TDN Indoor / Outdoor	4.5-135 mm F1.6-F4.4, PTZ 360° continuous rotation		IK10 vandal resistant IP66 rated	24 VAC ± 25%, 1.5A and POE+			
 HDZ302DIN	1/2.8" 2MP/1080p TDN Indoor	4.5-135 mm F1.6-F4.4, PTZ 360° continuous rotation	0.5 lux color/0.1 lux (B/W) @ F1.6	IK10 vandal resistant	N/A			

MULTI-IMAGER IP CAMERAS								
PART NUMBER	DESCRIPTION	OPTICAL / PTZ	MINIMUM ILLUMINATION	ENVIRON.	SMART IR LEDS	WDR	POWER	ADDITIONAL INFORMATION
 HM4L8GR1	8MP (Four 1/1.9" 2MP CMOS) TDN, H265	Four 5.0 mm / M12 F2.2	0.006 lux color @ F2.2, 0 lux B/W (IR LEDs on) @ F2.2	IK10 vandal resistant IP67 rated	up to 30 m (98')	DWDR	24 VAC 25 W Max (PoE+)	ONVIFS, G & Q Support for Micro SD up to 128 GB
 HMBL8GR1	8MP (Four 1/2.8" 2MP CMOS) TDN, H265	Four 3.0 mm / M12 F2.1	0.008 lux color @ F2.1, 0 lux B/W (IR LEDs on) @ F2.1					

Powerful High Definition, integrated IP video for the most demanding environments

MAXPRO NVRs are open, flexible and scalable high definition IP video surveillance systems that have new technology and features that simplify operation and save time on install and training.

MAXPRO NVR						
	PART NUMBER	DESCRIPTION	CHANNELS	STORAGE	RECORDING RATE	NETWORK THROUGHPUT
 MAXPRO NVR XE	MAXPRO NVR Express Edition		8 or 16 Channels	1TB to 12TB	Up to 480 fps @ 1080p (4 Mbps bitrate) HD	Incoming: 65 Mbps Outgoing: 180 Mbps Total: 245 Mbps
 MAXPRO NVR SE	MAXPRO NVR Standard Edition		16, 32 or 64 Channels	1TB to 36TB	Up to 1280 fps @ 1080p (4 Mbps bitrate) HD	Incoming: 160 Mbps Outgoing: 350 Mbps Total: 510 Mbps
 MAXPRO NVR PE	MAXPRO NVR Professional Edition		32 or 64 Channels	1TB to 48TB	Up to 1920 fps @ 1080p (4 Mbps bitrate) HD	Incoming: 256 Mbps Outgoing: 425 Mbps Total: 681 Mbps

Find out more at www.honeywell.com/security/uk or call 0844 8000 235