Honeywell
THE POWER OF CONNECTED | Performance Series

IP Performance You Want at the Price You Need

Upgrading to IP has never been so easy and affordable.



Choose from our full range of quality IP cameras and our intuitive and cost-effective Embedded NVRs with a user-friendly configuration process that takes you to live video after only minutes of setup time. With built-in network switches that also supply power to the cameras, installing IP video has never been easier.

Performance Series IP Cameras

Honeywell's expanded range of ONVIF-compliant IP cameras gives you increased flexibility and the freedom to choose what's right for your installation.

		PART NUMBER	DESCRIPTION	ENVIRONMENT	IR ILLUMINATION*	LENS	RECOMMENDED ACCESSORIES
IR BALL		HED8PR1	8 MP, 4k Ultra HD, True Day/Night, 1 High Power IR LED, Indoor/Outdoor Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 165 ft (50 m)	4.0 mm fixed lens	Junction Box: HQA-BB3; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HEW2PR2	2 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 200 ft (60 m)	2.7-12 mm Motorized Focus/ Zoom lens	Junction Box: HQA-BB2, HBS2-BB; Wall Mount: HQA-WK; Pole Mount: HQA-PM, HQA-PM2; Corner Mount: HB34S2-CM
		HEW4PR2	4 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 200 ft (60 m)	2.7-12 mm Motorized Focus/ Zoom lens	Junction Box: HQA-BB2, HBS2-BB; Wall Mount: HQA-WK; Pole Mount: HQA-PM, HQA-PM2; Corner Mount: HB34S2-CM
		HEW2PR1	2 MP True Day/Night, WDR, 1 High Power IR LED, Indoor/Outdoor, Grey or White Housing Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 130 ft (40 m)	3.6 mm fixed lens	Junction Box: HQA-BB3; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HEW4PR3	4 MP True Day/Night, WDR, 1 High Power IR LED, Indoor/Outdoor, Grey or White Housing Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 130 ft (40 m)	2.8 mm fixed lens	Junction Box: HQA-BB3; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HEW4PRW3	4 MP True Day/Night, WDR, 1 High Power IR LED, Indoor/Outdoor, Grey or White Housing Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 130 ft (40 m)	2.8 mm fixed lens	Junction Box: HQA-BB3; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HEW4PER3	4 MP True Day/Night, WDR, 18 IR LED, Indoor/Outdoor, White Housing Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 82 ft (25 m)	2.8 mm fixed lens	Junction Box: HBS2-BB; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HED2PER3	2 MP True Day/Night, 12 IR LED, Indoor/Outdoor, White Housing Ball, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 82 ft (25 m)	2.8 mm fixed lens	Junction Box: HBS2-BB; Wall Mount: HQA-WK2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
IR DOME		H4D8PR1	8 MP Rugged , 4k Ultra HD True Day/ Night, 28 IR LEDs, Indoor/Outdoor Mini Dome, PoE 802.3af or 12 VDC	IP66 rated, IK10 vandal resistant	Smart IR, up to 100 ft (30 m)	4.0 mm fixed lens	Junction Box: HQA-BB2; Wall Mount: HQA-WK; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		H2W2PRV3	2 MP True Day/Night, WDR, 10 IR LEDs, Indoor/Outdoor Micro Dome, PoE 802.3af or 12 VDC	IP66 rated, IK10 vandal resistant	Smart IR, up to 65 ft (20 m)	2.8 mm fixed lens	Junction Box: HQA-BB2; Wall Mount: HQA-WK; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		H2W4PRV3	4 MP True Day/Night, WDR, 10 IR LEDs, Indoor/Outdoor Micro Dome, PoE 802.3af or 12 VDC	IP66 rated, IK10 vandal resistant	Smart IR, up to 65 ft (20 m)	2.8 mm fixed lens	Junction Box: HQA-BB2; Wall Mount: HQA-WK; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		H4W4PER3	4 MP Rugged , True Day/Night, WDR 24 IR LEDs, Indoor/Outdoor Mini Dome, PoE 802.3af or 12 VDC	IP66 rated, IK10 vandal resistant	Smart IR, up to 82 ft (25 m)	2.8 mm fixed lens	Junction Box: HQA-BB2; Wall Mount: HQA-WK; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		H4W4PER2	4 MP Rugged , True Day/Night, WDR 2 High Power IR LEDs, Indoor/Outdoor Mini Dome, PoE 802.3af or 12 VDC	IP66 rated, IK10 vandal resistant	Smart IR, up to 148 ft (45 m)	2.7-13.5 mm Motorized Focus/ Zoom lens	Junction Box: HQA-BB2; Wall Mount: HQA-WK; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM

** Depending on scene reflectance.*

		PART NUMBER	DESCRIPTION	ENVIRONMENT	IR ILLUMINATION*	LENS	RECOMMENDED ACCESSORIES
IR BULLET		HBD8PR1	8 MP, 4K Ultra HD True Day/Night, 1 High Power IR LED, Indoor/Outdoor Bullet, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 100 ft (30 m)	4.0 mm fixed lens	Junction Box: HQA-BB1; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HBW2PR2	2 MP True Day/Night, WDR, 4 High Power IR LEDs, Indoor/Outdoor Bullet, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 200 ft (60 m)	2.7-12 mm Motorized Focus/ Zoom lens	Junction Box: HBS2-BB; Pole Mount: HQA-PM, HQA-PM2; Corner Mount: HB34S2-CM
		HBW4PER1	4 MP True Day/Night, WDR, 18 IR LEDs, Indoor/Outdoor Bullet, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 98 ft (30 m)	3.6 mm, fixed	Junction Box: HBS2-BB; Pole Mount: HQA-PM, HQA-PM2; Corner Mount: HB34S2-CM
		HBD2PER1	2 MP True Day/Night, 18 IR LEDs, Indoor/Outdoor Bullet, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 98 ft (30 m)	3.6 mm, fixed	Junction Box: HEJB, HBS2-BB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		HBW4PER2	4 MP True Day/Night, WDR, 4 High Power IR LEDs, Indoor/Outdoor Bullet, PoE 802.3af or 12 VDC	IP66 rated	Smart IR, up to 164 ft (50 m)	2.7-13.5 mm Motorized Focus/ Zoom lens	Junction Box: HBS2-BB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
FISHEYE		HFD5PR1	5 MP Superior HD Day/Night, Indoor Fisheye camera, PoE 802.3af or 12 VDC	-	-	1.42 mm fixed Fisheye lens	Junction Box: HQA-BB2; Pole Mount: HQA-PM2; Wall Mount: HQA-WK
PTZ DOME		HDZP252DI	2 MP 25x zoom True Day/Night, WDR, 6 High Power IR LEDs, Indoor/Outdoor PTZ Dome, PoE+ 802.3at 12 VDC	IP66 rated	Smart IR, up to 328 ft (100 m)	4.8–120 mm	Junction Box: HDZJB; Pole Mount: HDZPMA; Wall Mount: HDZGM; Corner Mount: HDZCMA; Ceiling Mount: HDZCM1, HDZCM2, HDZCM3
		HDZP304DI	4 MP 30x Zoom True Day/Night, 4 High Power IR LEDs, Indoor/Outdoor PTZ Dome, PoE+ 802.3at 24VAC	IP66 rated	Smart IR, up to 328 ft. (100 m)	4.5 mm – 135 mm	Junction Box: HDZJB; Pole Mount: HDZPMA; Wall Mount: HDZGM; Corner Mount: HDZCMA; Ceiling Mount: HDZCM1, HDZCM2, HDZCM3

**Depending on scene reflectance*

Performance Series 4K Embedded NVRs

The 4K Ultra HD Embedded NVRs from the new Honeywell Performance Focus Series offer a feature rich, flexible and affordable video solution. Its multitude of channel, hard drive and internal storage options makes Focus 4K ideal for completion of any application and offers all the benefits of a hassle-free integration with Performance IP, HDZ PTZ Series, and equIP® Series S IP cameras.

		PART NUMBER	RESOLUTION	DESCRIPTION	INTERNAL HDD	RECORDING RATE	REMOVABLE MEDIA
4CH		HEN04113	**8 MP** (4K) @ 1-15fps 6MP/5MP/ 4MP/3MP/ 1080p/720p – @25/30fps	H.265 4 CH NVR, 1 TB, 4 PoE	2 ports up to 16 TB	80Mbps	2 ports (1 USB3.0; 1 USB2.0)
		HEN04123		H.265 4 CH NVR, 2 TB, 4 PoE			
8 CH		HEN08123		H.265 8 CH NVR, 2 TB, 8 PoE		200Mpbs	
		HEN08143		H.265 8 CH NVR, 4 TB, 8 PoE			
16 CH		HEN16123		H.265 16 CH NVR, 2 TB, 16 PoE			
		HEN16143		H.265 16 CH NVR, 4 TB, 16 PoE			
		HEN16163		H.265 16 CH NVR, 6 TB, 16 PoE			

		PART NUMBER	RESOLUTION	DESCRIPTION	INTERNAL HDD	RECORDING RATE	REMOVABLE MEDIA
8 CH		HEN08144	**8 MP** (4K) @ 1-15fps 6MP/5MP/ 4MP/3MP/ 1080p/720p – @25/30fps	H.265 8 CH NVR, 4 TB, 8 PoE	2 ports up to 16 TB	240 fps @ 1080p (320 Mbps)	2 USB Ports (1 x USB 2.0, 1 x USB 3.0)
16 CH		HEN16144		H.265 16 CH NVR, 4 TB, 16 PoE		480 fps @ 1080p (320 Mbps)	
		HEN16184		H.265 16 CH NVR, 8 TB, 16 PoE			
		HEN16284		H.265 16 CH NVR, 8 TB, 16 PoE	4 ports up to 32 TB		3 USB Ports (1 x USB 2.0, 2 x USB 3.0)
		HEN16384		H.265 16 CH NVR, 8 TB, 16 PoE	8 ports up to 64 TB		4 USB Ports (2 x USB 2.0, 2 x USB 3.0)
32 CH		HEN321124	**12 MP/8 MP** (4K) @ 1-15fps 6MP/5MP/ 4MP/3MP/ 1080p/720p – @25/30fps	H.265 32 CH NVR, 12 TB, 16 PoE	2 ports up to 16 TB	960 fps @ 1080p (320 Mbps)	2 USB Ports (1 x USB 2.0, 1 x USB 3.0)
		HEN32284		H.265 32 CH NVR, 8 TB, 16 PoE	4 ports up to 32 TB		3 USB Ports (1 x USB 2.0, 2 x USB 3.0)
		HEN322164		H.265 32 CH NVR, 16 TB, 16 PoE			
		HEN32384		H.265 32 CH NVR, 8 TB, 16 PoE	8 ports up to 64 TB		4 USB Ports (2 x USB 2.0, 2 x USB 3.0)
		HEN323164		H.265 32 CH NVR, 16 TB, 16 PoE			
64 CH		HEN643164		H.265 64 CH NVR, 16 TB, 16 PoE	8 ports up to 64 TB	1920 fps @ 1080p (320 Mbps)	4 USB Ports (2 x USB 2.0, 2 x USB 3.0)
		HEN643324		H.265 64 CH NVR, 32 TB, 16 PoE			
		HEN643484		H.265 64 CH NVR, 48 TB, 16 PoE			

Compatible Accessories

Honeywell's new Rack Mount Tray is compatible with both Embedded NVRs (HEN models) and Performance Series DVRs (HRHT and HRHQ models).

PART NUMBER	DESCRIPTION
HEN48VPS4CH	48 VDC 4CH HEN NVR Power Adapter (as replacement)
HENHQA12VPS	12V/5A HEN NVR & HQA DVR Power Adapter (as replacement)
HENHQARC	Remote Control, IR, for HEN NVR and HQA DVR (as replacement)
HENHQATRAY	ENVR & HQA DVR Rack Mount Tray

Performance Series IP Kits

Honeywell's IP KIts come in a variety of configurations ranging from 4 and 8 Channel eNVRs and Bullet, Dome, and Ball Cameras.

		PART NUMBER	DESCRIPTION	RECORDING RATE	RESOLUTION	REMOVABLE MEDIA
IP KITS		HEN041234BKT	H.265 4 Channel, 2 TB Embedded NVR (HEN04123) with 4 Bullet Cameras (HBW4PER1)	80Mbs	4MP	2 ports (1 USB3.0; 1 USB2.0)
		HEN041234DKT	H.265 4 Channel, 2 TB Embedded NVR (HEN04123) with 4 Dome Cameras (H4W4PER3)			
		HEN081236BKT	H.265 8 Channel, 2 TB Embedded NVR (HEN08123) with 6 Bullet Cameras (HBW4PER1)	200Mbs		
		HEN081236DKT	H.265 8 Channel, 2 TB Embedded NVR (HEN08123) with 6 Dome Cameras (H4W4PER3)			
		HEN04113EBKT	H.265 4 Channel, 1 TB Embedded NVR (HEN04113) with 4 Ball Cameras (HED2PER3)	80Mbs	2MP	
		HEN04113BBKT	H.265 4 Channel, 1 TB Embedded NVR (HEN04113) with 4 Bullet Cameras (HBD2PER1)			
		HEN04123EBKT	H.265 4 Channel, 2 TB Embedded NVR (HEN04123) with 4 Ball Cameras (HED2PER3)			
		HEN04123BBKT	H.265 4 Channel, 2 TB Embedded NVR (HEN04123) with 4 Bullet Cameras (HBD2PER1)			

Performance Series Mounts

The Performance Series IP offers a variety of multi-compatible Wall, Pole and Corner Mounts and Junction boxes.

		PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS		HQA-BB1	Junction Box, Off-White	HBW2PR1, HBW4PR1, HBD8PR1
		HQA-BB2 HQA-BB2G	Junction Box, Off-White/ Grey	H4D3PRV2, H4W2PRV2, H4W4PRV2, H4W4PRV3, HEW2PR2, HEW4PR2, H4D8PR1, HFD5PR1, H4W4PER3, H4W4PER2
		HQA-BB3 HQA-BB3G	Junction Box, Off-White/ Grey	H2W2PRV3, H2W4PRV3, HEW2PR1, HEW2PRW1, HEW3PR3, HEW4PRW3, HED8PR1
		HBS2-BB	Junction Box, Off-White	HED1PR3, HED3PR3, HBD1PR1, HBD3PR1, HBD3PR2, HBW2PR2, HBW4PR2, H4W4PER3, H4W4PER2
		HEJB	Junction Box, Off-White	HED1PR3, HED3PR3, HBD1PR1, HBD3PR1, HBD3PR2
		HQA-WK	Wall Mount, Off-White	HED1PR3, HED3PR3, H4D3PRV2, H4D3PRV3, H4W2PRV2, H4W4PRV2, H4W4PRV3, HEW2PR2, HEW4PR2, H4D8PR1, HFD5PR1, HED2PER3, HEW4PER3, H4W4PER3, H4W4PER2
		HQA-WK2 HQA-WK2G	Wall Mount, Off-White/Grey	H2W2PRV3, H2W4PRV3, HEW2PR1, HEW2PRW1, HEW4PR3, HEW4PRW3, HED8PR1, HED2PER3, HEW4PER3
		HQA-PM2	Pole Mount, Off-White	HED8PR1, HBD8PR1, H4D8PR1, HFD5PR1, HED2PER3, H4W4PER3, HEW4PER3, H4W4PER2 (with a compatible junction box)
		HB34S2-CM	Corner Mount, Off-White	H2W2PRV3, H2W4PRV3, H4W2PRV2, H4W4PRV2, H4W4PRV3, HBW2PR1, HBW4PR1, HBW2PR2, HBW4PR2, HEW2PR1, HEW2PRW1, HEW2PR2, HEW4PR2, HEW4PR3, HEW4PRW3, HED8PR1, HBD8PR1, H4D8PR1, H4D3PRV2, H4D3PRV3, HBD1PR1, HBD3PR1, HBD3PR2, HED1PR3, HED3PR3, HED2PER3, H4W4PER3, HEW4PER3, H4W4PER2 (with a compatible junction box)

** A compatible junction box is required when installing the HQA-PM2 pole mount or the HB34S2-CM corner mount*

		PART NUMBER	DESCRIPTION
PTZ ACCESSORIES		HDZPMA	Pole mount adapter for wall mount
		HDZCMA	Corner mount adapter for wall mount
		HDZJB	Junction box
		HDZNPTA	1.5" NPT adapter
		HDZWM2	Wall mount with access hole

		PART NUMBER	DESCRIPTION
PTZ ACCESSORIES		HDZGM	Wall mount gooseneck bracket
		HDZCM1	Ceiling mount
		HDZCM2	Ceiling mount extension pole for HDZCM1, 220 mm
		HDZCM3	Ceiling mount extension pole for HDZCM1, 420 mm

Performance Series High Quality Analog (HQA)

Hassle-Free HD Cameras

Honeywell's Performance Series HQA offers competitively priced cameras for everyday security applications from a partner you know and trust. Performance you want at the price you need.

PERFORMANCE SERIES HQA CAMERAS

CAT.		PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	ANALOG FORMAT	IR ILLUMINATION*	ENVIRONMENT	RECOMMENDED ACCESSORIES
IR BALL		**HD30HD4**	Indoor/Outdoor IR Ball, True Day/ Night, True WDR	3.6 mm Fixed Lens	4 MP (2560 × 1440)	12 VDC	HD-CVI	Smart IR, up to 164 ft (50 m)	IP66	Wall Mount: HQA-WK2; Junction Box: HQA-BB3; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HE30XD2**	Indoor/Outdoor IR Ball, True Day/ Night	3.6 mm Fixed Lens	1080p (1920 × 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 130 ft (40 m)	IP66	Junction Box: HQA-BB3; Pole Mount: HQA-PM2; Wall Mount: HQA-WK
		**HE30XD2G**	Indoor/Outdoor IR Ball, True Day/ Night	3.6 mm Fixed Lens	1080p (1920 × 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 130 ft (40 m)	IP66	Junction Box: HQA-BB3G; Pole Mount: HQA-PM2; Wall Mount: HQA-WK
		**HE42XD2**	Indoor/Outdoor IR Ball, True Day/ Night, True WDR	2.7 -13.5 mm MFZ Lens	1080p (1920 × 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 164 ft (50 m)	IP66	Pole Mount: HQA-PM2; Wall Mount: HQA-WK
		**HE42XD2G**	Indoor/Outdoor IR Ball, True Day/ Night, True WDR	2.7 -13.5 mm MFZ Lens	1080p (1920 × 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 164 ft (50 m)	IP66	Pole Mount: HQA-PM2; Wall Mount: HQA-WK
IR RUGGED DOME		**HD72HD4**	Rugged IR Dome, True Day/Night, True WDR	2.8 mm Fixed Lens	4 MP (2560 × 1440)	12 VDC	HD-CVI	Smart IR, up to 100 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK; Junction Box: HQA-BB2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HD274HD4**	Rugged IR Dome, True Day/Night, True WDR	2.7-12 mm MFZ Lens	4 MP (2560 × 1440)	12 VDC/ 24 VAC	HD-CVI	Smart IR, up to 100 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK; Junction Box: HQA-BB2; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HD42XD2**	Rugged IR Dome, True Day/Night, True WDR	2.7 -13.5 mm MFZ Lens	1080p (1920 × 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK; Pole Mount: HQA-PM2;
		**H4D42HD8**	IR Rugged Dome, True Day/Night, True WDR	3.7-11 mm MFZ Lens	4K (3840 × 2160)	12 VDC/ 24 VAC	HD-CVI	Smart IR, up to 98 ft. (30 m)	IP66, IK10	Junction Box: HQA-BB4 or HQA-BB2/G; Pole Mount: HQA-PM2; Wall Mount: HQA-WK; Pendant Mount: HQA-PK; In-Ceiling Bracket: HQA-IC; Ceiling Mount: HQA-CB; Rain Shield: HQA-RS
		**HD30XD2**	Indoor/Outdoor IR Rugged Dome, True Day/Night, True WDR	3.6 mm Fixed Lens	1080p (1928 × 1088)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft. (30 m)	IP66, IK10	Pole Mount: HQA-PM2; Wall Mount: HQA-WK Junction Box: HQA-BB2/G; Corner Mount: HB34S2-CM; Rain Shield: HQA-RS
		**HD41XD2**	Indoor/Outdoor IR Rugged Dome, True Day/Night, True WDR	2.7–13.5 mm Vari-focal Lens	1080p (1928 × 1088)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft. (30 m)	IP66, IK10	Junction Box: HQA-BB4 or HQA-BB2/G; Pole Mount: HQA-PM2; Wall Mount: HQA-WK; Pendant Mount: HQA-PK; In-Ceiling Bracket: HQA-IC; Ceiling Mount: HQA-CB; Rain Shield: HQA-RS

**Depending on scene reflectance*

PERFORMANCE SERIES HQA CAMERAS

CAT.		PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	ANALOG FORMAT	IR ILLUMINATION*	ENVIRONMENT	RECOMMENDED ACCESSORIES
IR BULLET		**HB74HD4**	Indoor/Outdoor IR Bullet, True Day/ Night, True WDR	3.6 mm Fixed Lens	4 MP (2560 × 1440)	12 VDC	HD-CVI	Smart IR, up to 131 ft (40 m)	IP66	Junction Box: HQA-BB1; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HB276HD4**	Indoor/Outdoor IR Bullet, True Day/ Night, True WDR	2.7-12 mm MFZ Lens	4 MP (2560 × 1440)	12 VDC/ 24 VAC	HD-CVI	Smart IR, up to 200 ft (60 m)	IP66	Junction Box: HBS2-BB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HB30XD2**	Indoor/Outdoor IR Bullet, True Day/ Night	3.6 mm Fixed Lens	1080p (1920 × 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft (30 m)	IP66	Junction Box: HBS2-BB, HEJB. Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HB42XD2**	Indoor/Outdoor IR Bullet, True Day/ Night, True WDR	2.7 -13.5 mm MFZ Lens	1080p (1920 × 1080)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 164 ft (50 m)	IP66	Junction Box: HBS2-BB, HEJB; Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HB30PHD2**	Indoor/Outdoor IR Bullet, True Day/ Night, True WDR	2.8 mm Lens	1080p (1928 × 1088)	12 VDC	HD-CVI	Smart IR, up to 82 ft. (25m)	IP66	Junction Box: HBS2-BB or HEJB; Pole Mount: HQA-PM2 Corner Mount: HB34S2-CM
		**HBD42HD8**	Indoor/Outdoor IR Bullet, True Day/ Night, True WDR	3.7-11 mm MFZ Lens	4K (3840 × 2160)	12 VDC/ 24 VAC	HD-CVI	Smart IR, up to 150 ft. (50 m)	IP66	Junction Box: HBS2-BB Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
		**HB41XD2**	Indoor/Outdoor IR Bullet, True Day/ Night, True WDR	2.7–13.5 mm Vari-focal Lens	1080p (1928 × 1088)	12 VDC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 98 ft. (30 m)	IP66	Junction Box: HBS2-BB, Pole Mount: HQA-PM2; Corner Mount: HB34S2-CM
PTZ		**HDP302DQI**	1080p 30x IR PTZ Dome (Wall Mount Bracket Included)	4.5-135.0 mm Lens, 30x Optical Zoom	1080p (1920 × 1080)	24 VAC	HD-CVI	Smart IR, up to 492 ft (150 m)	IP66	Junction Box: HDZJB; Pole Mount: HDZPMA; Corner Mount: HDZCMA; Ceiling Mount: HDZCM1
		**HDZP30XD4**	4 MP 30x IR PTZ Dome (Wall Mount Bracket Included)	4.5 -135.0 mm Lens, 30x Optical Zoom	4 MP (2592 × 1520)	24 VAC	HD-CVI, HD-TVI, AHD, Standard Definition	Smart IR, up to 328 ft (100 m)	IP66	Junction Box: HDZJB; Pole Mount: HDZPMA; Corner Mount: HDZCMA; Ceiling Mount: HDZCM1; Mount Adapter: HDZBSPPA
FISHEYE		**HFD40HD4**	Fisheye, True Day/ Night, WDR	1.18 mm Fixed Lens	4 MP (2560 × 1440)	12 VDC	HD-CVI	NA	IP66, IK10	Junction Box: HQA-BB2/G; Pole Mount: HQA-PM2; Wall Mount: HQA-WK; Corner Mount: HB34S2-CM; Pendant Mount: HQA-PK;

**Depending on scene reflectance*

PERFORMANCE SERIES ANALOG CAMERAS

CAT.		PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	ANALOG FORMAT	IR ILLUMINATION*	ENVIRONMENT	RECOMMENDED ACCESSORIES
DOME		**HD262H**	Indoor IR Mini Dome, True Day/ Night	2.8–12 mm, F1.4, VFMI	700 TVL	12 V DC / 24 V AC ±10%	960H	Smart IR, up to 66 ft (20 m)	N/A	Wall Mount: HDPR1-WM; Pendant Mount: HD262H-PK; In-Ceiling Mount: HD262H-IC
IR RUGGED DOME		**HD273H**	Rugged IR Mini Dome, True Day/ Night	2.8–12 mm, F1.4, VFMI	700 TVL	12 V DC / 24 V AC ±10%	960H	Smart IR, up to 100 ft (30 m)	IP66, IK10	Wall Mount: HD273H-WM; Pendant Mount: HD273H-PK; In-Ceiling Mount: HD273H-IC;

**Depending on scene reflectance*

DVRs

Our digital video recorders support a wide variety of user-friendly capabilities such as mouse operation, IR remote control, remote connectivity and best-in-class search engines.

PERFORMANCE SERIES HQA DVRS

CAT.		PART NUMBER	DESCRIPTION	STORAGE
4 CH		**HRHT4041**	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	1 TB
		HRHT4042	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHQ1041	1080p 15fps/ch (720p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	1 TB
8 CH		**HRHT4082**	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHT4084	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB
		HRHQ1081	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	1 TB
		HRHQ1082	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
16 CH		**HRHT4162**	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHT4164	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB
		HRHT4166	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	6 TB
		HRHT41612	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	12 TB
		HRHQ1162	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
		HRHQ1164	1080p 15fps/ch (720p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB

CAT.		PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS		**HQA-WK**	Wall Mount, Off-White	HD29HD1, HD31HD2, HD231HD2, HD73HD1, HD74HD2, HD274HD2, HD72HD4, HD274HD4, HD42XD2, HE30XD2/G, HE42XD2/G
		**HQA-WK2/ HQA-WK2G**	Wall Mount, Off-White/Gray	HD30HD1, HD30HD2, HD30HD4
		**HQA-BB1**	Junction Box, Off-White	HD30HD1, HD30HD2, HB74HD2, HB74HD4
		**HQA-BB2/ HQA-BB2G**	Junction Box, Off-White/Gray	HD72HD4, HD274HD4, HD31HD2, HD73HD1, HD74HD2, HD231HD2, HD274HD2
		**HQA-BB3/ HQA-BB3G**	Junction Box, Off-White/Gray	HD30HD4, HE30XD2, HE30XD2G
		**HEJB**	Junction Box, Off-White	HD31HD2, HD231HD2, HB74HD1, HB30XD2, HB42XD2
		**HBS2-BB**	Junction Box, Off-White	HD29HD1, HD31HD2,HD231HD2, HB74HD1, HB75HD1, HB76HD2, HB276HD2, HB276HD4, HB30XD2, HB42XD2
		**HQA-PM2***	Pole Mount, Off-White	All Performance Series HQA cameras (with a compatible junction box), except PTZ cameras
		**HB34S2-CM***	Corner Mount, Off-White	All Performance Series HQA cameras (with a compatible junction box), except HE30XD2/G, HE42XD2/G, HD42XD2 and PTZ cameras

CAT.		PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS		**HQA-BB4**	Junction Box, Off-White	H4D42HD8, HD274HD4, HD41XD2, HD42XD2
		**HQA-IC**	In-Ceiling Bracket, Off-White	H4D42HD8, HD274HD4, HD41XD2, HD42XD2
		**HQA-RS**	Rain Shield Bracket, Off-White	H4D42HD8, HD274HD4, HD41XD2, HD42XD2, HD30XD2, HD72HD4
		**HQA-PK**	Pendant Mount Cap, Off-White	All HQA cams models except Bullet models
		HQA-CB	Ceiling Mount Bracket, Off-White	All HQA cams models except Bullet models

** With a compatible junction box (please refer to the Mount data sheet at www.honeywellvideo.com)*

5 YEAR WARRANTY
Extended warranty on select cameras

365 SWAP
Over the counter exchange on defective product

I-VIEW NOW READY
Add RMR to every surveillance proposal, sale and installation

MAXPRO® Cloud
Cloud Service enabled helps you drive RMR

Download the Camera & NVRs app on Google Play or the App Store.

Honeywell Security and Fire
2700 Blankenbaker Pkwy, Suite 150
Louisville, KY 40299
1.800.323.4576
www.honeywell.com

L/PSQRG/D | 11/18
© 2018 Honeywell International Inc.

Honeywell