




HDZ Series PTZ Cameras

Quick Reference Guide









Indoor Cameras	Model #	Description	Lens	Resolution	Power Information
	HDZ30HD	IP, 1080P, WDR, TDN, H.264	30x optical zoom and 12x digital zoom 4.3 to 129 mm	High Definition 1080p (1920 x 1080)	24VAC or PoE+ (25.5w)
	HDZ22HDX	IP, 1080P, WDR, TDN, H.264	22x optical zoom and 12x digital zoom 4.3 to 94.6 mm	High Definition 1080p (1920 x 1080)	24VAC or PoE+ (25.5w)
	HDZ30X	IP, 720 x 576, WDR, TDN, H.264	30x optical zoom and 12x digital zoom 3.4 to 102 mm	Standard Definition D1 (720 x 576, 570K effective pixels)	24VAC or PoE+ (20w)
	HDZ30AX	Analogue, 650TVL, WDR, TDN	30x optical zoom and 12x digital zoom 3.4 to 102 mm	650 TVL	24VAC (20w)

Outdoor Cameras	Model #	Description	Lens	Resolution	Power Information
	HDZ30HDE	IP, 1080P, WDR, TDN, H.264	30x optical zoom and 12x digital zoom 4.3 to 129 mm	High Definition 1080p (1920 x 1080)	24VAC or PoE++ (59w)
	HDZ22HDEX	IP, 1080P, WDR, TDN, H.264	22x optical zoom and 12x digital zoom 4.3 to 94.6 mm	High Definition 1080p (1920 x 1080)	24VAC or PoE++ (59w)
	HDZ36EX	IP, 720 x 576, WDR, TDN, H.264	36x optical zoom and 12x digital zoom 3.4 to 122.4 mm	Standard Definition D1 (720 x 576, 570K effective pixels)	24VAC or PoE++ (57w)
	HDZ36EAX	Analogue, 650TVL, WDR, TDN,	36x optical zoom and 12x digital zoom 3.4 to 122.4 mm	650 TVL	24VAC (50w)

Domes for HDZ models

	HDZVRSMKAC	Smoked Polycarbonate Acrylic Dome for HDZ Series Pendant Domes
	HDZIK10AC	Clear IK10 Vandal Proof Acrylic Dome for HDZ Series (Default Dome on HDZ30HD/E & HDZ22HDX/EX)

Mounts

HDXWM2		HDXPMA2	
	Indoor and Outdoor Wall Mount		Pole Mount Adapter for HDXWM2
HDXCMA1		HDPRM2	
	Corner Mount Adapter for HDXWM2		Parapet and Roof Mount
HDCM1		HDZINBKT	
	Indoor Pendant Ceiling Mount		Drop/Hard In-Ceiling Bracket to Mount Pendant HDZ's
517082-7130		HDXSM1	
	In-Ceiling PTZ support plate. Use when installing HDZINBKT, for any in-ceiling back can model in drop tile ceiling or when extra support is required		Half swan neck mount bracket with 1.5" NPT is designed for pole mount applications in outdoor environments

All trademarks are property of their respective owners.



For more information:

securitysales@honeywell.com

Honeywell Security Group

Aston Fields Road
 Whitehouse Industrial Estate
 Runcorn
 Cheshire
 WA7 3DL
 UK
 Tel: 08448 000 235
www.honeywell.com

HVS-HDZFAMF-01-UK(0615)GU-E
 June 2015
 © 2015 Honeywell International Inc.