

Secure your future in a connected world

Reliable high quality video solutions for every need

Honeywell's latest IP cameras feature a simplified user interface with ONVIF integration to recording devices with new technology that makes checking the status of your system faster and easier. Designed to meet your customer's security needs, Honeywell's equIP and HDZ cameras along with MAXPRO NVRs integrate to Honeywell and third party products for a complete, fully integrated IP solution.



	EQUIP SERIES CAMERAS								
PART N	JMBER	DESCRIPTION	OPTICAL	MINIMUM ILLUMINATION	ENVIRON.	SMART IR LEDS	WDR	POWER	ADDITIONAL INFORMATION
	IP INDOOR IF	RMINIDOMES							
	H3W2GR1	1/2.7" 2MP/1080 p TDN,	2.7-12mm, F1.4, MFZ						
-	H3W2GR2	Low-Light, 3 IR LEDs, H.264	7-22mm, F1.4, MFZ	0.01 lux color/ 0 lux with IR	N/A	3 IR LEDs up to 20m (65')		12 VDC/ 24 VAC/PoE 9W Max	ONVIFS & G Support for Micro SD up to 128 GB, Built-in
1	H3W4GR1	1/3" 4MP TDN, Low-Light, 3 IR LEDs, H.264	2.7-12mm, F1.4, MFZ	LEDs on @ F1.4			True WDR 120 dB		microphone
	H3W2GR1V	1/2.8" 2MP /1080p TDN, H.265+	2.7-13.5mm, F1.6,	0.001 lux color/ 0 lux with IR LEDs on @ F1.6	N/A	3 IR LEDs up to 20m		12 VDC / 24 VAC / PoE 11 W Max	ONVIFS, G & Q Support for Micro SD up to
	H3W4GR1V	1/3" 4MP TDN, H.265+	MFZ	0.01 lux color / 0 lux with IR LEDS on @ 1.6	IV/A	(65')"		12 VDC / 24 VAC / 10.5 W Max PoE	Micro SD up to 128 GB, Built-in microphone
	OUTDOOR R	UGGED IR MINIDOMES							
	H4L2GR1	1/2.8" 2MP/1080p TDN, Ultra Low-Light, H.264	2.7-12mm, F1.4, MFZ	0.005 lux color/ 0 lux with IR LEDs on @ F1.4			True WDR 140 dB	12 VDC/ 24 VAC/PoE 12 W Max	ONVIFS & G Support for Micro SD up to 128 GB
	H4W2GR1	1/2.7" 2MP/1080p TDN,	2.7-12mm, F1.4, MFZ		IK10 vandal	3 IR LEDs			
	H4W2GR2	Low-Light, H.264	7-22mm, F1.4, MFZ	0.01 lux color/ 0 lux with IR LEDs on @ F1.4		up to 50 m (150')			
-	H4W4GR1	1/3" 4MP TDN, Low- Light, H.264	2.7-12mm, F1.4, MFZ		resistant IP67 rated				
	H4D8GR1	1/1.7" 12MP (4K) TDN, Low-Light, H.265	4.1-12.8mm, F1.53, MFZ	0.02 lux color @ F1.53, 0 lux B/W with IR LEDs off @ F1.53		3 IR LEDs up to 45 m (145')		12 VDC/ 24 VAC/PoE+ 18W Max	
	H4L6GR2	1/1.8" 6MP TDN, Low-Light, H.265	4.1-16.4mm, F1.53, MFZ	0.004 lux color @ F1.53, 0 lux B/W with IR LEDs off @ F1.53			Digital WDR		ONVIFS, G & Q Support for Micro SD up to 128 GB
	H4L2GR1V	1/2.8" 2MP /1080p TDN, Low-Light, H.265+	2.7-12mm, F1.6, MFZ	0.001 lux color/ 0 lux		3 IR LEDs up to 50 m	True WDR 140 dB	12 VDC / 24 VAC / PoE+ 20.5 W Max	
	H4W2GR1V	H4W2GR1V 1/2.8" 2MP/1080p TDN, 2.7-13.5mm, F1.6, With IR LEDs on @ F1.6 v re	IK10 vandal resistant IP67 rated	(164')	True WDR	12 VDC / 24 VAC / PoE+ 22 W Max	ONVIFS, G & Q Support for Micro SD up to 128 GB		
	H4W4GR1V	1/3" 4MP TDN, H.265+	2.7-13.5mm, F1.6, MFZ	0.01 lux color / 0 lux with IR LEDS on @ 1.6	IP67 rated		120 dB	12 VDC / 24 VAC / PoE+ 15 W Max	35 up to 120 ub

	EQUIP SERIES	SCAMERAS			_	_			
		RUGGED IR BULLETS							
	HBL2GR1	1/2.8" 2MP/1080p TDN, Ultra Low-Light, H.264	2.7-12mm, F1.4, MFZ	0.005 lux color/0 lux with IR LEDs on @ F1.4			True WDR 140 dB	12 VDC/ 24 VAC/PoE+ 14.5W Max	
	HBW2GR1	1/2.7" 2MP/1080p TDN,	2.7-12mm, F1.4, MFZ			4 IR LEDs up to 60 m			
	HBW2GR3	Low-Light, H.264	5-50mm, F1.4, MFZ	0.01 lux color/0 lux with IR LEDs on @ F1.4	IK10 vandal	(195')	True WDR 120 dB	12 VDC/ 24 VAC/PoE 12W Max	ONVIFS & G Support for Micro SD up to 128 GB
	HBW4GR1	1/3" 4MP TDN, Low-Light, H.264	2.7-12mm, F1.4, MFZ		resistant IP67 rated				
	HBD8GR1	1/1.7" 12MP (4k) TDN, Low-Light, H.265	5.1-12.8mm, F1.7, MFZ	0.02 lux color @ F1.7/0 lux B/W with IR LEDs on @ F1.7		4 IR LEDs up to 65 m (210')	Digital	12 VDC/ 24 VAC/PoE+	
	HBL6GR2	1/1.8" 6MP TDN, Low- Light, H.265	4.1-16.4mm, F1.53, MFZ	0.004 lux color @ F1.53, 0 lux B/W with IR LEDs on @ F1.53		4 IR LEDs up to 50 m (164')	WDR	18W Max	ONVIFS, G & Q Support for Micro SD up to 128 GB
	HBW2GR3V	1/2.8* 2MP /1080p TDN, H.265+	5-60 mm, F1.6, MFZ		IK10 vandal resistant IP67 rated		True WDR	12 VDC / 24 VAC / PoE+ 17.3 W Max	ONVIFS, G & Q Support for Micro SD up to 128 GB
	HBW2GR1V	1/2.8* 2MP /1080p TDN, H.265+	2.7-13.5mm, F1.6, MFZ	0.001 lux color/ 0 lux with IR LEDs on @ F1.6			60 m	12 VDC / 24 VAC / PoE+ 20.5 W Max	
	HBL2GR1V	1/2.8 " 2MP /1080p TDN, Low-Light, H.265+	2.7-12mm, F1.6, MFZ		or racea		True WDR 140 dB	12 VDC / 24 VAC / PoE+ 17 W Max	
	IP BOX CAME	RAS							
	HCL2G	1/2.8" 2MP/1080p TDN, Ultra Low-Light, WDR, H.264	Ordered separately, support for DC-iris lens	0.002 lux color/ 0.0002 lux B/W @ F1.4			True WDR 140 dB		
	HCW2G	1/2.7" 2MP/1080p TDN, Low-Light, WDR, H.264	Ordered separately, support for DC-iris lens	0.01 lux color/ 0.001 lux B/W	N/A	N/A	True WDR	12 VDC/ 24 VAC/PoE 6.5W Max	ONVIFS & G Support for
	HCW4G	1/3" 4MP TDN, Low- Light, WDR, H.264	Ordered separately, support for DC-iris lens	@ F1.4	IN/A	IN/A	120 dB		Micro SD up to 128 GB, Built-in microphone
	HCD8G	1/1.7" 12MP (4k) TDN, Low-Light, WDR, H.265	Ordered separately, support for DC-iris lens	0.02 lux color @ F1.53, 0.01 lux B/W @ F1.5			Digital WDR	12 VDC/ 24 VAC/ PoE 8W Max	
	HCL2GV	1/2.8* 2MP /1080p TDN, Low-Light, H.265+	Ordered separately,	0.001 lux color @	NI /A	N/A	True WDR 140 dB	12 VDC / 24 VAC / PoE 9.5 W Max	ONVIFS, G & Q
-		4 (0 0) 01 01 0 10 0 7 7 11	support for DC-iris lens	F/1.6, 0.001 Lux B/W	N/A	IN/A	T WDD	101/00/06/140/	Support for Micro

			oracica soparatoty,	F/1.6, 0.001 Lux B/W	I N/A				
	HCW2GV	1/2.8" 2MP /1080p TDN, H.265+	support for DC-iris lens	eF1.6		N/A	True WDR 120 dB	12 VDC / 24 VAC / PoE 10 W Max	Support for Micro SD up to 128 GB
	INDOOR/OUT	TDOOR FISHEYE IR CAMERA	NS .						
HFD6GR.		1/1.8" 6MP TDN Low- Light, IR, WDR, H.265	1.7mm F2.0 (fisheye)	0.01 lux color/0 lux BW with IR LEDs on @ F2.0, 30 IR	IK10 vandal	3 IR LEDs	Digital	12 VDC / PoE	ONVIFS & G, Supports Micro SD up to 128 GB
	HFD8GR1	1/1.8" 12MP (4k) TDN Low-Light, IR, WDR, H.265	1.98mm F2.8 (fisheye)	0.01 lux color/0 lux BW with IR LEDs on @ F2.8, 30 IR	recistant UPI	(25')	WDR	10 W	cards, Built-in microphone
	MICRO DOME	CAMERAS							
	H2W2GR1	1/2.8" 2MP /1080p TDN, H.265+	2.8 mm, F2.0	0.001 lux color/ 0 lux B/W @ F2.0	IP67 rated	3 IR LEDs up to 15 m (45')	True WDR 120 dB	12 VDC / PoE 4.4 W Max	ONVIFS, G & Q Support for Micro SD up to 128 GB, Built-in microphone
		1/2.8" 2MP /1080p TDN,	2.8 mm, F2.0	0 lux B/W	IP67 rated	up to 15 m			Q Support for Micro SD up to 128 GB, Built-i

Perfect when large-scale, detailed surveillance is critical

For continuous detailed surveillance in the most challenging environments rely on the HDZ Series of PTZ dome cameras. With 360° continuous rotation and zoom lens functionality and WDR IR options, these cameras provide consistently high coverage to capture extremely crisp video images with up to 2 million effective pixels.

IP EXPI	LOSION-PROOF	FIR CAMERAS					
PART NUMB	ER	DESCRIPTION	OPTICAL	MINIMUM ILLUMINATION	ENVIRON.	WDR	POWER
HE	PZ302W0	1/2.8* 2MP/1080p PTZ, TDN Low-Light, IR, WDR, Wiper, H.265	30x 4.5-135mm F1.6 MFZ	0.0187 lux color/0.012 lux (B/W) @ F1.6, 30 IRE, 1/30"	ATEX, IECEx, IP66/IP68 rated, IP69 (housing) -40°C to 65°C	WDR (120dB)	24VAC 120W

	HDZ SERIES P	TZ - ULTRA LOW-LIGHT DOME CAI	MERAS										
PART	NUMBER	DESCRIPTION	OPTICAL / PTZ	MINIMUM ILLUMINATION	ENVIRON.	SMART IR LEDS	WDR	POWER	ADDITIONAL INFORMATION				
•	HDZ302LIW	1/1.9" 2MP/1080p TDN Ultra Low-Light, IR, Wiper, Outdoor	6.0-180 mm F1.6-F4.8, PTZ 360° continuous rotation	0.005 lux color/ 0.0005 lux B/W	IP67	up to 150 m (492')		24 VAC, 3A/High PoE (Class 5) 32 W Max					
	HDZ302LIK	1/1.9° 2MP/1080 p TDN Ultra Low-Light, IR, Outdoor	6.0-180 mm F1.6-F4.8, PTZ 360° continuous rotation	@ F1.6; O lux IR On	IK10 vandalresistant - IP67 rated	IK10 (65	IK10 (6			200 m		24 VAC, 3A/High PoE (Class 5) 38 W Max	
•	HDZ302DE	1/2.8* 2MP/1080 pTDN Indoor/Outdoor	4.5-135 mm F1.6-F4.4, PTZ 360° continuous rotation			N/A	True WDR 120 dB	24 V AC ± 25%, 3A and PoE+	ONVIFS&G Support for Micro SD up to				
٠	HDZ302D	1/2.8* 2MP/1080p TDN Indoor/ Outdoor	4.5-135 mm F1.6-F4.4, PTZ 360° continuous rotation	0.005 lux color/ 0.0005 lux B/W @ F1.6	IK10 vandal resistant IP66 rated		24	24 V AC ± 25%,	128 GB				
	HDZ302DIN	1/2.8* 2MP/1080p TDN Indoor	4.5-135 mm F1.6-F4.4, PTZ 360° continuous rotation		IK10 vandal resistant (Bubble only)	N/A		1.5A and PoE+					

MULTI-IMAGE	ER IP CAMERAS							
PART NUMBER	DESCRIPTION	OPTICAL/PTZ	MINIMUM ILLUMINATION	ENVIRON.	SMART IR LEDS	WDR	POWER	ADDITIONAL INFORMATION
HM4L8GR1	8MP (Four 1/1.9* 2MP CMOS) TDN, H.265	Four 5.0 mm / M12 F2.2	0.006 lux color @ F2.2, 0 lux B/W (IR LEDs on) @ F2.2	IK10	up to 30 m	DWDD	24 VAC / PoE+	ONVIFS, G&Q
HMBL8GR1	8MP (Four 1/2.8" 2MP CMOS) TDN, H.265	Four 3.0 mm / M12 F2.1	0.008 lux color @ F2.1, 0 lux B/W (IR LEDs on) @ F2.1	vandal resistant IP67 rated	(98')	DWDR	25 W Max	Support for Micro SD up to 128 GB

Powerful High Definition, integrated IP video for the most demanding environments


MAXPRO NVRs are open, flexible and scalable high definition IP video surveillance systems that have new technology and features that simplify operation and save time on install and training.

MAXPRO NVR						
	PART NUMBER	DESCRIPTION	CHANNELS	STORAGE	RECORDING RATE	NETWORK THROUGHPUT
	MAXPRO NVR XE	MAXPRO NVR Express Edition	8 or 16 Channels	1TB to 12TB	Up to 480 fps @ 1080p (4 Mbps bitrate) HD	Incoming: 65 Mbps Outgoing: 180 Mbps Total: 245 Mbps
	MAXPRO NVR SE	MAXPRO NVR Standard Editio	32, 48, or 64 Channels	1TB to 48TB	Up to 1280 fps @ 1080p (4 Mbps bitrate) HD	Incoming: 160 Mbps Outgoing: 350 Mbps Total: 510 Mbps
	MAXPRO NVR PE	MAXPRO NVR Professional Edition	32, 48, 64, or 128 Channels	1TB to 64TB	Up to 3000 fps @ 1080p (3.5 Mbps bitrate) HD	Incoming: 500 Mbps Outgoing: 425 Mbps Total: 800 Mbps
	MAXPRO NVR SW	MAXPRO NVR Software Edition	Up to 128 Channels	8	Up to 3840 fps @ 1080p (4 Mbps bitrate) HD	Incoming: 500 Mbps Outgoing: 425 Mbps Total: 800 Mbps

MAXPRO® NVR XE (Xpress Edition)

8/16-Channel Entry Level Network Video Recorder (NVR)

 $Refer to the storage \ calculator \ on \ www.honeywellvideo.com \ to \ help \ determine \ what \ size \ unit \ to \ order.$




	MAXPRO NVR XE - CHANNEL UPGRADE LICENSE
HNM01UP	MAXPRO NVR -1 Channel License Upgrade. Applicable for MAXPRO NVR XE, Rev B, 8 Channel (HNMXEO8B***) units only to add support up to 16 Channels.
HNM04UP	HNM04UP MAXPRO NVR - 4 Channel License Upgrade to add support for up to 64 Channels per NVR
HNM08UP	HNM08UP MAXPRO NVR - 8 Channel License Upgrade to add support for up to 64 Channels per NVR

MAXPRO® NVR SE (Standard Edition)

32/48/64-Channel Network Video Recorder (NVR)

Refer to the storage calculator on www.honeywellvideo.com to help determine what size unit to order.




M	MAXPRO NVR SE – CHANNEL UPGRADE LICENSES						
HNM01UP	MAXPRO NVR – 1 Channel License Upgrade to add support for up to 64 Channels per NVR						
HNM04UP	MAXPRO NVR – 4 Channel License Upgrade to add support for up to 64 Channels per NVR						
HNM08UP	MAXPRO NVR – 8 Channel License Upgrade to add support for up to 64 Channels per NVR						
HNM16UP MAXPRO NVR – 16 Channel License Upgrade to add support for up to 64 Channels per NVR							
HNM32UP	MAXPRO NVR – 32 Channel License Upgrade to add support for up to 64 Channels per NVR						

	ACCESSORIES
HNMSEBRAM4GB	RAM 4 GB Upgrade, MAXPRO NVR SE, Rev B Server (required only for units with 4 GB RAM)
HNMSEBHD1T	1 TB Upgrade Kit, MAXPRO NVR SE, Rev B Server
HNMSEBHD2T	2 TB Upgrade Kit, MAXPRO NVR SE, Rev B Server
HNMSEBHD3T	3 TB Upgrade Kit, MAXPRO NVR SE, Rev B Server
HNMSEBHD4T	4 TB Upgrade Kit, MAXPRO NVR SE, Rev B Server
HNMSEBHD6T	6 TB Upgrade Kit, MAXPRO NVR SE, Rev B Server

MAXPRO® NVR PE (Professional Edition)

32/48/64/128-Channel Enterprise Network Video Recorder (NVR)

Refer to the storage calculator on www.honeywellvideo.com to help determine what size unit to order.



	MAXPRO NVR PE – CHANNEL UPGRADE LICENSES
HNM01UP	MAXPRO NVR 1 Channel License Upgrade to add support for up to 64 Channels per NVR
HNM04UP	MAXPRO NVR 4 Channel License Upgrade to add support for up to 64 Channels per NVR
HNM08UP	MAXPRO NVR 8 Channel License Upgrade to add support for up to 64 Channels per NVR
HNM16UP	MAXPRO NVR 16 Channel License Upgrade to add support for up to 64 Channels per NVR
HNM32UP	MAXPRO NVR 32 Channel License Upgrade to add support for up to 64 Channels per NVR
HNM64UP	MAXPRO NVR 64 Channel License Upgrade to add support for up to 128 Channels per NVR

	ACCESSORIES
HNMPEBHD1S	1 TB SAS Upgrade Kit, MAXPRO NVR PE Rev B / Hybrid PE Server
HNMPEBHD2S	2 TB SAS Upgrade Kit, MAXPRO NVR PE Rev B / Hybrid PE Server
HNMPEBHD3S	3 TB SAS Upgrade Kit, MAXPRO NVR PE Rev B / Hybrid PE Server
HNMPEBHD4S	4 TB SAS Upgrade Kit, MAXPRO NVR PE Rev B / Hybrid PE Server
HNMPEBHD6S	6 TB SAS Upgrade Kit, MAXPRO NVR PE Rev B / Hybrid PE Server
HNMPEBBZL	Front Locking Bezel, MAXPRO NVR PE Rev B / Hybrid PE Server

Software Only Licenses

SOFTWARE MODEL	DESCRIPTION
MPNVRSW4	MAXPRO NVR Software – Base Software and License for 4 Channels
MPNVRSW8	MAXPRO NVR Software – Base Software and License for 8 Channels
MPNVRSW16	MAXPRO NVR Software – Base Software and License for 16 Channels
MPNVRSW32	MAXPRO NVR Software – Base Software and License for 32 Channels
MPNVRSW48	MAXPRO NVR Software – Base Software and License for 48 Channels
MPNVRSW64	MAXPRO NVR Software – Base Software and License for 64 Channels
MPNVRSW128	MAXPRO NVR Software – Base Software and License for 128 Channels

SOFTWARE ONLY CHANNEL UPGRADE LICENSES	
MPNVRSW1UP	MAXPRO NVR Software – 1 Channel License Upgrade
MPNVRSW4UP	MAXPRO NVR Software – 4 Channel License Upgrade
MPNVRSW8UP	MAXPRO NVR Software – 8 Channel License Upgrade
MPNVRSW16UP	MAXPRO NVR Software – 16 Channel License Upgrade
MPNVRSW32UP	MAXPRO NVR Software – 32 Channel License Upgrade
MPNVRSW64UP	MAXPRO NVR Software – 64 Channel License Upgrade to add support for up to 128 Channels per NVR

Software Support Agreement

	SOFTWARE SUPPORT AGREEMENTS
SMUMPNVR4	Software Maintenance Upgrade - MAXPRO NVR - 4 Channel
SMUMPNVR8	Software Maintenance Upgrade - MAXPRO NVR - 8 Channel
SMUMPNVR16	Software Maintenance Upgrade - MAXPRO NVR - 16 Channel
SMUMPNVR32	Software Maintenance Upgrade - MAXPRO NVR - 32 Channel
SMUMPNVR48	Software Maintenance Upgrade - MAXPRO NVR - 48 Channel
SMUMPNVR64	Software Maintenance Upgrade - MAXPRO NVR - 64 Channel
SMU24MPNVR4	Software Maintenance Upgrade with 24/7 Support - MAXPRO NVR - 4 Channel - Includes 24/7 emergency support, remote diagnostic and programming assistance. REQUIRES PURCHASE OF STANDARD SMU.
SMU24MPNVR8	Software Maintenance Upgrade with 24/7 Support - MAXPRO NVR - 8 Channel - Includes 24/7 emergency support, remote diagnostic and programming assistance. REQUIRES PURCHASE OF STANDARD SMU.
SMU24MPNVR16	Software Maintenance Upgrade with 24/7 Support - MAXPRO NVR - 16 Channel - Includes 24/7 emergency support, remote diagnostic and programming assistance. REQUIRES PURCHASE OF STANDARD SMU.
SMU24MPNVR32	Software Maintenance Upgrade with 24/7 Support - MAXPRO NVR - 32 Channel - Includes 24/7 emergency support, remote diagnostic and programming assistance. REQUIRES PURCHASE OF STANDARD SMU.
SMU24MPNVR48	Software Maintenance Upgrade with 24/7 Support - MAXPRO NVR - 48 Channel - Includes 24/7 emergency support, remote diagnostic and programming assistance. REQUIRES PURCHASE OF STANDARD SMU.
SMU24MPNVR64	Software Maintenance Upgrade with 24/7 Support - MAXPRO NVR - 64 Channel - Includes 24/7 emergency support, remote diagnostic and programming assistance. REQUIRES PURCHASE OF STANDARD SMU.
SMU24MPNVR128	Software Maintenance Upgrade with 24/7 Support - MAXPRO NVR - 128 Channel - Includes 24/7 emergency support, remote diagnostic and programming assistance. REQUIRES PURCHASE OF STANDARD SMU.

For more information

www.honeywell.com/security

Honeywell Security and Fire

2700 Blankenbaker Pkwy, Suite 150 Louisville, KY 40299 1.800.323.4576 www.honeywell.com

