NOTIFIER by Honeywell

Product Announcement

VeriFire Tools Version 9.00 & ONYX Series Version 24 Firmware





November 2015

NOTIFIER is pleased to announce the release of VeriFire Tools version 9.00 and ONYX series firmware version 24. VeriFire Tools version 9.00 (or higher) is required for panels operating with version 24 firmware.

VeriFire Tools 9.00

VeriFire Tools version 8.00 introduced a completely redesigned user interface that maximizes the real estate of the user's screen for improved visualization and programming efficiency.

Since the release of version 8.00 we have implemented many improvements and features to enhance the user experience of VeriFire Tools. The input we've received from you, our valued business partners, has been a critical component of these efforts and much appreciated.

VeriFire Tools version 9.00 includes the following features:

- Supports programming for SWIFT 2.0
  - SWIFT 2.0 adds the FW-RM wireless relay module, expanding your wireless application opportunities. Please refer to the SWIFT 2.0 Product Announcement for additional details
- *Auto Populate of the UDACT-2s assigned points based on the type code label of the host panel now applies to all ONYX series panels
  - Eliminating programming redundancy for improved efficiency
- *Surface Pro 3 Tablet support
  - Alleviate the need for technicians to carry laptops

*Refer to the 'What's New In This Release' presentation located in the file/backstage area of VeriFire Tools version 9.00 for additional details on the improvements to version 9.00; improvements and features of previously released versions are documented here as well.

VeriFire Tools version 9.00 is available for download from https://esd.notifier.com.

ONYX Series Version 24 Firmware Features:

- Supports SWIFT 2.0 (Relay Module)
    - Enhanced capabilities/opportunities for wireless applications
- Supervisory Type Code for Acclimate (photo element) for programming flexibility
    - Select latching or tracking for the photo element (global setting)
- Ability to set CO element of an FCO-851 for latching/tracking (global setting)
    - Meet application requirements
- Ability to set alarm verification time up to 240 seconds (requires AHJ approval)
    - Comply with jurisdictional requirements
- *Improved labeling for SCS (Smoke Control Systems) events
    - Better support weekly test requirements

*Specific to NFS2-3030 and NCA-2

ONYX Series panels are now shipping with version 24 firmware allowing you to apply the above referenced products and features in your ongoing and future installations. The availability of version 24 for download from the ESD portal enables you to apply these to existing installations as well. Refer to the version 24 release notes, included with the firmware download, for additional information.

Please contact NOTIFIER Technical Services at 1-800-289-3473 or NOTIFIER.Tech@honeywell.com with any technical or applications questions pertaining to VeriFire Tools version 9.00 and firmware version 24.