

UL Online Certifications Directory

[OCD Home](#) [Quick Guide](#) [Contact Us](#) [UL.com](#)

AMQV.BP547 Connectors and Switches

[Page Bottom](#)

Connectors and Switches

[See General Information for Connectors and Switches](#)

HONEYWELL SECURITY
SUITE 100
2 CORPORATE CENTER DR
PO BOX 9040
MELVILLE, NY 11747 USA

BP547

Flexible connectors, Cat. Nos. 63, 63L, 64, 69, 71L.

Foil connectors, Cat. Nos. 173, 174, 175, 175L, 367 all with suffix BR, GY or WH.

Magnetically actuated contacts, consisting of Models PR-20412, PR-20411, PR-20422+, PR-3814+ may be followed by WH or BR only, may be followed by -M, -S or -2-S, may be followed by additional suffix letters.

Models PR-20443 may be followed by suffix BR, GY or WH, may be followed by -M, -S or -2-S, may be followed by additional suffix letters.

Model PRO51SP may be followed by BR, GY or WH, may be followed by additional suffix letters.

Cat. Nos. 13, 14, 35, 39, 39-2, 40, 40-2, 46, 46-2, 56L, 57, 57-2, 59L, 67.

Models 940, 945, FA945, 949, FA949, 950, 950-2, 950W may be followed by suffix BR, BY or WH, may be followed by -B or -PL, may be followed by -S, may be followed by additional suffix letter, may be followed by a digits. For use with magnets, Models 910,

940, 945, 949, 950 may be followed by suffix BR, GY or WH, may be followed by -B or -PL, followed by -M, may be followed by additional suffix letters, may be followed by a digit.

Models 941, 941-2, 941W, 943, FA943, 944, 944-T, 944-2, 944-TRE, 944SP, 944TSP, 951, 444193 may be followed by suffix BR, GY or WH, may be followed by -S, may be followed by additional suffix letters, may be followed by a digit. For use with magnets, Models 911, 941, 943, 944, 944-T, 951, may be followed by suffix BR, GY or WH, followed by -M, may be followed by additional suffix letters, may be followed by a digit. Models 947, 947-75, 947-75T, 947-75WH1 may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters.

Models 960+, 960-2+ may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters; Series 7945+ with or without suffixes BR, GY or WH.

Model Series 7939, FA7939, may be followed by -2, W, may be followed by -B or -PL, may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters.

Model Series 7940+ may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters, may be followed by a digit.

Model 944CE-XX, where XX represents color.

Overhead door contacts, Models 959+, 959-2+ may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters.

Magnetically actuated switches, Cat. Nos. B4053+, B4054+ with or without suffix -L, -W or -2; Models PRO44BTM, -45T, -51BTM, -55, -55T, -3438, -3438T; Cat. Nos. 956-2, with 953 (WH or BR) spacer; Cat. Nos. 957+, 957L, 957W, 957L-W, 957-2, 957-2L, 957-2W, 957-2L-W, 958-22 may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters, may be followed by a digit.

Mercury contacts, Cat. Nos. 162, 163, 164.

Plunger button contacts, Cat. Nos. 956RP-XX, 956RPT-XX.

Plunger switches, Cat. Nos. 955, 955-2 (BR or WH), 955PS-XX, 955PST-XX.

Tamper switches, Cat. No. 19.

Mechanical switches, Cat. Nos. 19, 112, 116.

Floor mat, Model 159 for use in household burglar alarm systems only.

Magnetically actuated switch, Model 4944SN or 4945SN for use with this manufacturer's Listed serial programming control panels as indicated in the installation instructions.

Floor traps, Cat. Nos. 72, 176.

Magnetically actuated switches, Models 4194+ may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters for use with this manufacturer's Listed Vector control units.

Models 4139SN+, 4191SN+, 4191SNWH1, 4939SN+, 4939SNWH1 may be followed by BR, GY or WH, may be followed by -S, may be followed by additional suffix letters, for use with this manufacturer's Listed Vista serial programming control panels.

Model 4191WA steel door/window adapter for use with Listed Model 4191WH magnetically actuated switch.

Models 4959SN-M, 4959SN-S overhead contact and magnet for use with this manufacturer's Listed Vista serial programming control panels.

Maximum security magnetic switches, Models 966, 966SC, 966RM; Models PAL, -CE, -T may be followed by BR or WH; Model 945T-XX where -XX denotes color designation .

Vibration sensor, Cat. No. 11 having (BR or WH suffix).

High security magnetic switch , Model 968XTP.


Magnetically activated switches, Models PR-20411WG, PR-20412WG, PR-20439WG-WH, PR-20439WG-WH-M, PR-20439WG-BR, PR-20439WG-BR-M, PR-20439WG-GY, PR-20439WG-GY-M, PR-20443WG-WH, PR-20443WG-WH-M, PR-20443WG-BR, PR-20443WG-BR-M, PR-20443WG-GY, PR-20443WG-GY-M, 7939WG-WH, 7939WG-WH-M, 7939WG-BR, 7939WG-BR-M, 7939WG-GY, 7939WG-GY-M, 943WG-WH, 943WG-WH-M, 943WG-BR, 943WG-BR-M, 943WG-GR, 943WG-GR-M, 951WG-WH, 951WG-WH-M, 951WG-BR, 951WG-BR-M, 951WG-GY, 951WG-GY-M.

Door/Window contact transmitters, Models 5820, 5820L.

Door contact transmitters, Models 5818MN, 5818MNL, for use with the Listee\'s 5800 series wireless receiver, residential use only.

Window contact transmitter, Model 5800Micra, for use with the Listee\'s 5800 series wireless receiver, residential use only.

(+)All contact and magnet models may contain prefix SA or WA.

Trademark and/or Tradename: "Ademco (may or may not be in an oval)""BP547"

[Last Updated](#) on 2007-12-20

[Copyright © 2008 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

