



Enter a new dimension...

Comparison chart



For more information, contact us:

For Sales

dihhsuk6@sales@honeywell.com
 Tel: +44 (0) 1698 738 200
 Fax: +44 (0) 1698 738 500

For technical support

uk64techsupport@honeywell.com
 Tel: +44 (0) 844 800 0235
 Fax: +44 (0) 1698 738 491

For literature ordering

Tel: +44 (0) 870 2403387

www.honeywell.com/security/uk/truder

Galaxy Dimension Features	GD-48	GD-96	GD-264	GD-520
Zones on-board (total)	16 (48)	16 (96)	16 (264)	16 (520)
Outputs (400mA) on-board	8	8	8	8
Trigger outputs on flying lead (10mA)	6	6	6	6
Integrated PSU	2,5 A	2,5 A	2,5 A	2,5 A
RS485 Databuses	1	2	2	4
Keypads (Keyprox)	8 (3)	16 (7)	16 (7)	32 (24)
Galaxy Dimension TouchCenter	1	2	2	4
Bus mounted prox readers (MAX)	4	16	16	32
DCMs with 2 x Wiegand interfaces	4	16	16	32
DCM controlled doors	8	32	32	64
Wireless	5800H Series via RF RIOs			
Users	100	250	1000	1000
7 Day Timer Schedules	19	35	67	67
Zone types	52	52	52	52
O/P types	81	81	81	81
Library (Words)	Yes	Yes	Yes	Yes
Event Log	1000	1500	1500	1500
Access Log	1000	1000	1000	1000
Multi-users	Yes	Yes	Yes	Yes
Autoset	Yes	Yes	Yes	Yes
Pre-Check	Yes	Yes	Yes	Yes
Timed Lockout	Yes	Yes	Yes	Yes
Links	64	128	256	256
Part Set	Yes	Yes	Yes	Yes
Silent Part Set	Yes	Yes	Yes	Yes
RS232	Built-in	Built-in	Built-in	Built-in
Integrated PSTN (V 22)	Built-in	Built-in	Built-in	Built-in
Printer Output	Via RS232	Via RS232	Via RS232	Via RS232
Remote Servicing	Yes	Yes	Yes	Yes
Ethernet module	Optional	Optional	Optional	Optional
PCB	New G3	New G3	New G3	New G3
Groups	8	16	32	32
Audio Verification channels	6	32	32	32
SMS text	Yes	Yes	Yes	Yes
ISDN	Optional	Optional	Optional	Optional
EN50131	Yes	Yes	Yes	Yes