#### **SAMPLE FORMULATION**

Using Solstice® Enhance and Solstice® Propellant



# Moisturizing Ice Cream<sup>1</sup>

An ultra-cooling, moisturizing cream that spreads smoothly like butter to enhance your experience

Solstice Propellant (HFO-1234ze(E)), a breakthrough for aerosol-based products, and Solstice Enhance (HFO-1233zd(E)), a multifunctional solvent and carrier fluid, offer exciting possibilities for formulators. As nonflammable alternatives to hydrocarbons and high global warming potential (GWP) hydrofluorocarbons, they are non-ozone-depleting, VOC-exempt, with an **Earth-friendly** ultra-low GWP of one or less.

PHASE	TRADE NAME	INCI	WT%
Concentrate	DI Water	Water	83.4
	AHCOHOL™ 1618 TA	Cetearyl Alcohol	2
	DOWSIL™ 2503 Cosmetic Wax	Stearyl Dimethicone; Octadecene	3
	Olivem® 1000	Cetearyl Olivate; Sorbitan Olivate	4
	DOWSIL™ 9041 Silicone Elastomer Blend	Dimethicone; Dimethicone Crosspolymer	5
	XIAMETER™ PMX-1184 Silicone Fluid	Dimethicone; Trisiloxane	2
	euxyl® PE 9010	Phenoxyethanol; Ethylhexylglycerin	0.5
	Fragrance	Fragrance	0.1
		TOTAL	100
Aerosolized	Concentrate		42
	Solstice Enhance	Chlorotrifluoropropene	8
	Solstice Propellant	Tetrafluoropropene	50
		TOTAL	100

<sup>&</sup>lt;sup>1</sup> Not for human consumption

## **FORMULATION PROCEDURE:**

**Pre-step:** Chill Solstice Enhance (below 19°C) before combining with the formulation. Store in refrigerator.

## Concentrate:

- In a main beaker, weigh Water and start heating to 70-80°C.
- In a separate beaker, weigh the oil phase (AHCOHOL 1618, DOWSIL 2503, Olivem 1000) and start heating to 70-80°C.
- 3. Once both phases are at 70-80°C, add the oil phase to the main beaker and homogenize for 1 min.
- Mix the batch with a paddle mixer.
   Cool down the batch to room temperature and then add the rest of the ingredients in the order of addition.
- 5. Homogenize the batch for 1 minute to ensure uniform mixing.

## Aerosolized:

- 1. Fill liquid concentrate into aluminum/ plastic cans in the order of addition.
- 2. Add Solstice Enhance.
- 3. Crimp valve on can.
- 4. Charge with Solstice Propellant.
- 5. Shake the can vigorously until uniform.

<sup>&</sup>lt;sup>2</sup> ASTM E-681, EU A11

<sup>&</sup>lt;sup>3</sup> Solstice Enhance: VOC-exempt (U.S. EPA), Solstice Propellant: VOC-exempt (U.S. EPA and CARB); negligible contribution to smog formation

For more information:

call 800-631-8138 (U.S. and Canada) or your local sales office.

www.hwll.co/personalcare

**Honeywell Advanced Materials** 115 Tabor Road Morris Plains, NJ 07950 Solstice is a registered trademark of Honeywell International Inc.
AHCOHOL™ 1618TA is a registered trademark of Acme Hardesty Co.
DOWSIL™ 2503 Cosmetic Wax and DOWSIL™ 9041 Silicone Elastomer Blend are registered trademarks of The Dow Chemical Company.
Olivem® 1000 is a registered trademark of Hallstar.

Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein. Solstice is a registered trademark of Honeywell International Inc.





Euxyl® PE 9010 is a registered trademark of Schülke Inc.