

SAFETY AND COMPLIANCE JUST GOT EASIER

Nonflammable and Reduced-GWP Stationary Refrigerant Platform

Honeywell's new Solstice® N41 (R-466A*) refrigerant helps OEMs meet industry calls for changes in safety and environmental compliance. It's a nonflammable, reduced-GWP replacement for R-410A in air-conditioning applications.



Meeting A Major Industry Need For A Nonflammable R-410A Replacement

Solstice N41 Highlights



RELIABILITY

- Chemical Stability
- Material Compatibility
- Lubricant Compatibility



SAFETY

- Non Toxic
- Nonflammable



PERFORMANCE

- Capacity \geq 95%,
- Energy Efficiency \geq 100%,
- Glide $<$ 2°C
- Minimal changes in design



REGULATORY

- Ozone Depletion Potential (ODP) \sim 0
- Global Warming Potential (GWP) $<$ 750

* Provisional

Honeywell

DON'T JUST TAKE OUR WORD FOR IT

Solstice® N41 has been tested worldwide by more than 15 OEMs and five compressor manufacturers. The results they've experienced show why more and more OEMs and contractors are turning to Solstice N41. Highlights from the Dec 6-7, 2018 presentation at the International Symposium on New Refrigerants and Environmental Technology, Kobe, Japan:

TOSHIBA CARRIER: EVALUATION OF VRF SYSTEMS USING LOW GWP REFRIGERANT

- COP and Annual Performance Factor (APF) of the VRF system are almost equal to those using R-410A
- R-466A shows 30% lower LCCP than R-410A in test VRF system
- Cycle components can be designed without reviewing their design pressures
- There is high probability that similar product lineup and piping flexibility can be achieved

TRANE: EVALUATION OF HIGH PRESSURE CHILLER ALTERNATIVES

- Identified R-466A as "the first nonflammable that meets <750 GWP regulatory requirements"
- Efficiency is equal to or better than flammable alternatives
- R-466A is the most like R-410A with low glide (0 to <2K)

"HDR146 (R-466A) has good properties as an alternative to R410A"

"New nonflammable <750 GWP R466A appears to be an acceptable R-410A replacement"



Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

Honeywell Advanced Materials

115 Tabor Road
Morris Plains, NJ 07950
800-631-8138

4174 FP | September 2019
©2019 Honeywell International Inc. All rights reserved.

Honeywell