

SmartLine RM71 Guided Radar (TDR) Level Meter Applications

Measurement of Liquids in a Bypass Chamber



Honeywell's SmartLine® RM71 is a Guided Radar (TDR: Time Delay Reflectometry) Level Meter for measuring distance, level, interface, level and interface, volume and mass. A version with a remote housing can be mounted up to 14.5 m / 47.6 ft from the probe. The Guided Radar Level Meter has higher signal dynamics and a sharper pulse than conventional TDR devices and therefore better reproducibility and accuracy.

Where can the application be found

Chemicals, Petrochemicals, Oil & Gas, Minerals & Mining, Wastewater and Pulp & Paper

Who is interested in the solution


Instrument engineer, plant manager, maintenance engineer and environmental engineer

Equipment provided

SmartLine RM71 Guided Radar Level Meter

Process description

Honeywell's Guided Radar Level Meter can measure accurately in agitated conditions and in the presence of foam. If the tank is full of obstructions such as agitators and reinforcements, Honeywell recommends installing the Guided Radar Level Meter in a bypass chamber.



Solution description

- Accurate, continuous level measurement
- Overfill/spill protection
- Two wire design reduces installation cost

Benefits

- Improves process monitoring for higher quality product
- Prevention of spills
- Tighter monitoring of process level for reduced inventory cost
- Low installation and maintenance cost
- Design and Installation versatility to meet the specific needs of the application and installation

For More Information

To learn more about Honeywell's RM71 Guided Radar Level Meter, visit www.honeywell.com/ps or contact your Honeywell account manager.

Automation & Control Solutions

Process Solutions
Honeywell
2500 W. Union Hills Dr.
Phoenix, AZ 85027
Tel: +1-602-313-6665 or 877-466-3993
www.honeywell.com/ps

SmartLine® is a registered trademark of Honeywell International Inc.