

SmartLine

RMA801 SmartLine Remote DE or Analog Indicator Specification

34-ST-03-148, December 2025



Introduction

The Honeywell RMA801 is a DE or analog remote indicator suitable for use with any DE transmitter or a transmitter operating in analog, 4-20 mA mode. The RMA801 is part to the RMA 800 family and delivers the ability to locate a remote indicator away from a SmartLine transmitter. In this specific instance, the RMA801 is the remote display offering that supports Honeywell's DE protocol and thus it connects to the SmartLine family of transmitters when using DE protocol. Besides supporting DE protocol, the RMA801 is also capable of operating in analog only mode allowing it to connect to any transmitter with a 4-20 mA output including HART protocol transmitters.

Best in Class Features:

- RMA auto-configuration when connected to DE protocol transmitters
- Modular design hardware
- Dual compartment housing separating sensitive electronics from termination wiring
- Standard and custom measurement units available
- Integrated two configuration buttons
- Simple, easy to use interface
- Remote indicator diagnostic displays
- Reverse wiring polarity protection
- Functions as a second, remotely-located display for ease of view

Integral Keypad

The RMA801 features a built-in 2-button keypad on display, permitting display set-up and operation, including:

- RMA configuration for LRV, URV and engineering unit
- RMA calibration
- Display appearance (contrast setting)



Figure 1–RMA801 Remote Indicator

Display Characteristics

The RMA801 Remote Indicator features the following:

- 360° rotation in 90° Increments
- 2 lines, 8 characters
- Diagnostic messaging
- Custom units of measurement
- Standard units of measurement:

Temperature	°C, °F, °R, K, mV, Ohm
Pressure	inH2O@39°F, mH2O@4°C, cmH2O@4°C, Torr, mmH2O@68°F, ftH2O@68°F, inH2O@68°F, inH2O@60°F, atm, Pa, kPa, MPa, gf/cm2, kgf/cm2, psi, mbar, bar, inHg@0°C, mmHg@0°C, mmH2O@4°C.
Flow	ft3/sec, gal/min, gal/hr, liter/min, liter/hr, m3/sec, m3/hr, Pounds per sec(lbm/sec), Pounds per min (lbm/min), Pounds per hr(lbm/hr), kg/sec, kg/hr, Standard Cubic Feet per min (SFt3/m), Standard Cubic Feet per hr (SFt3/h), Standard Cubic Feet per Day (SFt3/d), Metric Standard Cubic Feet per Hour(MSCFH), Normal Cubic meter per hr(NM3/h), Million Standard Cubic Feet per Day (MMSCFD), Million Standard Cubic Feet per Hour (MMSCFH)
Level	ft, in, m, cm, mm, %

Display Screens & Diagnostics

Similar to all other SmartLine products, the display rotation and contrast settings are user configurable.

The RMA801 remote indicator can rotate the display in 90 deg and cover 360 deg manually

Diagnostic messages



BAD-Tx

Transmitter critical diagnostic condition present



BAD-RMA

RMA diagnostics present



RMA DG

RMA Diagnostics

Figure 2: Standard Display screens

Specifications

Operating Conditions						
Parameter	Reference Condition		Operative Limits		Transportation and Storage	
	°C	°F	°C	°F	°C	°F
Ambient Temperature	25±1	77±2	-40 to 70*	-40 to 158	-30 to 80	-22 to 175
Humidity (%RH)	10 to 55		0 to 100		0 to 100	

Note: LCD display ambient temperature: -30°C to +70°C. LCD display storage temperature: -30°C to +80°C. The display will be slower and may become unreadable as the ambient temperature drops below -20°C to -30°C. It will return to normal functionality once the ambient temperature rises above -20°C.

Physical/Functional Specifications	
Parameter	Description
Input Signal	4-20 mA DC
Max Voltage drop	2.3V @ 21.5mA
Drop under Failure conditions	5.6V
Min loop operating current	3.6mA
Vibration:	IEC 60770-1 field or pipeline, vibration (10-2000 Hz: 0.21mm displacement / 3g max acceleration)
Electromagnetic Compatibility	IEC 61326-3-1
Electronic Housing	Pure Polyester Powder Coated Low Copper (<0.4%) Aluminum. Meets NEMA 4X, IP66, IP67 and NEMA 7 (explosion proof). All stainless-steel housing is optional. Cover o-ring material: Silicone
Wiring	Accepts up to 16 AWG (1.5 mm diameter).
Mounting Bracket	Carbon Steel (zinc-chromate plated) or 316 Stainless Steel. Suitable for wall or 2" (50mm) vertical or horizontal pipe mounting.
Electrical Connections	½"-14 NPT or M20
Dimensions	See Figure 3 and Figure 5
Net Weight	2.5 lbs (1,1 kg) with aluminum housing

Performance	
Parameter	Description
Accuracy: <ul style="list-style-type: none"> • Analog 4-20 mA Mode • Temperature Effect • DE 	+/- 0.1% of Span under standard conditions +/- 0.01 % of Span under standard conditions Same as transmitter*
Display	Digital Readout: 7 digits,
Display Resolution	0.01 unit for reading range (-999 to 999) 0.1 unit for reading range (-9999 to -1000) or (1000 unit to 9999). 1 unit for reading range (-99999 to -10000) or (10000 to 99999). 10 units for reading range (-999999 to -100000) or (100000 to 999999).

*Reproduces the transmitter signal exactly to within its resolution

Mounting & Dimensional Drawings

Reference Dimensions: $\frac{\text{millimeters}}{\text{inches}}$




Figure 3 – RMA Dimensions

Mounting & Dimensional Drawings

TRANSMITTER ENCLOSURE CAN BE ROTATED A TOTAL OF 90° FROM THE STANDARD MOUNTING POSITION




Figure 4 - Wall Mounting




Figure 5 - Pipe Mount, Horizontal & Vertical

Mounting & Dimensional Drawings

TRANSMITTER ENCLOSURE CAN BE ROTATED A TOTAL OF 90° FROM THE STANDARD MOUNTING POSITION




Figure 6: Pipe Mount - Horizontal Mounting Bracket




Figure 7: Pipe Mount - Vertical Mounting Bracket

Approval Certifications:

MSG CODE	AGENCY	TYPE OF PROTECTION	Electrical Parameters	Ambient Temperature
C	ATEX	Flame-proof and Dust:  II 2 G Ex db IIC T6..T5 Gb II 2 D Ex tb IIIC T 95°C Db	Note 1	T6: -50°C to 65°C T95°C, T5: -50°C to 85°C
		Intrinsically Safe:  II 1 G Ex ia IIC T4 Ga II 3 G Ex ic IIC T4 Gc	Note 2	-50°C to 70°C
		Non-Incendive  II 3 G Ex ec IIC T4 Gc	Note 1	-50°C to 85°C
		Enclosure: Type IP66/ IP67	ALL	ALL
		STANDARDS: EN 60079-0: 2018; EN 60079-1: 2014; EN 60079-11: 2012; EN 60079-31: 2014; EN 60079-7: 2015+A1: 2018;		
C	UKEX	Flame-proof and Dust:  II 2 G Ex db IIC T6..T5 Gb II 2 D Ex tb IIIC T 95°C Db	Note 1	T6: -50°C to 65°C T95°C, T5: -50°C to 85°C
		Intrinsically Safe:  II 1 G Ex ia IIC T4 Ga II 3 G Ex ic IIC T4 Gc	Note 2	-50°C to 70°C
		Non-Incendive  II 3 G Ex ec IIC T4 Gc	Note 1	-50°C to 85°C
		Enclosure: Type IP66/ IP67	ALL	ALL
		STANDARDS: EN 60079-0: 2018; EN 60079-1: 2014; EN 60079-11: 2012; EN 60079-31: 2014; EN 60079-7: 2015+A1: 2018;		
D	IECEX	Flame-proof: Ex db IIC T6..T5 Gb Ex tb IIIC T 95°C Db	Note 1	T6: -50°C to 65°C T95°C, T5: -50°C to 85°C
		Intrinsically Safe: Ex ia IIC T4 Ga Ex ic IIC T4 Gc	Note 2	-50°C to 70°C
		Non-Incendive Ex ec IIC T4 Gc	Note 1	-50°C to 70°C
		Enclosure: IP66/ IP67	ALL	ALL
		STANDARDS: IEC 60079-0: 2018; IEC 60079-1: 2014; IEC 60079-11: 2011; IEC 60079-7: 2017; IEC 60079-31: 2014		
E	SAEx	Flame-proof: Ex db IIC T6..T5 Gb Ex tb IIIC T 95°C Db	Note 1	T6: -20°C to 65°C T95°C, T5: -20°C to 85°C
		Intrinsically Safe: Ex ia IIC T4 Ga Ex ic IIC T4 Gc	Note 2	-20°C to 70°C
		Non-Incendive Ex ec IIC T4 Gc	Note 1	--20°C to 85°C
		Enclosure: IP66/ IP67	ALL	ALL
		STANDARDS: IEC 60079-0: 2011; IEC 60079-1: 2014; IEC 60079-11: 2011; IEC 60079-7: 2006; IEC 60079-31: 2013		
F	INMETRO	Flame-proof: Ex db IIC T6..T5 Gb Ex tb IIIC T 95°C Db	Note 1	T6: -50°C to 65°C T95°C, T5: -50°C to 85°C
		Intrinsically Safe: Ex ia IIC T4 Ga Ex ic IIC T4 Gc	Note 2	-50°C to 70°C

		Non-Incendive Ex ec IIC T4 Gc	Note 1	--50°C to 85°C
		Enclosure: IP66/ IP67	ALL	ALL
		STANDARDS: ABNT NBR IEC 60079-0: 2018; ABNT NBR IEC 60079-1: 2016; ABNT NBR IEC 60079-11: 2013; ABNT NBR IEC 60079-7: 2018; ABNT NBR IEC 60079-31: 2014		
G	NEPSI	Flame-proof: Ex d IIC T6/T5 Gb Ex tD A21 IP66/67 T95°C	Note 1	T6: -50°C to 65°C T95°C, T5: -50°C to 85°C
		Intrinsically Safe: Ex ia IIC T4 Ga Ex ic IIC T4 Gc	Note 2	-50°C to 70°C
		Non-Incendive Ex nA IIC T4 Gc	Note 1	--50°C to 85°C
		Enclosure: IP66/ IP67	ALL	ALL
		STANDARDS: GB 3836.1-2010; GB 3836.2-2010; GB 3836.4-2014; GB 3836.19-2010; GB 3836.20-2010; GB 12476.1-2013; GB 12476.5-2013		
P	CCoE/ PESO	Flame-proof: Ex db IIC T6..T5 Gb	Note 1	T6: -50°C to 65°C T5: -50°C to 85°C
		Intrinsically Safe: Ex ia IIC T4 Ga	Note 2	-50°C to 70°C
		Enclosure: IP66/ IP67	ALL	ALL
		STANDARDS: IEC 60079-0: 2011; IEC 60079-1: 2014; IEC 60079-11: 2011; IEC 60079-7: 2006; IEC 60079-31: 2013		
K	cCSAus	Explosion proof: Class I, Division 1, Groups A, B, C, D;T6..T4	Note 1	T6: -50°C to +65°C T4, T5: -50 °C to 85°C
		Dust Ignition Proof: Class II, III, Division 1, Groups E, F, G; T4 Class I Zone 1 Ex db IIC T4 Gb Ex db IIC T4 Gb Zone 21 Ex tb IIIC T 95°C Db Ex tb IIIC T 95°C Db		
		Intrinsically Safe: CSA 14.2689056 Class I, II, III, Division 1, Groups A, B, C, D, E, F, G; T4 Ex ia IIC T4 Ga	Note 2	-50°C to 70°C
		Non-Incendive Class I, Division 2, Groups A, B, C, D; T4 Class I Zone 2 Ex nA IIC T4 Gc Ex nA IIC T4 Gc	Note 1	-50°C to 85°C
		Enclosure: Type 4X/ IP66/ IP67	ALL	ALL
		Standards: CSA C22.2 No. 0: 2015; CSA C22.2 No. 30: 2016; CSA C22.2 No. 94-M91; CSA C22.2 No. 25: 2017; CSA C22.2 No. 61010-1: 2017; CSA-C22.2No.157: 2016; C22.2 No. 213: 2017; C22.2 No. CSA 60079-0:2015; C22.2 No. 60079-1: 2016; C22.2 No. 60079-11: 2014; C22.2 No. 60079-15: 2016; C22.2 No. 60079-31: 2015; ANSI/ ISA12.12.01-2017; ANSI/ ISA 61010-1: 2016; ANSI/ UL 60079-0: 2013; ANSI/ UL 60079-1: 2015; ANSI/ UL 60079-11: 2014; ANSI/ UL 60079-15: 2013; ANSI/ UL 60079-31: 2015 ; FM 3600: 2011; FM 3615: 2006; FM Class 3616: 2011; ANSI/ UL 913: 2015; UL 916: 2015; ANSI/ UL 12.27.01: 2017; ANSI/UL 50E: 2015		

Notes**1. Operating Parameters:**

Input : 4-20 mA ; 42VDC max, 30mA.

2. Intrinsically Safe Entity Parameters

For details see Control Drawing, 50089981.

Model Selection Guide

The Model Selection Guide is subject to change and is inserted into the specification as guidance only.

Model Selection Guide

34-ST-16-90 Issue 25

Instructions: Make selections from all Tables Key through VI using column below the proper arrow. Asterisk indicates availability. Letter (a) refer to restrictions highlighted in the restrictions table. Tables delimited with dashes.

List Price: Price equals the sum of prices for all selections made.

Key	I	II	III	IV	V	VI
RMA80_	-	-	-	-	-	00000

KEY NUMBER	BASE MODEL
Remote Indicator	DE Protocol or Analog (4-20mA DC) Foundation Fieldbus

Selection		
RMA801	↓	
RMA803		↓

TABLE I	AGENCY APPROVALS (see data sheet for Approval Code Details)
Approvals	No Approvals Required
	FM Explosion proof, Intrinsically Safe, Non-incendive, & Dustproof
	cCSAus Explosion proof, Intrinsically Safe, Non-incendive, & Dustproof
	ATEX Explosion proof, Intrinsically Safe & Non-incendive
	IECEX Explosion proof, Intrinsically Safe & Non-incendive
	cCSAus Explosion proof, Intrinsically Safe, Non-incendive, & Dustproof-Canada & US
	SAEx Explosion proof, Intrinsically Safe & Non-incendive
	KOSHA Explosion proof, Intrinsically Safe & Non-incendive
	CCoE Explosion proof, Intrinsically Safe & Non-incendive

0	*	*
A		*
B		*
C	*	*
D	*	*
K	*	
E	*	*
H	*	
P	*	*

TABLE II	TRANSMITTER ELECTRONICS SELECTIONS		
a. Electronic Housing Material & Connection Type	Material	Connection	Lightning Protection
	Polyester Powder Coated Aluminum	1/2 NPT	None
	Polyester Powder Coated Aluminum	M20	None
	Polyester Powder Coated Aluminum	1/2 NPT	Yes
	Polyester Powder Coated Aluminum	M20	Yes
	316 Stainless Steel (Grade CF8M)	1/2 NPT	None
	316 Stainless Steel (Grade CF8M)	M20	None
	316 Stainless Steel (Grade CF8M)	1/2 NPT	Yes
316 Stainless Steel (Grade CF8M)	M20	Yes	
b. Protocol Compatibility	Communications Protocol		
	DE protocol or Analog (4-20mA DC) Foundation Fieldbus Enabled		
c. Customer Interface Selections	Display	External Config Buttons	Languages
	Standard	None (Integrated on Display)	English
	Advanced	None	EN, GE, FR, IT, SP, RU, TU
	Advanced	External	EN, GE, FR, IT, SP, RU, TU
	Advanced	None	EN, CH, JP
Advanced	External	EN, CH, JP	

A__	*	*
B__	*	*
C__		*
D__		*
E__	*	*
F__	*	*
G__		*
H__		*

D	*	
F		*

__A	*	
__D		*
__E		*
__H		*
__J		*

TABLE III	CONFIGURATION SELECTIONS	
a. Application Software	Application Software	
	Standard Software Additional Function Blocks (Fieldbus Only: Adds PID, Char, Arith, Selector & Integ blocks)	
b. Configuration	Factory Configuration	Write Protection
	Factory Standard Factory Standard	Disabled Enabled

1_	*	*
2_		*

_S	*	*
_T	*	



TABLE IV		ACCESSORY SELECTIONS	
	Bracket Type	Material	
a. Mounting Bracket	None	None	
	Flat Pipe Mounting Bracket	Carbon Steel	
	Flat Pipe Mounting Bracket	316 Stainless Steel	
	Wall Mounting Bracket	Carbon Steel	
	Wall Mounting Bracket	316 Stainless Steel	
	Angle Pipe Mounting Bracket	Carbon Steel	
	Angle Pipe Mounting Bracket	316 Stainless Steel	
	Customer Tag Type		
b. Customer Tag	No customer tag		
	One Wired Stainless Steel Tag (Up to 4 lines 26 char/line)		
	Two Wired Stainless Steel Tag (Up to 4 lines 26 char/line)		
Unassembled Conduit Plugs & Adapters			
c. Unassembled Conduit Plugs & Adapters	No Conduit Plugs or Adapters Required		
	1/2 NPT Male to 3/4 NPT Female 316 SS Certified Conduit Adapter		
	1/2 NPT 316 SS Certified Conduit Plug		
	M20 316 SS Certified Conduit Plug		

0	---	*	*
1	---	*	*
2	---	*	*
3	---	*	*
4	---	*	*
6	---	*	*
7	---	*	*

0	---	*	*
1	---	*	*
2	---	*	*

A0	---	*	*
A2	---	n	n
A6	---	n	n
A7	---	m	m

TABLE V		OTHER Certifications & Options:(String in sequence comma delimited (XX, XX, XX,...))	
a. Additional Options	None - No additional options required		
	Certificate of Conformance		
	Certificate of Origin		
	Extended Warranty Additional 1 year		
	Extended Warranty Additional 2 years		
	Extended Warranty Additional 3 years		
	Extended Warranty Additional 4 years		
	Extended Warranty Additional 15 years		

00	*	*
F3	*	*
F5	*	*
01	*	*
02	*	*
03	*	*
04	*	*
15	*	*

b

TABLE VI		MANUFACTURING SPECIALS	
Factory	Factory Identification		

0000	*	*
------	---	---

MODEL RESTRICTIONS

Restriction Letter	Available Only with		Not Available with	
	Table	Selection(s)	Table	Selection(s)
m	Ia	B, D, F, H		
n	Ia	A, C, E, G		
b	Select only one option from this group			

PRODUCT MANUALS

Description	Part Number
RMA801 Remote Meter Assembly HART / DE manual - English	34-ST-25-62
RMA803 Remote Meter Assembly Foundation Fieldbus manual - English	34-ST-25-51

All product documentation is available at www.honeywellprocess.com.

Sales and Service

For application assistance, current specifications, pricing, or name of the nearest Authorized Distributor, contact one of the offices below.

ASIA PACIFIC

Honeywell Process Solutions,
(TAC) hfs-tac-support@honeywell.com

Australia

Honeywell Limited
Phone: +(61) 7-3846 1255
FAX: +(61) 7-3840 6481
Toll Free 1300-36-39-36
Toll Free Fax:
1300-36-04-70

China – PRC - Shanghai

Honeywell China Inc.
Phone: (86-21) 5257-4568
Fax: (86-21) 6237-2826

Singapore

Honeywell Pte Ltd.
Phone: +(65) 6580 3278
Fax: +(65) 6445-3033

South Korea

Honeywell Korea Co Ltd
Phone: +(822) 799 6114
Fax: +(822) 792 9015

EMEA

Honeywell Process Solutions,
Phone: (TAC) + 80012026455 or
+44 1202645583

Email: (Sales)

FP-Sales-Apps@Honeywell.com

or

(TAC)

hfs-tac-support@honeywell.com

Web

Knowledge Base search
engine <http://bit.ly/2N5Vldi>

AMERICA'S

Honeywell Process Solutions,
Phone: (TAC) 1-800-423-9883 or
215/641-3610
(Sales) 1-800-343-0228

Email: (Sales)

FP-Sales-Apps@Honeywell.com

or

(TAC)

hfs-tac-support@honeywell.com

Web

Knowledge Base search
engine <http://bit.ly/2N5Vldi>

Specifications are subject to change without notice.

For more information

To learn more about SmartLine devices,
visit <https://process.honeywell.com/>

Or contact your Honeywell Account Manager

Process Solutions

Honeywell
1250 W Sam Houston Pkwy S
Houston, TX 77042

Honeywell Control Systems Ltd
Honeywell House, Skimped Hill Lane
Bracknell, England, RG12 1EB

Shanghai City Centre, 100 Jungi Road
Shanghai, China 20061

<https://process.honeywell.com/>



34-ST-03-148
December 2025
©2025 Honeywell International Inc.