

# HF ACID PRODUCT OVERVIEW

**Performance You Need.  
Quality You Count On.**

For more than 55 years, Solstice has been the trusted source for HF Acid supply. Our high quality HF Acid is safely and reliably manufactured, transported, and delivered from our state-of-the-art Geismar, La. production facility.



# The #1 Choice for HF Acid

Our production experience, robust inventory, and industry-leading railcar and truck fleet give us greater flexibility to meet your needs. Our facility in Geismar, LA is the largest HF plant in the world and is operated by Solstice's highly-trained HF Acid team. We have the HF products you need, when you need them. Why settle for less?

## Benefits of Using Solstice HF Acid

- Reliable, U.S.-based production.
- Robust supply chain.
- Modern rail and truck fleet (Solstice - employed drivers).
- Technical support:
  - Over 1,000 customers and emergency responders trained annually.
- Strategically vested - HF Acid is the foundation for Solstice's next-generation fluorine molecules.

## Applications

### Anhydrous HF Acid:

- Fluorinated carbon compounds.
- Raw materials for petrochemical and plastics industries.

### Aqueous HF Acid - 70% and 49% Solution

- Stainless steel and titanium pickling.
- Glass etching/frosting.
- Quartz purification.
- Chemical milling.
- Feedstock in production of chemical derivatives.



	Anhydrous	Aqueous 70% Solution	Aqueous 49% Solution
Appearance	Colorless liquid, fumes in air	Colorless liquid, fumes in air	Colorless liquid
Physical State	Liquid	Liquid	Liquid
Chemical Formula	HF	70% HF in H <sub>2</sub> O by weight	49% HF in H <sub>2</sub> O by weight
Specific Gravity	Water=1.0)0.97 @ 70°F (21.1 °C)	Water=1.0)1.225 @ 70°F (21.1 °C)	Water=1.0)1.175 @ 60°F (15.5 °C)
Solubility in Water	100% by weight	100% by weight	100% by weight
Boiling Point	67.2 °F (19.54 °C)	151 °F (66 °C)	224 °F (106 °C)
Melting Point	-118 °F (-84 °C)	-95.8 °F (-71 °C)	-34 °F (-37 °C)
Vapor Pressure	776 mmHg at 70 °F (21.1 °C)	110 mmHg at 70 °F (21.1 °C)	27 mmHg at 70 °F (21.1 °C)
Vapor Density (Air=1.0)	2.21 at 70 °F, 1.76 at 80 °F (26.67°C)	2.21 at 70 °F, 1.76 at 80 °F (26.67°C)	2.21 at 70 °F, 1.76 at 80 °F (26.67°C)
% Volatiles	100%	100%	100%
Ionization Potential	15.98 eV	15.98 eV	15.98 eV
Flash Point	Nonflammable	Nonflammable	Nonflammable

For more information, click [HERE](#) or scan the QR code to contact us.



Although Solstice Advanced Materials Inc believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Solstice Advanced Materials Inc, either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.



[solstice.com](http://solstice.com)  
Solstice Advanced Materials  
115 Tabor Rd.  
Morris Plains, NJ 07950

Version MAR 2026  
© 2026 Solstice Inc.