

## Product Family



### Miller Descent Devices (AUS)

Manual Descent Device is designed for a variety of applications where smooth, controlled descent from an elevated position is required.

[Visit MillerFallProtection.com >](http://MillerFallProtection.com)



## Product Numbers & Ordering Information

	Product Numbers	Details
	13506	<b>Pro ALLP tech descender</b> Finger tip control and hands free descent; 586 grams; Certification to EN12841-Descenders
	M1030029	<b>Descender Unit only DSD-30</b> operator can control the rate at which they descend to the ground; Stainless Steel cam.; Double locking with double security handle; Hole for karabiner attachment at bottom of 15mm dia; Certification to EN341 as a descender

### Additional Information

Pro Allp Tech unit (13506) can be set for rapid descent and allows finger tip control and hands free descent, allowing maximum casualty care.

## Overview

### Key Features

Vertical descent units acts so that the operator can control the rate at which users descend to the ground. Users can set their own rate of descent, or rely on ground personnel to assist with descent.

### Recommended Industries/Use

- Agriculture
- Chemical
- Construction
- Food Services
- Forestry
- Manufacturing
- Mining
- Municipal Services
- Oil and Gas
- Pharmaceutical
- Steel and Metals
- Transportation
- Utilities

### Hazards

- Confined Space
- Fall from height

### Regulations

- Carries certification to EN341 as a descender (M1030029), EN12841-Descenders

## Warranty Information

MILLER FALL PROTECTION PRODUCT TOTAL SATISFACTION ASSURANCE At Sperian Protection, we have been providing quality Miller brand fall protection equipment to millions of workers worldwide since 1945. LIMITED LIFETIME WARRANTY BACKED BY OVER 60 YEARS IN THE FALL PROTECTION BUSINESS We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous tests to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 1300 139 166 (Aust customers) or 0800 322 200 (NZ customers) Manufacturing specifications are subject to change without notice.

## Specifications

### Double Locking (M1030029)

- If the operator panics, the unit will lock up.

### Markings (M1030029)

- The DSD-30 has a clear roping path printed onto the unit.

### Load (M1030029)

- Can be used with 2 people at a time. It is recommended that secondary belaying in the rescue situation.

### Threading (M1030029)

- The unit swings open to allow for easy roping.

### Rope diameter

- (M1030029) - 11mm kernmantle rope & 12mm polyester rope, (13506) - min 10.5mm, max 12.7mm

### Weight

- (M1030029) - 379g, (13506) - 586g

### Specification Sheets

- For full engineering specification sheets, go to the spec sheet section under downloads and documentation

## Literature & Documents

### M1030029 DSD 30 Vertical Descent Unit AUS NZ 2016

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Ascenders\\_\\_Descenders/4294998718/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Ascenders__Descenders/4294998718/1033.aspx)

□ □

### Instructions Miller DSD-30 Descender - AUS

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Ascenders\\_\\_Descenders/15826/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Ascenders__Descenders/15826/1033.aspx)

Miller DSD-30 M1030029 Descent unit

### Miller Industry Fall Protection Guide Poster - AUS

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/24943/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/24943/1033.aspx)

Industry Fall Protection Guide Post 13 Sperian Protection Australia Pty Ltd 3 Walker St, Braeside, Victoria 3195 Australia  
Tel: 1300 139 166 Fax: 1300 362 491 New Zealand Tel: 0800 322 200 [www.sperianprotection.com.au](http://www.sperianprotection.com.au) POLYESTER CONSTRUCTION HARNESS WEBBING LANYARD ADJUSTABLE LANYARD MILLER ANCHOR GRIPS™ TIE-OFF ADAPTOR

### ProAllp Tech Descender 13506 AUS NZ -2016

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/4294999042/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/4294999042/1033.aspx)

## Training & Proper Use

## Miller Descent Devices (AUS)

Please refer to product instruction sheets included with the products prior to use.

### Additional Information

[marketing.australia@sperianprotection.com](mailto:marketing.australia@sperianprotection.com) or ph: 1300 139 166

### Technical Support

1300 139 166 (Aust) or 0800 322 200 (NZ)

© Honeywell International Inc.