

Miller Black Rhino Self-Retracting Lifelines (SRL)

Description

The Black Rhino SRLs are designed with stainless steel wire rope to endure the daily rigors of harsh environments. Ideal for concrete construction, welding, steel erection, food processing and warehouse applications.

Materials

Cover:	Impact-resistant thermoplastic over aluminum
Housing:	Aluminum
Hub:	Aluminum
Braking Mechanism:	Stainless Steel
Lifeline:	3/16" Stainless Steel Wire Rope
Snap Hook:	Zinc-plated, locking rebar hook with 2 1/2-inch opening and load indicator (CFL-5, CFL-6).

Technical

Max. Capacity:	310 lbs. (141kg)
Working Length Capacity:	9 ft. (2.7m)
Max. Arrest Distance	24-in. (610mm)
Avg. Arresting Force:	900 lbs. (4kN) (When tested to ANSI Z359.14)
Max. Peak Arresting Force:	1,800 lbs. (8kN) (When tested to ANSI Z359.14)
Max. Peak Arresting Force:	900 lbs. (4kN) (When tested to OSHA 1926.502 and CSA Z259.2.2)
Ultimate Strength:	3,000 lbs. (13kN)
Lifeline Tension:	3 lbs. – 11 lbs. (13N – 49N)

Certification

Meets OSHA 1926.502, 1910.66, ANSI A10.32, *ANSI Z359.14-2012 Class A and B, and CSA Z259.2.2 Type 1 requirements.

*ANSI Z359 and CSA Z259.12-11 compliant for connectors that meet the 3,600lb gate requirements.



Miller Black Rhino Self-Retracting Lifelines (SRL)

ANSI A10.32 and CSA Z259.2.2 Compliant Models			
Model No.	Anchorage Connection	Connection to Harness	Weight
CFL-1/9FT	None (need carabiner, not included)	Locking, swivel snap hook with load indicator	4.3 lbs (1.9 kg)
CFL-2/9FT	Steel twist-lock carabiner	Locking, swivel snap hook with load indicator	4.8 lbs (2.2 kg)
CFL-3/9FT	Stainless steel swivel (need carabiner, not included)	Locking, swivel snap hook with load indicator	4.5 lbs (2.0 kg)
CFL-4/9FT	Stainless steel swivel and steel twist-lock carabiner	Locking, swivel snap hook with load indicator	5.0 lbs (2.3 kg)
CFL-5/9FT	Stainless steel swivel and locking rebar snap hook	Locking, swivel snap hook with load indicator	5.7 lbs (2.6 kg)
CFL-6/9FT	Stainless steel swivel and steel twist-lock carabiner	Locking, 2-1/2" (63mm) rebar hook with load indicator	5.15 lbs (2.35 kg)
ANSI Z359 Compliant Models (Meets the 3,600 gate requirements)			
Model No.	Anchorage Connection	Connection to Harness	Weight
CFL-2-Z7/9FT*	Steel twist-lock carabiner	Locking, swivel snap hook with load indicator	4.8 lbs (2.2 kg)
CFL-3-Z7/9FT*	Stainless steel swivel (need carabiner, not included)	Locking, swivel snap hook with load indicator	4.5 lbs (2.0 kg)
CFL-4-Z7/9FT*	Stainless steel swivel and steel twist-lock carabiner	Locking, swivel snap hook with load indicator	5.0 lbs (2.3 kg)
CFL-5-Z7/9FT*	Stainless steel swivel and rebar locking snap hook	Locking, swivel snap hook with load indicator	5.7 lbs (2.6 kg)
CFL-6-Z7/9FT*	Stainless steel swivel and steel twist-lock carabiner	Locking, 2 1/2" (63mm) rebar hook with load indicator	5.5 lbs (2.5 kg)

*ANSI Z359 and CSA Z259.12-11 compliant for connectors that meet the 3,600 lb. gate requirements.



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

⚠ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.