



Product Family

Miller Revolution Harnesses

The Revolution Harness reinvents harness safety and functionality with features developed to meet key, user needs. Exceeding worker expectations in comfort, fit, ease-of-use, style, durability, compliance, flexibility and convenience, the Revolution provides over 11 key product features from 7 new, unique components.

[Visit MillerFallProtection.com](http://MillerFallProtection.com) > Miller Logo

Product Numbers & Ordering Information

Overview

Key Features

- **Web Finials** - Clip-on design safely organizes webbing after proper adjustment
- **PivotLink Connection** - Unique rotary design provides greater comfort in bending/mobility
- **ErgoArmor Back Shield** - Semi-flexible back shield minimizes impact from sharp/heavy snap hooks and self-retracting lifelines
- **Cam Buckles** - Easy, one-hand adjustment/release allows simultaneous adjustment of shoulder straps
- **Self-Contained Label Pack** - Integrated pack encapsulates labels minimizing damage and loss
- **Integrated Accessory System** - Modular attachment design provides connection points for belts/tools/accessories

Recommended Industries/Use

- Construction
- Manufacturing
- Transportation

Hazards

- Confined Space
- Fall from height

Regulations

- Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

Maximum Working Capacity

- All Miller harnesses are rated to 400 lbs. capacity

DualTech Webbing

- Patent-pending DualTech webbing offers a soft, textured inside and a durable, chemical-resistant polyester outer material. Tested to 7,000 lbs. minimum tensile strength (40 percent stronger than ANSI requirements) for greater safety and longer service life.

DuraFlex Webbing

- Patented, elastomer webbing specially-formulated to stretch.

Python Webbing

- Patented, cushioned tubular webbing reduces stress to shoulders when using a tool belt.

Kevlar/Nomex Webbing

- Rugged, black Kevlar outside and gray Nomex inside provide superior comfort and durability for harsh working environments. Kevlar and Nomex are registered trademarks of E.I. DuPont

Specification Sheets

- For full engineering specification sheets, go to the spec sheet section under downloads and documentation

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

RELATED PRODUCTS