

# Miller YR Series Safety Straps

Models: 6YRLS/6FTBR, 7YRLS/7FTBR

## Description

Miller brand safety straps are equipped with locking snap hooks and are constructed with a red inner core/wear indicator. Should the red core become exposed, the strap must be removed from service. The YR Series safety strap is manufactured with six-ply nylon and remains flexible in all types of weather conditions. Tongue buckle adjuster included for quick, safe adjustment.



## Materials

<b>Webbing:</b>	1 3/4" 6-Ply Neoprene
<b>Hardware:</b>	Steel
<b>Rivets:</b>	Copper
<b>Label:</b>	Metal Tag

\*All hardware meets ASTM (50) fifty-hour salt spray test requirements.

## Technical

<b>Max. Working Load:</b>	310 lbs (kg)
<b>Webbing Min.</b>	
<b>Tensile:</b>	4,500 lbs (20kN)
<b>Snaps:</b>	5,000 lbs (22kN)
<b>Buckle Min. Tensile:</b>	4,000 lbs (18kN)

## Certification

OSHA 1926.159, 1926.959, 1926.502 (d),  
ANSI A10.32 and CSA Z259.3



Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • [www.millerfallprotection.com](http://www.millerfallprotection.com)

**WARNING!** THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.