




**Product Family**  
**Miller Series 70 Universal Rescue System**

Simple, one-person operation, the rope control handle allows the user to easily ascend and descend the rope line. Should an emergency rescue situation occur, a top-side worker may activate the system to retrieve the user.

[Visit MillerFallProtection.com](http://MillerFallProtection.com) > Miller Logo

**Product Numbers & Ordering Information**

Product Numbers	Details
 70-100/100FT	<b>ANSI Z359-2007 Compliant</b> 25' working length
 70-200/200FT	<b>ANSI Z359-2007 Compliant</b> ANSI Z359-2007 Compliant - 50' working length
 70-400/400FT	<b>ANSI Z359-2007 Compliant</b> ANSI Z359-2007 Compliant - 100' working length
 70-500/500FT	<b>ANSI Z359-2007 Compliant</b> ANSI Z359-2007 Compliant - 125' working length
 70-C/	<b>Series 70 Rope Control Handle</b> Rope control handle with attached Manyard shock-absorbing lanyard

**Overview**

**Key Features**

The Miller Series 70 Universal Rescue System is a lightweight, compact, versatile access and retrieval rope system. Simple, one-person operation, the rope control handle allows the user to easily ascend and descend the rope line. Should an emergency rescue situation occur, a top-side worker may activate the system to retrieve the user.

Ideal for refineries, grain elevators, subways, fire departments, breweries, chairlifts, window washing, confined

## Miller Series 70 Universal Rescue System

spaces, shipbuilding, transmission towers, power plants, offshore drilling and bridge inspection.

*A secondary fall arrest system is recommended.*

Aluminum head assembly with roller pulley and anti-reversing lock

- Kernmantle rope with a tensile strength of 5600 lbs. (25kN) and high-temperature resistance to 360°F (182°C)
- Rope control handle with friction locking device and with permanently attached Manyard shock-absorbing lanyard
- Two carabiners
- Convenient carrying bag

### Recommended Industries/Use

- Utilities

### Hazards

- Confined Space
- Fall from height

### Regulations

- Meets all applicable OSHA, ANSI and CSA standards

### Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

## Specifications

### Specification Sheets

- For full engineering specification sheets, go to the spec sheet section under downloads and documentation

### Kernmantle rope

- Tensile strength of 5,600 lbs. (25kN) and high-temperature resistance to 360°F (182°C)

### Fall Arrest

- A secondary fall arrest system is recommended

## Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

## Additional Information

800/873-5242 or 814/423-2118 email: millertecheexpert@sperianprotection.com

## Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertecheexpert@sperianprotection.com