

## Miller RA25-1/ Reusable Roof Anchor

The RA25-1/ temporary foldable roof anchor is used as part of a personal fall arrest system. It is designed for residential and commercial construction applications and comes complete with twelve (12) 2 1/2 in. #8 screws.

The RA25-1/ is intended for use on wood framed structures with pitches from 0-12/12. This allows for anchorage connection at the roof peak or in a flat position. The RA25-1/ may be secured with either 2 1/2 in. #8 screws or 16d nails.

### Materials

Anchor / D-Ring: Red painted 1020 carbon steel  
Screws: Flat head metal

### Technical

Weight: 2.46 lbs. (1.12 kg)  
Max. Working Load: 420 lbs. (190.51 kg)  
[fall arrest system must limit force to 1,800 lbf (8kN)]

### Certification

Meets OSHA1926.502 requirements



**Limitless Possibilities. Ask the Expert.**

**Technical Service: 800.873.5242**

[www.millerfallprotection.com](http://www.millerfallprotection.com)

### Honeywell Industrial Safety

900 Douglas Pike  
Smithfield, RI 02917

### USA

Phone: 800.430.5490  
Fax: 800.322.1330

### Canada

Phone: 888.212.7233  
Fax: 888.667.8477

**⚠ WARNING!** This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.