









North Rope Grabs_FP541_321_Main_main.jpg

Product Family
North Rope Grabs

Automatic rope grab with parking feature - 0.6m (2')
Soft Pak energy absorbing lanyard + double locking ergonomic snap hook for 13mm (1/2") cable

logo_North

Product Numbers & Ordering Information

	Product Numbers	Details
	FP541	Automatic Rope Grab with Panic Lock Rope grab will trail user without manipulation Rope grab will stop on a lifeline even when the panic lock is held open
	FP542	Automatic Rope Grab with Panic Lock FP541 with 2' (0.6 m) Lanyard energy absorber with snap hook
	FP543	Automatic Rope Grab with Panic Lock FP541 with 2' (0.6 m) lanyard
	FP561	Automatic rope grab with parking feature Bolt-action, quick closure system. FP560 series rope grab are compatible with 5/8" rope
	FP562	Automatic rope grab with parking feature FP561 with 6" (150 mm) web lanyard with carabiner
	FP563	Automatic rope grab with parking feature FP561 with 2' (0.6 m) web lanyard with snap hook
	FP564	Automatic rope grab with parking feature FP561 with 2' (0.6 m) Soft Pak energy absorbing lanyard with snap hook
	FP582	Automatic rope grab with parking feature FP561 with 6" (150 mm) soft pak energy absorbing lanyard with snap hook for 1/2" (13 mm) rope



FP584

AUTO.ROPE GRAB-S/A WEB/HOOK .5
AUTO.ROPE GRAB-S/A WEB/HOOK .5**Additional Information**

1-888-212-SAFE (7233)

Overview**Key Features**

The North Series Rope Grab is constructed of high strength materials, and plated steel against corrosion for long lasting service. North's FP540 Series Rope Grab is a simple, cost effective solution for fall arrest requirements. Its unique feature is that its cam lever is sprung to allow the cam to engage the lifeline even if the user grabs the cam lever (forcing it open) in the event of a fall. This eliminates the so-called "death grip fall" associated with regular rope grabs. The FP540 Series Rope Grab is designed for use in vertical applications of 16mm (5/8") approved synthetic rope only. It can be adjusted up or down the lifeline with little effort. Should a fall occur, the rope grab would lock onto the lifeline thus arresting the fall, and suspending the user. It can be purchased with attached lanyard or shock absorber, or without a lanyard.

Recommended Industries/Use

- Construction
- Manufacturing
- Utilities

Hazards

- Fall from height

Regulations

- Regulations - ANSI
- Regulations - CSA
- Regulations - OSHA

Training & Proper Use

See Operating and Maintenance Instruction Manual for details.

Technical Support

1.800.873.5242 or hsptechinfo@honeywell.com