



SP_EWash_PortaStreamIII_32_000310_0000-a

Product Family

Fendall Porta Stream III

Freeze-protected primary eyewash for indoor and outdoor use. The fluid-heating system makes it ideal for use between 72° and -32° F (22° to -36° C).

Product Numbers & Ordering Information

Product Numbers	Details
 32-000310-0000	Eyewash Station - English Fendall Porta Stream III Station w/ 180 oz. Saline - English (15 minute Heated) Ideal for use between 72° F and -32°D (22°C to -36°C), Twin 600 watt, 110 volt thermostatically controlled heater for indoor or outdoor use. Case Qty: 1 Case Dimentions: 26" x 20" x 20" Case Weight (lbs): 44
 32-000303-0000	Instruction Manual Fendall Porta Stream III Instruction Manual Case Qty: 1 Case Dimentions: 9" x 12" envelope Case Weight (lbs): 1
 32-000530-0000	Insulated Jacket Insulated Jacket for Fendall Porta Stream III Case Qty: 1 Case Dimentions: 24" x 8" x 15" Case Weight (lbs): 4
 32-000502-0000	Sperian Saline Solution - Ready to Use Ready-to-Use 1 Gallon Saline (3.8L) For use with Fendall Porta Steam I, II, and III. Case Qty: 4 Case Dimentions: 15" x 10" x 12" Case Weight (lbs): 38
 32-000513-0000	Sperian Saline Concentrate 180 oz. Saline Concentrate for Fendall Porta Stream I, II or other 14-16 gallon stations Case Qty: 4 Case Dimentions: 19" x 14" x 10" Case Weight (lbs): 52
 32-000513-0020	Sperian Saline Concentrate - English/French (Canada) 180 oz Saline Concentrate Eng/French for Fendall Porta Stream II, III or Other 14-16 Gallon Stations Case Qty: 4 Case Dimentions: 19"x14"x10" Case Weight (lbs): 52
 32-001100-0000	Sperian Water Additive Water Additive - 8 oz for Fendall Porta Stream I, II and III Case Qty: 4 Case Dimentions: 5" x 5" x 7" Case Weight (lbs): 3
 32-001100-0022	Sperian Water Additive - French (Canada) Water Additive - 8 oz for Fendall Porta Stream I, II and III Case Qty: 4 Case Dimentions: 5"x5"x7 Case Weight (lbs): 3
 32-000204-0000	Replacement Part - Inspection Tag Inspection Tag for Fendall Porta Stream II, III Case Qty: 1 Case Dimentions: 9"x12"x1" Case Weight (lbs): 1

Fendall Porta Stream III



32-000203-0000

Replacement Part - Nozzle Assembly

Nozzle assembly for Fendall Porta Stream II, III (2 ea.) Case Qty: 1
Case Dimensions: 7" x 5" x 5" Case Weight (lbs): 1



32-000201-0000

Replacement Part - Locking Fill Cap

Locking fill cap for Fendall Porta Stream II, III Case Qty: 1 Case
Dimensions: 7" x 5" x 5" Case Weight (lbs): 1



32-000105-0000

Replacement Part - Wall Bracket

Wall bracket for Fendall Porta Stream I, II, III Case Qty: 1 Case
Dimensions: 7" x 5" x 5" Case Weight (lbs): 1



32-000102-0000

Replacement Part - Pull Strap

Pull Strap for Fendall Porta Stream I, II, III Case Qty: 1 Case Dimensions:
7" x 5" x 5" Case Weight (lbs): 1

Additional Information

Case Dimensions: 26" x 20" x 20", Case Weight: 44 lbs Ships with 180 oz. Sperian Saline concentrate, eyewash sign, fill cap, hanging bracket (no fasteners), instruction manual, mixing tag, MSDS (Material Safety Data Sheet) for Sperian Saline concentrate with mixing instructions, nozzles, pull strap, warranty card, and insulated cover

Overview

Key Features

Fendall Porta Stream III is freeze protected by a special form fitted insulated cover and twin, 600 watt, 110 volt thermostatically controlled heaters for indoor and outdoor use. The fluid-heating system makes it ideal for use between 72° and -32° F (22° to -36° C). Fendall Porta Stream III offers versatile portability and 15-minutes of uninterrupted flushing — without costly plumbing. Fendall Porta Stream's simplicity of installation and operation has made it a popular choice. Self-contained, it features a nozzle strap that is easily removed to activate flushing, leaving hands free to hold eyelids open. Can be easily and affordably placed near most workplace hazards with single bracket mounting device or transported with optional universal cart or universal stand. Molded handle accepts hanging bracket for vertical or horizontal surface installation.

- Large 16 gallon (60.5L) capacity permits thorough flushing by providing 0.4 gpm over the entire 15-minute flushing period required by ANSI Z358.1
- Efficient "full-flow" nozzles cover a wide area around the eyes.
- Sturdy, molded construction. When properly installed, the system may be safely leaned upon during use.
- Large fill hole/lockable fill cap simplifies refilling and cleaning, and reduces risk of possible tampering.
- Easy-to-use design features simple, highly visible operating instructions on the unit itself.

Hazards

- Airborne Particulates
- Biohazard
- Chemical
- Contamination
- Gas, Vapors, Smoke
- Splash

Regulations

- ANSI Z358.1 - Meets ANSI Z358.1 15-minute flushing requirement

Historical Brand

Fend-All

Warranty Information

Sperian Eye & Face Protection, Inc., warrants that Sperian Eye & Face, Inc. Emergency Eyewash products are free of defects in material and workmanship for one (1) year from the date of shipment under the following conditions: 1. This limited warranty is effective only if the Sperian Eye & Face Protection, Inc. product is installed, maintained and used for the purpose intended and in accordance with the Sperian Eye & Face Protection, Inc. Installation and Operation Manual. 2. Sperian Eye & Face Protection, Inc.'s only obligation under this limited warranty shall be the repair or replacement, without charge, of any products or components, which upon inspection by Sperian Eye & Face Protection, Inc., are determined to be defective in materials or workmanship. 3. This limited warranty does not cover any damage, loss or expense due to damage caused by accident, abuse, improper installation, or improper maintenance. 4. No warranty is provided if any portion of the product covered by this limited warranty is altered or modified without the express written consent of Sperian Eye & Face Protection, Inc.

Specifications

Solution

- Versatile flushing fluid options include Sperian Saline concentrate, Sperian Water Additive, 1 gallon container of Sperian Saline solution

Flow Duration

- 15 minutes

Dimensions

- 19 3/4" L x 24" H x 19" D

Capacity

- Large 16 gallon (60.5L) capacity permits thorough flushing by providing 0.4 gpm over the entire 15-minute flushing period required by ANSI Z358.1-2004.

Maintenance

- Replace Sperian Saline solution every 6 months, replace Sperian water additive every 4 months

Certifications

HON_Eyewash Cert_of_Compliance-7-2012

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Emergency_Eyewash/4294970336/1033.aspx

Training & Proper Use

Unit comes with installation and operation manual

Additional Information

Replacement parts and accessories available.

Technical Support

US Sperian Customer Care: 866-257-7374

RELATED PRODUCTS