

## Miller 210WLS-Z7 Non-Shock-Absorbing Lanyard

### Description

The 210WLS-Z7 is a non-shock-absorbing web lanyard designed for positioning and restraint applications. The standard 6' model is adjustable to 4' for greater versatility. It includes 2 locking snap hooks on either end.

### Materials

<b>Webbing:</b>	1 in. yellow nylon 1in. blue polyester (available with model 210WDLS)
<b>Minimum Tensile:</b>	5,000 lbs.
<b>Thread:</b>	Polyester thread, with a minimum tensile of 42 lbs.
<b>Hardware:</b>	Steel minimum tensile strength
<b>Locking Snap Hooks:</b>	5,000 lbs.(22kN), 3/4 in. (19mm) gate opening <i>*All hardware meets ASTM (5) fifty-hour salt spray test requirements.</i>
<b>Keeper:</b>	A black elastic keeper is used to hold the snap hook in position.

### Technical

Max. Working Load: 310 lbs. - 140.62 kg

### Certifications

Meets all applicable OSHA 1926.502, ANSI Z359.1, ANSI A10.32 and CSA Z259.11 requirements

### Sizes Available

Available in 5 ft., 6 ft., 8 ft., 10 ft., 12 ft., 16 ft., 20 ft., 25 ft., and 30 ft. lengths.



**WARNING: This product is to be used for positioning only, unless it is used in conjunction with a shock absorber.**

#### Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242  
www.millerfallprotection.com

#### Honeywell Industrial Safety

900 Douglas Pike  
Smithfield, RI 02917

#### USA

Phone: 800.430.5490  
Fax: 800.322.1330

#### Canada

Phone: 888.212.7233  
Fax: 888.667.8477

**!** This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.