

Non Shock-Absorbing Rope Lanyard

Models: 205RLS Series

Description

The 205RLS is a non-shock-absorbing rope lanyard designed for attachment to a full body harness with shoulder D-rings for the purpose of raising and lowering workers from a confined space. The 205RLS is available in three unique models that utilize different rope diameters with either nylon or polyester rope.

Materials

Rope Designations by Model:

205RLS-2 – 5/8" Spun Nylon
 205RLS-5 – 5/8" Filament Polyester
 205RLS-8 – 1/2" Filament Nylon

Splices: A standard four-tuck splice is hand-crafted on each end with a tensile strength equal to that of the rope. The ends of the rope are seared to prevent fraying. The last splice is treated with a nylon-based stiffening agent to prevent the splice from unraveling.

Thimbles: A round, black plastic thimble is used in each lanyard eye to protect the eye from wear.

Technical

Max. Working Load: 310 lbs (141 kg)

Sizes Available

All models listed above are available in lengths from 3-6 feet.

Certification

Meets OSHA 1926.502, 1910.66, ANSI A10.32, and CSA Z259.2.2 Type 1 requirements.



 **WARNING!**

This product is to be used for positioning only, unless it is used in conjunction with a shock absorber.

MILLER

by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.