

Miller Cross-Arm Chain Anchorage Connector

Model: 440/6FT

Description

The 6-ft. (1.8m) Chain Anchor provides a single user with an easy-to-install, temporary anchorage connector. It easily wraps around I-beams or other structures. This product safely wraps around corners and sharp edges and is ideal to use in environments where chemical, heat or welding splatter may occur.

Materials

Chain: 9/32" (7.1mm) Grade 80 Steel
Long Links: 1/2" (12.7mm) Alloy Steel
Connecting Links: 9/32" (7.1mm) Grade 80 Steel

*All hardware meets ASTM (50) fifty-hour salt spray test requirements

Technical

Maximum Working

Load Capacity:

400 lbs (181.4 kg)

Chain:

5,000 lbs (22 kN) minimum tensile strength

Links:

5,000 lbs (22 kN) minimum tensile strength

Length:

6 ft (1.8m)



Certification

OSHA 1926.502, OSHA 1910.66, ANSI A10.32 and ANSI Z359.1-2007

MILLER®

by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.