

Miller AirCore™ Steel and Aluminum Harnesses

Description

Patent-pending Miller AirCore™ Harnesses feature world-class, breathable padding and specially-formulated elastomer webbing that stretches to maximize comfort, improve safety and increase productivity.

Materials

Webbing (DuraFlex®): Stretchable Polyester (green or blue)
Cam Buckle: Anodized black aluminum
Elastic Keepers: Elastic
Thread: Polyester
Grommets: Stainless Steel
***Hardware:** Clear Chromate, Finished Carbon Steel or Aluminum with Clear Chromate

Back, Belt, Shoulder

Pads: Nylon, Polyester, Polyurethane, Poly Pro
Back Mesh Shield: Polyester mesh
Label Pack: Evoprene, Nylon

*All hardware meets ASTM (50) fifty-hour salt spray.

Technical

Max. Working Load: 400 lbs. (181.4 kg)
 Webbing Min. Tensile: 5,000 lbs. (22 kN)
 *D-Ring Min. Tensile: 5,000 lbs. (22 kN)
 *Buckle Min. Tensile: 4,000 lbs. (18 kN)

Certification

Harness meets OSHA 1926.502, ANSI A10.32, ANSI Z359.11-14 and CSA Z259.10-12 requirements.



AAF-QCBDPUG
AirCore™ Aluminum
Harness with
Front and Side D-Rings
(Universal Green)



AC-QC/UGN
AirCore™ Steel Harness
(Universal Green)



ACF-QCBDPUG
AirCore™ Aluminum
Harness with
Front and Side D-Rings
(Universal Green)



AC-QC/UBL
AirCore™ Steel
Harness (Universal Blue)

AirCore™ Harnesses with Front D-Ring

Miller AirCore™ Steel Harness with Front D-Ring							
Model Number	Front D-Ring	Side D-Rings	Chest Strap	Leg Strap	Lumbar Pad	Removable Belt	Weight
ACF-QCUG	Yes	No	Quick-Connect	Quick-Connect	No	No	4.1 lbs. (1.86 kg)
ACF-TBUG	Yes	No		Tongue	No	No	4.1 lbs. (1.86 kg)
ACF-QCDUG	Yes	Yes		Quick-Connect	No	No	4.8 lbs. (2.18 kg)
ACF-TBDUG	Yes	Yes		Tongue	No	No	4.8 lbs. (2.18 kg)
ACF-QCBDPUG	Yes	Yes		Quick-Connect	Yes	Yes	6.2 lbs. (2.81 kg)
ACF-TBBDPUG	Yes	Yes		Tongue	Yes	Yes	6.2 lbs. (2.81 kg)
Miller AirCore™ Aluminum Harness with Front D-Ring							
AAF-QCUG	Yes	No	Quick-Connect	Quick-Connect	No	No	3.6 lbs. (1.63 kg)
AAF-TBUG	Yes	No		Tongue	No	No	3.6 lbs. (1.63 kg)
AAF-QCDUG	Yes	Yes		Quick-Connect	No	No	4.0 lbs. (1.81 kg)
AAF-TBDUG	Yes	Yes		Tongue	No	No	4.0 lbs. (1.81 kg)
AAF-QCBDPUG	Yes	Yes		Quick-Connect	Yes	Yes	5.4 lbs. (2.45 kg)
AAF-TBBDPUG	Yes	Yes		Tongue	Yes	Yes	5.4 lbs. (2.45 kg)

Model numbers listed are **for size L/XL**. Harnesses are also available in **XS** through **4XL** by replacing the “U” in the model number with “XS” for Extra Small; “SM” for Small/Medium; “23X” for 2/3 XL; and “4X” for 4XL. To order a blue harness, simply replace the “G” in the model number with “B” (ex. ACF-QCUB). All listed models include a back D-ring and sub-pelvic strap.

Miller AirCore™ Steel and Aluminum Harnesses

AirCore™ Harnesses (without Front D-Ring)

Miller AirCore™ Steel Harness							
Model Number	Side D-Rings	Shoulder D-Rings	Chest Strap	Leg Strap	Lumbar Pad	Removable Belt	Weight
AC-QC/UGN	No	No	Quick-Connect	Quick-Connect	No	No	4.0 lbs. (1.8 kg)
AC-TB/UGN	No	No		Tongue	No	No	4.0 lbs. (1.8 kg)
AC-QC-D/UGN	Yes	No		Quick-Connect	No	No	4.7 lbs. (2.1 kg)
AC-TB-D/UGN	Yes	No		Tongue	No	No	4.7 lbs. (2.1 kg)
AC-QC-BDP/UGN	Yes	No		Quick-Connect	Yes	Yes	6.1 lbs. (2.8 kg)
AC-TB-BDP/UGN	Yes	No		Tongue	Yes	Yes	6.1 lbs. (2.8 kg)
ACMB-TB/UGN	No	No	Mating Buckle	Tongue	No	No	4.0 lbs. (1.8 kg)
ACMB-TB-BDP/UGN	Yes	No		Tongue	Yes	Yes	6.1 lbs. (2.8 kg)
ACSD-QCUG	No	Yes	Quick-Connect	Quick-Connect	No	No	4.4 lbs. (2.0 kg)
ACSD-QCBDPUG	Yes	Yes		Quick-Connect	Yes	Yes	6.5 lbs. (2.9 kg)
Miller AirCore™ Aluminum Harness							
ACA-QC/UGN	No	No	Quick-Connect	Quick-Connect	No	No	3.6 lbs. (1.63 kg)
ACA-TB/UGN	No	No		Tongue	No	No	3.6 lbs. (1.63 kg)
ACA-QC-D/UGN	Yes	No		Quick-Connect	No	No	4.0 lbs. (1.81 kg)
ACA-TB-D/UGN	Yes	No		Tongue	No	No	4.0 lbs. (1.81 kg)
ACA-QC-BDP/UGN	Yes	No		Quick-Connect	Yes	Yes	5.4 lbs. (2.45 kg)
ACA-TB-BDP/UGN	Yes	No		Tongue	Yes	Yes	5.4 lbs. (2.45 kg)

Model numbers listed are **for size L/XL**. Harnesses are also available in **XS** through **4XL** by replacing the “U” in the model number with “**XS**” for Extra Small; “**SM**” for Small; “**2/3XL**” for 2/3 XL; and “**4X**” for 4XL. To order a blue harness, simply replace the “**GN**” in the model number with “**BL**” (ex. AC-QC/UBL). All listed models include a back D-ring and sub-pelvic strap.



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

⚠ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.