

## CSA Certified Vinyl-Coated Energy-Absorbing Lanyards

### Description

Miller Vinyl-Coated Shock-Absorbing Lanyards feature a special vinyl coating on the webbing to protect against a variety of liquids that could compromise overall performance. Miller Vinyl-Coated Products are effective in a wide range of applications, including food processing, petrochemical, water treatment, painting, billboards, and general industry.

### Materials

Webbing: Vinyl-coated 1" green webbing

#### SofStop Shock Absorber

- Webbing: Polyester

- Safety Strap

(Inside SofStop): Polyester

Locking Snap

Hook: Steel, 3/4 in. (19 mm) gate opening

Miller 5K Locking

Snap Hook: Steel, 3/4 in. (19 mm) gate opening

Thread: Polyester

*All hardware meets ASTM (50) fifty-hour salt spray test requirements.*

### Technical

CSA Approved

Max. Capacity Range: 120-335 lbs. (141 kg)

Maximum Elongation

Distance: 52 in. (in a 6 ft. drop)

*Non CSA Approved*

Max. Capacity Range: 100-385 lbs. (175 kg)

Maximum Elongation

Distance: 68 in. (in a 6 ft. drop)

Snap Hooks: 5,000 lbs. (22kN)

3/4" (19mm) gate opening

Rebar Hooks: 5,000 lbs. (22kN)

2 1/2 in. (63mm) gate opening

Fall Arrest Force: 1,800 lbs. max.

**See table on product for specific weight range and elongation distances.**

### Certification

Meets all CSA Z259.11-17 requirements.



M1FSFS-DS6C

## CSA Certified Vinyl-Coated Energy-Absorbing Lanyards

Model Number	Color	Number of Legs	Harness Connection	Anchorage Connection	Standard Length
M1FSFR-DS6C	Green	One	Standard Snap Hook	Standard Rebar (2")	6 ft. (1.8 m)
M1FSFS-DS6C	Green	One	Standard Snap Hook	Standard Snap Hook	6 ft. (1.8 m)
M2FSFC-DS4C	Green	Two	Standard Snap Hook	Large Rebar Hook	4 ft. (1.2 m)
M2FSFC-DS6C	Green	Two	Standard Snap Hook	Large Rebar Hook	6 ft. (1.8 m)
M2FSFS-DS6C	Green	Two	Standard Snap Hook	Standard Snap Hook	6 ft. (1.8 m)

*Locking Snap Hook – 3/4 in. (19 mm) gate opening; Locking Rebar Hook – 2 1/2-in. (64 mm) gate opening. Aluminum models available upon request. All connectors include 3,600-lb. gate-strength.*

**Limitless Possibilities. Ask the Expert.**

Technical Service: 800.873.5242  
www.millerfallprotection.com

**Honeywell Industrial Safety**


900 Douglas Pike  
Smithfield, RI 02917

**USA**

Phone: 800.430.5490  
Fax: 800.322.1330

**Canada**

Phone: 888.212.7233  
Fax: 888.667.8477

 This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.