

## Midas<sup>®</sup> SENSOR CARTRIDGE SPECIFICATIONS

### Phosphine (PH<sub>3</sub>)

### MIDAS-E-PHX



Gas Measured	Phosphines (PH <sub>3</sub> )
Cartridge Part Number	MIDAS-E-PHX 2 year extended warranty
Sensor Technology	3 electrode electrochemical cell
Measuring Range (ppm)	PH <sub>3</sub> 0 – 1.2ppm
Minimum Alarm 1 Set Point	0.15ppm
Lower Detectable Limit (LDL)	0.11ppm
Repeatability	< ± 5% of measured value
Linearity	< ± 20% of measured value
Response Time t <sub>92.5</sub>	≤5 seconds
Sensor Cartridge Life Expectancy	≥24 months under typical application conditions
Operating Temperature	0°C to + 40°C (32°C to 104°F)
Effect of Temperature Zero	< ± 0.02 ppm (0°C to 40°C)
Operating Humidity (continuous)	10 – 90% rH
Effect of Humidity Zero Sensitivity	< ± 0.0005 ppm / %rH < ± 0.1 % of measured value / %rH
Operating Pressure	90 – 110kPa
Effect of Position	No effect in typical application
Long Term Drift	< ± 5% of measured value / 6 month
Calibration Gas	Phosphine (PH <sub>3</sub> )
Challenge Gas (Bump Test)	Phosphine (PH <sub>3</sub> )
Warm Up Time	< 20 minutes
Storage Temperature	+5°C to +25°C (+41°F to +77°F)

#### Cross Sensitivities

Each Midas<sup>®</sup> sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration Applied (ppm)	Reading (ppm PH <sub>3</sub> )
Ammonia	NH <sub>3</sub>	108	<0.1
Arsine	AsH <sub>3</sub>	0.15	0.12
Carbon Dioxide	CO <sub>2</sub>	5000	0
Carbon Monoxide	CO	85	0
Chlorine	Cl <sub>2</sub>	0.85	<-0.05
Diborane	B <sub>2</sub> H <sub>6</sub>	0.2	0.01
Hydrocarbons	CH <sub>4</sub>	18000	0.0
Hydrogen	H <sub>2</sub>	3100	<0.05
Hydrogen Chloride	HCl	7.9	0
Hydrogen Cyanide	HCN	12.6	0.3
Hydrogen Fluoride	HF	7.2	0
Hydrogen Selenide	SeH <sub>2</sub>	0.85	0
Hydrogen Sulfide	H <sub>2</sub> S	18.2	0
Nitrogen Dioxide	NO <sub>2</sub>	10.1	-1.6
Propan-2-ol	C <sub>3</sub> H <sub>7</sub> OH	20000	<0.05
Silane	SiH <sub>4</sub>	3.5	0.4
Sulfur Dioxide	SO <sub>2</sub>	17.8	0

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed

#### Find out more

[www.honeywellanalytics.com](http://www.honeywellanalytics.com)

**Korea Tel:** +82 (0)2 6909 0300

**Singapore Tel:** +65-65803776

**Australia Tel:** +61-3-94642770

**Japan Tel:** +81-3-6730-7320

**India Tel:** +91-124 4752700

#### Technical Services

AP: [ha.ap.service@honeywell.com](mailto:ha.ap.service@honeywell.com)

EMEA: [ha.emea.service@honeywell.com](mailto:ha.emea.service@honeywell.com)

US: [ha.us.service@honeywell.com](mailto:ha.us.service@honeywell.com)

#### Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions.

Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.