



**Product Family**

**Uvex Ultra-spec 2001 OTG**

Lightweight over-the-glass design fits over most Rx eyewear. Adjustable Duoflex cushioned temples.

[Learn more about all of our Uvex plano products at uvex.us >](http://uvex.us)

[Learn more about our Uvex Rx safety frames at uvexrx.com >](http://uvexrx.com)



**Product Numbers & Ordering Information**

	Product Numbers	Details
	S0112	<b>Clear Frame</b> Clear Lens, Ultra-dura Anti-scratch Coating
	S0112C	<b>Clear Frame</b> Clear Lens, Uvextreme Anti-fog Coating
	S0113	<b>Gray Frame</b> Gray Lens, Ultra-dura Anti-scratch Coating
	S0113C	<b>Gray Frame</b> Gray Lens, Uvextreme Anti-fog Coating

**Packaging Information**

Ind. box, 10/stocker, 200/case

**Overview**

**Key Features**

- Lightweight over-the-glass unilens design fits over most Rx eyewear
- Adjustable Duoflex cushioned temples
- Made in USA

**Hazards**

- Abrasion
- Airborne Particulates
- Biohazard
- Impact

### Regulations

- ANSI Z87+ - Meets ANSI Z87+ (High Impact) standard
- ANSI Z87.1/1989, CA 18,833 - Meets ANSI Z87.1/1989, CA 18,833 ([http://www.mte.gov.br/Empregador/segsau/Pesquisa/CA\\_DET.asp?vNRCAProc=18833&Equipamento=00&NOEquipamento=&Fabricante=00&NOFabricante=](http://www.mte.gov.br/Empregador/segsau/Pesquisa/CA_DET.asp?vNRCAProc=18833&Equipamento=00&NOEquipamento=&Fabricante=00&NOFabricante=))
- CSA Z94.3 - Tested by Honeywell to meet the requirements of the CSA Z94.3 standard

### Historical Brand

Uvex

### Warranty Information

Limited warranty

## Specifications

#### Lens overall width

- 158 mm (6.2 nominal) "

#### Lens material

- Polycarbonate

#### Lens coating

- Ultra-dura,<sup>®</sup> Uvextreme<sup>®</sup> AF

#### Lens thickness

- 2.0 mm (.08 in) min

#### Available lens tints

- Clear, Gray

#### Replacement lenses available (yes/no)

- No

#### Rx capable

- No. Over-the-glass design fits over most Rx eyewear

#### Temple material

- Nylon

#### Temple length

- 110 mm (4.5) "

#### Temple set-back

- 100 mm (4.0) "

#### Temple style

- Duoflex<sup>®</sup> cushioned

#### Spectacle weight

- 44 grams (1.5 oz.) approx.

#### Frame material

- Not applicable

#### Available temple colors

- Black/Black

#### Dielectric frame (yes/no)

- Yes

#### Country of origin

- Made in U.S.A.

## Certifications

**ANSI Certificate of Compliance\_Eng**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Eye\\_and\\_Face\\_Protection/Laser\\_Filters\\_\\_\\_Eyewear/19294/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Laser_Filters___Eyewear/19294/1033.aspx)

ANSI Certificate of Compliance\_Eng

**ANSI Certificate of Compliance\_Spanish**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Eye\\_and\\_Face\\_Protection/Laser\\_Filters\\_\\_\\_Eyewear/19295/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Laser_Filters___Eyewear/19295/1033.aspx)

ANSI Certificate of Compliance\_Spanish

## Training & Proper Use

All products come packaged with instructions and warnings for proper use.

## Technical Support

(800) 682-0839, Sperian Protection Americas, Customer Care