



Product Family Miller Falcon Self-Retracting Lifelines

Pound for pound the strongest, most durable retractable. Lifeline available in 16-ft., 20-ft., 30-ft., 50-ft. and 65-ft. lengths.



Product Numbers & Ordering Information

	Product Numbers	Details
	MP16P/16FT	Web Lifeline; ANSI A10.32 Compliant 16-ft. [4.9m]; stainless steel swivel, aluminum carabiner and aluminum snap hook; 400 lbs. capacity
	MP16P-Z7/16FT	Web Lifeline; ANSI Z359 Compliant 16-ft. [4.9m]; stainless steel carabiner with swivel and stainless steel snap hook; 400 lbs. capacity
	MP20G/20FT	Cable Lifeline; ANSI A10.32 Compliant 20-ft. [6.1m] galvanized wire rope (3/16"); tagline and carabiner
	MP20G-Z7/20FT	Cable Lifeline; ANSI Z359 Compliant 20-ft. [6.1m] galvanized wire rope (3/16"); tagline and carabiner
	MP20P/20FT	Web Lifeline; ANSI A10.32 Compliant 20-ft [6.1m]; stainless steel swivel, aluminum carabiner and aluminum snap hook; 400 lbs. capacity
	MP20P-Z7/20FT	Web Lifeline; ANSI Z359 Compliant 20-ft [6.1m]; stainless steel swivel, aluminum carabiner and aluminum snap hook; 400 lbs. capacity
	MP20SS/20FT	Cable Lifeline; ANSI A10.32 Compliant 20-ft [6.1m]; stainless steel wire rope (3/16") with tagline and carabiner

Miller Falcon Self-Retracting Lifelines



MP30G/30FT

Cable Lifeline; ANSI A10.32 Compliant

30-ft [10m]; galvanized wire rope (3/16"); tagline and carabiner



MP30G-Z7/30FT

Cable Lifeline; ANSI Z359 Compliant

30-ft [10m]; galvanized wire rope (3/16"); tagline and carabiner



MP30SS/30FT

Cable Lifeline; ANSI A10.32 Compliant

30-ft [10m]; stainless steel wire rope (3/16"); tagline and carabiner



MP50G/50FT

Cable Lifeline; ANSI A10.32 Compliant

50-ft [15m]; galvanized wire rope (3/16"); tagline and carabiner



MP50G-Z7/50FT

Cable Lifeline; ANSI Z359 Compliant

50-ft [15m]; galvanized wire rope (3/16"); tagline and carabiner



MP50SS/50FT

Cable Lifeline; ANSI A10.32 Compliant

50-ft. [15m]; stainless steel wire rope (3/16"); tagline and carabiner



MP65G/65FT

Cable Lifeline; ANSI A10.32 Compliant

65-ft [20m]; galvanized wire rope (3/16"); tagline and carabiner



MP65G-Z7/65FT

Cable Lifeline; ANSI Z359 Compliant

65-ft [20m]; galvanized wire rope (3/16"); tagline and carabiner



MP65SS/65FT

Cable Lifeline; ANSI A10.32 Compliant

65-ft. [20m]; stainless steel wire rope (3/16"); tagline and carabiner

Overview

Key Features

- Corrosion-resistant stainless steel and aluminum internal components extend service life and reduce replacement costs
- Lightest composite unit on the market – easy to handle and transport to/from jobsites
- Unique side payout design reduces wear on the entry guide bushing and cable for smooth operation with less drag
- Smooth, quiet operation; engineered spring retraction tension designed not to pull or drag on a worker to improve productivity and reduce fatigue
- Built-in, ergonomically-designed molded handle on the 50-ft (15m) and 65-ft. (20m) cable units provide support and leverage when attaching C3811 anchorage connector. Easier to install. Dual swivels D3814 (unit top and snap hook) included on all cable models to minimize lifeline from twisting during use

Recommended Industries/Use

- Construction
- Steel and Metals
- Transportation
- Wind Energy

Hazards

- Confined Space
- Fall from height

Regulations

- Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

Falcon Cable Maximum Working Load

- Rated to 400 lbs. (181.4kg) capacity when using a SofStop shock absorber (928LS/18INYL)

Falcon Web Maximum Working Load

- Rated for up to 400 lbs. (181.4kg) worker

Load indicators (identifying when the unit needs to be removed from service)

- Cable models – on snap hook Web models – flag on webbing

Housing

- High impact-resistant nylon

Specification Sheets

- For full engineering specification sheets, go to the spec sheet section under downloads and documentation

Literature & Documents

Miller Falcon Brochure - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/20606/1033.aspx

Learn more about the Miller Falcon

Miller SRL Manual - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/15824/1033.aspx

Miller Self-Retracting Lifeline Instruction Manual

SP345 Falcon Web Spec Sheet - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/16183/1033.aspx

SP345 Falcon Web Spec Sheet

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 email: hsptechsupport@honeywell.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

© Honeywell International Inc.