

Miller 213 Series - Positioning/Restraint

Description

The 213 non shock absorbing lanyards are to be used for positioning only, unless it is used in conjunction with a shock absorber. The standard web lanyards are economical, abrasion resistant and easy to clean.

Materials

Webbing: 1" (25.4m) Polyester Webbing
Snap Hooks: Steel, 3/4" (19mm) gate opening
Thread: Six cord bonded, three strand polyester thread
Labels: Lexan and Valeron

*All hardware meets ASTM (50) fifty-hour salt spray test requirements

Technical

Max. Working Load: 310lbs (140.62kg)
Minimum Tensile
 - Lanyard Webbing: 5,000lbs (22kN)
 - Snap Hook: 5000lbs (22kN)
 - Thread: 42lbs (0.18kN)

Certification

Meets OSHA 1910.66, 1926.502(d), ANSI A10.32, Z359-2007* and CSA Z259.11 requirements.

*ANSI Z359-2007 compliant for connectors which meet the 3600lb gate requirements.



Model #	Description	Standard Length*
213WLS/6FTYL	Yellow web lanyard with two locking snap hooks	6ft (1.8m)
213TWDLS /6FTBL	Blue web lanyard with two locking snap hooks	6ft (1.8m)
213TWLS/6FTGN	Green web lanyard with two locking snap hooks	6ft (1.8m)
213TWLS-Z7/6FTGN	ANSI Z359-2007 compliant green web lanyard with two locking snap hooks	6ft (1.8m)

*Additional lengths are available.



Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.