

8175 Rope Grab Family - CANADA

Description

Lightweight, trailing rope grabs move easily up and down vertical lifelines to provide continuous fall protection. Trailing rope grabs offer complete hands-free operation for increased productivity. In the event of a fall, Miller rope grabs lock quickly.

For vertical applications, the rope grab design prevents installation in the wrong direction as well as includes anti-panic hardware.

Materials

Rope Grabs:	Stainless Steel
Attachments	
Rope Lanyard:	5/8" (16mm) Synthetic Rope
Web Lanyard:	Polyester
Snap Hook:	Clear Zinc Chromate Plated Forged Alloy Steel Proof tested to 3,600 lbs (16kN)

Technical

Min. Tensile Strength

Rope Grab:	3,600lbs (16kN)
Snap Hook:	5,000lbs (22.2kN)

Max Working Load:	310lbs (141kg)
Weights:	see chart
O-Ring Inner Diameter:	2.145" (54.4mm)



#8175/C

Certification

8175 Rope Grabs for Canada meet OSHA 1910.66, 1926.502, ANSI A10.32, Z359.1 and CSA Z 259.2.1-98 requirements.

Model #	Weight	Description
8175/C	1.62lb (0.73kg)	Stainless steel, trailing rope grab for use with 5/8" (16mm) synthetic rope
8175RLS/3FTWHC	2.57lb (1.16kg)	8175/C with attached 3ft (0.9m) rope lanyard with locking snap hook
8175WLS/3FTYLC	2.43lb (1.10kg)	8175/C with attached 3ft (0.9m) web lanyard with locking snap hook



Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.