



Product Family
Miller TurboLite Personal Fall Limiter (EUR)

Never need a shock-absorbing lanyard AGAIN with the 2m lightweight fall limiter adapted to all situations when working with a low space clearance!



Product Numbers & Ordering Information

	Product Numbers	Details
	1017900	TurboLite Web PFL webbing 2m Twistlock + Snaphook
	1018013	TurboLite Web PFL webbing 2m Twistlock + Scafhook
	1018014	TurboLite Web PFL webbing 2m Scafhook + Twistlock
	1018015	TurboLite Web PFL webbing 2m - 2 Twist lock carabiner

Overview

Key Features

Features :

- Built-in web load indicator identifies when the unit needs removed from services
- Compact and lightweight provides 2m working capacity lifeline
- Engineered webbing for greater abrasion resistance and long service life (vectran / polyester webbing).
- Lightweight, high-strength, impact-resistant nylon housing for maximum durability
- Built-in swivel prevents lifeline from twisting • No annual factory recertification required.
- Rated for up to a 136 kg user / Rated for up to a 100kg user (use in down level)

Benefit :

- Adapted to all situation when working with low space clearance.
- Can be used in Fall Factor 2 (below the back D ring and not lower than foot level).
- Can be used on both sides.
- Quick activating Patent Pending Braking System

Recommended Industries/Use

- Construction
- Utilities
- Wind Energy

Hazards

- Fall from height

Regulations

- Conforms to EN360

Warranty Information

Our state of the art equipment provides the critical tool for worker protection, combining mobility with unsurpassed comfort.

At our ISO 9001 certified manufacturing facilities in Europe, we ensure that every Miller product is made in accordance with the standards and meets your exacting requirements.

Literature & Documents

NT90022859 IND F

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/4294996658/1033.aspx

90022859 ind F 31/05/2016EN 3602IndexPicture guide 4EN English 7FR Franais . 11DE Deutsh . 16ES Espaol . 21PT Portugs . 26NL Nederlands . 31DA Dansk . 36FI Suomi . 41NO Norsk . 45SV Svenska . 49IT Italiano 53PL Polska 58RU Russian 62GENERAL MANUAL USER3HU Magyar . 67RO Romna . 72SK Slovenčina 77HR Hrvatski

Training & Proper Use

Training is an essential part of any safety program. The employer is responsible for ensuring that any person working at height is fully informed regarding the correct use of PPE and systems.

More information about the training...

Technical Support

Miller Techniserv

Northern and Central Europe

Phone: +49 (0) 9281/8302-205

Email: techniservnorth.hsp@honeywell.com

Southern Europe, UK, Ireland

Phone: +33 (0)2 48 52 40 42

Email: techniserv.hsp@honeywell.com



