

Technical Specifications

Söll MultiRail® Horizontal safety rail

**EN 795:2012
COMPLIANT**

Description:

The Söll MultiRail® horizontal safety rail is the main part of the MultiRail® system, which offers a high level of fall protection to people working in a fall risk area by complying with the latest European standard for horizontal rigid anchor rail systems. The rail is available in different lengths and has been designed to withstand high loads in order to enable usage for multiple workers at the same time.

References:

- 19146 / 1013480 (6m)
- 24401 / 1013485 (3m)
- 17488 / 1007120 (variable m)



Material:

- Stainless steel 316 (A4)



Technical characteristics:

- Recommended fixation distance: 4m
- Max. fixation distance: 6m
- Max. users: 6
- Max. deflection in case of a fall: 1250mm
- Breaking strength: >17kN
- Operating temperature: -50 to +90°C





by Honeywell

Order reference	Part number	Dimensions	Weight
19146	1013480	45x35x6000 mm	16,11 kg
24401	1013485	45x35x3000 mm	7,923 kg
17488	1007120	45x35x1000 mm	2,708 kg

Certifications:

- Söll MultiRail® components are tested according to EN 795:2012 type D and the additional tests CEN/TS 16415:2013

Quality control:

- Manufacturing according to EN ISO 9001
- Quality check for each part